

IES LM-79-19
MEASUREMENT AND TEST REPORT
For

GREEN CREATIVE LTD

519 Codisco Way, Sanford, FL 32771

Test Model: 11A19DIM/950/R

Report Type:	Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution
Project Engineer:	Bay Wang
Report Number:	RKSB211125008-10
Test Date:	2021-11-25 to 2021-11-28
Report Date:	2021-12-06
Reviewed By:	Seven Xia/ EE Engineer
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan). No. 248 Chenghu Road, Kunshan, Jiangsu Province, People's Republic of China Tel: +86-0512-86175000 Fax: +86-0512-88934268

1. Product Description

General Information:

One sample was received on 2021-11-25 and used for testing.

Model Tested: 11A19DIM/950/R
Manufacturer: GREEN CREATIVE LTD
Brand Name: GREEN CREATIVE
Product Designation: LED Lamp
Burning Time Before Test: 0hour (For New Products)

Rated Values:

Rated Voltage/Frequency: 11A19DIM/950/R
Rated Power: 11W
Nominal CCT: 5000K
Nominal Lumen Output: 1200lm

2. Standards Used

- IES LM-79-19: Approved Method: Optical and Electrical Measurements of Solid-state Lighting Products
- ANSI C82.77-10-2014: Harmonic Emission Limits – Related Power Quality Requirements for Lighting Equipment
- IES TM-30-18: IES Method for Evaluating Light Source Color Rendition

3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
2.0m integrating sphere	EVERFINE	R98	G121960CS1361154D	2021-11-02	2022-11-01
spectroradiometer	EVERFINE	HAAS-2000	M12048CS1361148	2021-11-02	2022-11-01
Digital CC&CV DC Power Supply	EVERFINE	WY305	G115986CN1361134	2021-11-02	2022-11-01
Thermal Meter	ANYMETRE	TH-20E	N/A	2020-11-30	2021-11-29
Standard Light Source	EVERFINE	D215S	G119786CS1361115	2021-09-15	2022-09-14
Digital Power Meter	YOKOGAWA	WT210	91KB35700	2021-11-13	2022-11-12
Intelligence ac power supply	EVERFINE	DPS1005	G119890CS1361121	2021-11-02	2022-11-01
AC Power Supply	INVENTFINE	CHP-5KVA	900511765	2021-11-02	2022-11-01
DC Power Supply	INVENTFINE	WL3010	JWDMP030001	2021-11-02	2022-11-01
Power Meter	INVENTFINE	WT500	GSDSQ200007	2021-03-16	2022-03-15
Goniophotometer	INVENTFINE	GPM-1900	YWGCF120001	2021-11-15	2022-11-14
Wireless Weather Station	ZHONGXING	KG218	N/A	2021-11-02	2022-11-01
Standard Light Source	INVENTFINE	N/A	JWBYR040008	2020-12-23	2021-12-22

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with ANSI/IES LM-79-19. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at $25^{\circ}\text{C} \pm 1.2^{\circ}\text{C}$ during measurement. And relative humidity is maintained between 10% than 65%.

Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

4π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is $U_{rel}=2.7\%$ ($k=2$), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is $U=27\text{K}$ ($k=2$), at the 95% confidence level. The uncertainty of the CRI is $U=2.7(k=2)$, at the 95% confidence level.

The uncertainty of power meter AC current $U_{rel}=0.27\%$ of rdg, AC Voltage $U_{rel}=0.26\%$ of rdg, Power $U_{rel}=0.41\%$ ($k=2$), at the 95% confidence level.

Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. For measurement of luminous intensity distribution, the horizontal angle (C plane) test intervals were set 22.5 degree, the vertical angle (γ) test intervals were set 1 degree while data for 5 degree intervals is reported.

The uncertainty of the luminous flux is $U_{rel}=2.6\%$ ($k=2$), at the 95% confidence level.

Fidelity Index and Gamut Index Calculation

The R_i , R_g was calculated according to IES TM-30-18 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

5. Test Result

[Integrating Sphere System]

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Downward**


Photometric and Electrical Measurement Result







Voltage(V)	Frequency(Hz)	Current(A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy(lm/W)
120.1	60	0.1081	10.42	0.8027	1208.6	115.98

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
3.816	4809	0.000771	0.3509	0.3578	0.2130	0.4885


Color Rendering Index

Ra			
95.7			
R1	R2	R3	R4
98	97	89	95
R5	R6	R7	R8
99	94	97	97
R9	R10	R11	R12
97	89	92	73
R13	R14	R15	
99	93	97	






Relative Spectral Power Distribution




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
380	7.025E-01	421	2.431E+00	462	1.612E+01	503	1.410E+01	544	1.804E+01
381	5.130E-01	422	2.661E+00	463	1.534E+01	504	1.441E+01	545	1.802E+01
382	3.656E-01	423	2.928E+00	464	1.470E+01	505	1.474E+01	546	1.801E+01
383	4.954E-01	424	3.195E+00	465	1.405E+01	506	1.504E+01	547	1.797E+01
384	5.496E-01	425	3.529E+00	466	1.355E+01	507	1.529E+01	548	1.787E+01
385	5.800E-01	426	3.856E+00	467	1.291E+01	508	1.556E+01	549	1.784E+01
386	4.487E-01	427	4.292E+00	468	1.231E+01	509	1.581E+01	550	1.787E+01
387	4.145E-01	428	4.693E+00	469	1.179E+01	510	1.607E+01	551	1.780E+01
388	3.327E-01	429	5.115E+00	470	1.119E+01	511	1.629E+01	552	1.769E+01
389	2.862E-01	430	5.596E+00	471	1.065E+01	512	1.646E+01	553	1.772E+01
390	3.691E-01	431	6.090E+00	472	1.011E+01	513	1.668E+01	554	1.762E+01
391	2.573E-01	432	6.634E+00	473	9.720E+00	514	1.688E+01	555	1.761E+01
392	2.746E-01	433	7.221E+00	474	9.273E+00	515	1.701E+01	556	1.750E+01
393	3.136E-01	434	7.812E+00	475	8.938E+00	516	1.716E+01	557	1.744E+01
394	2.201E-01	435	8.513E+00	476	8.597E+00	517	1.729E+01	558	1.737E+01
395	3.016E-01	436	9.233E+00	477	8.362E+00	518	1.742E+01	559	1.730E+01
396	2.880E-01	437	1.007E+01	478	8.188E+00	519	1.748E+01	560	1.720E+01
397	2.671E-01	438	1.100E+01	479	8.154E+00	520	1.761E+01	561	1.718E+01
398	2.849E-01	439	1.191E+01	480	8.109E+00	521	1.771E+01	562	1.710E+01
399	3.277E-01	440	1.306E+01	481	8.090E+00	522	1.782E+01	563	1.700E+01
400	3.502E-01	441	1.425E+01	482	8.142E+00	523	1.787E+01	564	1.694E+01
401	3.801E-01	442	1.547E+01	483	8.239E+00	524	1.797E+01	565	1.687E+01
402	3.565E-01	443	1.693E+01	484	8.361E+00	525	1.800E+01	566	1.673E+01
403	3.632E-01	444	1.847E+01	485	8.507E+00	526	1.804E+01	567	1.668E+01
404	3.612E-01	445	2.009E+01	486	8.644E+00	527	1.805E+01	568	1.656E+01
405	4.303E-01	446	2.166E+01	487	8.842E+00	528	1.813E+01	569	1.648E+01
406	4.478E-01	447	2.328E+01	488	9.043E+00	529	1.813E+01	570	1.637E+01
407	4.809E-01	448	2.477E+01	489	9.332E+00	530	1.816E+01	571	1.627E+01
408	5.778E-01	449	2.600E+01	490	9.546E+00	531	1.815E+01	572	1.616E+01
409	6.315E-01	450	2.699E+01	491	9.853E+00	532	1.821E+01	573	1.604E+01
410	7.522E-01	451	2.748E+01	492	1.013E+01	533	1.817E+01	574	1.591E+01
411	7.488E-01	452	2.745E+01	493	1.045E+01	534	1.819E+01	575	1.581E+01
412	8.945E-01	453	2.711E+01	494	1.077E+01	535	1.821E+01	576	1.570E+01
413	1.019E+00	454	2.610E+01	495	1.115E+01	536	1.818E+01	577	1.559E+01
414	1.141E+00	455	2.498E+01	496	1.151E+01	537	1.818E+01	578	1.545E+01
415	1.275E+00	456	2.340E+01	497	1.188E+01	538	1.814E+01	579	1.538E+01
416	1.406E+00	457	2.201E+01	498	1.225E+01	539	1.816E+01	580	1.523E+01
417	1.595E+00	458	2.052E+01	499	1.263E+01	540	1.815E+01	581	1.514E+01
418	1.770E+00	459	1.915E+01	500	1.306E+01	541	1.815E+01	582	1.503E+01
419	1.995E+00	460	1.799E+01	501	1.343E+01	542	1.816E+01	583	1.502E+01
420	2.184E+00	461	1.698E+01	502	1.372E+01	543	1.810E+01	584	1.500E+01

nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
585	1.493E+01	626	1.504E+01	667	3.045E+00	708	8.429E-01	749	2.738E-01
586	1.483E+01	627	1.589E+01	668	3.050E+00	709	8.120E-01	750	2.555E-01
587	1.473E+01	628	2.050E+01	669	3.197E+00	710	7.901E-01	751	2.566E-01
588	1.458E+01	629	3.703E+01	670	3.122E+00	711	7.652E-01	752	2.580E-01
589	1.437E+01	630	5.885E+01	671	2.902E+00	712	7.558E-01	753	2.614E-01
590	1.423E+01	631	5.938E+01	672	2.717E+00	713	7.361E-01	754	2.496E-01
591	1.406E+01	632	4.074E+01	673	2.585E+00	714	7.125E-01	755	2.523E-01
592	1.384E+01	633	3.104E+01	674	2.430E+00	715	6.898E-01	756	2.465E-01
593	1.370E+01	634	3.981E+01	675	2.322E+00	716	6.722E-01	757	2.356E-01
594	1.349E+01	635	4.274E+01	676	2.236E+00	717	6.622E-01	758	2.423E-01
595	1.344E+01	636	2.933E+01	677	2.175E+00	718	6.243E-01	759	2.410E-01
596	1.352E+01	637	1.680E+01	678	2.101E+00	719	6.111E-01	760	2.436E-01
597	1.387E+01	638	1.119E+01	679	2.018E+00	720	5.901E-01	761	2.220E-01
598	1.396E+01	639	8.964E+00	680	1.936E+00	721	5.958E-01	762	2.141E-01
599	1.363E+01	640	7.931E+00	681	1.864E+00	722	5.643E-01	763	2.205E-01
600	1.337E+01	641	7.423E+00	682	1.800E+00	723	5.457E-01	764	2.212E-01
601	1.328E+01	642	7.092E+00	683	1.764E+00	724	5.408E-01	765	2.218E-01
602	1.325E+01	643	6.933E+00	684	1.716E+00	725	5.265E-01	766	2.081E-01
603	1.330E+01	644	6.875E+00	685	1.649E+00	726	5.015E-01	767	2.132E-01
604	1.332E+01	645	7.887E+00	686	1.625E+00	727	4.838E-01	768	1.986E-01
605	1.332E+01	646	1.162E+01	687	1.575E+00	728	4.668E-01	769	1.854E-01
606	1.392E+01	647	1.493E+01	688	1.513E+00	729	4.564E-01	770	1.969E-01
607	1.700E+01	648	1.283E+01	689	1.484E+00	730	4.325E-01	771	2.011E-01
608	2.146E+01	649	8.943E+00	690	1.441E+00	731	4.365E-01	772	2.034E-01
609	2.142E+01	650	7.033E+00	691	1.401E+00	732	4.171E-01	773	2.110E-01
610	1.808E+01	651	6.607E+00	692	1.348E+00	733	4.127E-01	774	1.868E-01
611	1.918E+01	652	6.435E+00	693	1.317E+00	734	4.087E-01	775	1.761E-01
612	2.812E+01	653	5.945E+00	694	1.279E+00	735	4.015E-01	776	1.799E-01
613	3.574E+01	654	5.441E+00	695	1.228E+00	736	3.814E-01	777	1.719E-01
614	3.181E+01	655	5.175E+00	696	1.213E+00	737	3.780E-01	778	1.656E-01
615	2.262E+01	656	4.959E+00	697	1.171E+00	738	3.601E-01	779	1.659E-01
616	1.708E+01	657	4.613E+00	698	1.125E+00	739	3.488E-01	780	1.662E-01
617	1.515E+01	658	4.329E+00	699	1.100E+00	740	3.362E-01		
618	1.490E+01	659	4.206E+00	700	1.071E+00	741	3.349E-01		
619	1.492E+01	660	4.079E+00	701	1.026E+00	742	3.168E-01		
620	1.442E+01	661	3.905E+00	702	1.015E+00	743	3.293E-01		
621	1.378E+01	662	3.622E+00	703	9.702E-01	744	3.055E-01		
622	1.350E+01	663	3.430E+00	704	9.632E-01	745	3.043E-01		
623	1.382E+01	664	3.276E+00	705	9.216E-01	746	2.871E-01		
624	1.439E+01	665	3.174E+00	706	8.867E-01	747	2.945E-01		
625	1.475E+01	666	3.099E+00	707	8.641E-01	748	2.836E-01		

CIE 1931xy Chromaticity Diagram



7-Step Chromaticity Quadrangles



[Goniophotometer System]

Total operating time for luminous intensity distribution: **1.0hour**

Test orientation: **Downward**


Electrical Measurement

Input Voltage(V)	Frequency(Hz)	Input Current(A)	Power (W)	Power Factor
120.0	60	0.108	10.36	0.801

Photometric Measurement

Luminous Flux(lm)	Efficacy(lm/W)	$I_{max}(cd)$	S/MH(C0/180)	S/MH(C90/270)
1208.6	116.71	179.4	1.46	1.45

Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle(50% I_{max}):	187.7	188.7	188.5	187.0	188.0
Field Angle(10% I_{max}):	312.1	314.7	317.6	315.5	315.0

Luminous Intensity (cd) Distribution Data

$\gamma \backslash C$	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	175.5	175.5	175.5	175.5	175.5	175.5	175.5	175.5
5.0°	174.1	174.6	175.1	175.7	176.1	176.6	177.1	177.0
10.0°	173.0	173.6	174.3	175.5	176.4	177.2	178.1	178.2
15.0°	171.4	172.2	173.3	174.8	176.4	177.8	179.0	179.0
20.0°	169.5	170.4	171.9	173.8	175.7	177.8	179.2	179.4
25.0°	167.5	168.5	170.0	172.4	174.7	177.2	178.8	179.1
30.0°	164.8	166.0	167.7	170.3	173.1	175.8	177.7	178.1
35.0°	161.7	162.8	164.6	167.5	170.4	173.6	175.7	175.9
40.0°	157.9	159.0	160.8	163.8	167.0	170.2	172.3	172.7
45.0°	153.5	154.5	156.2	159.1	162.4	165.8	168.1	168.3
50.0°	148.5	149.5	151.1	153.7	157.1	160.5	162.7	162.6
55.0°	142.8	143.7	145.2	147.7	151.0	154.4	156.5	156.3
60.0°	136.6	137.5	138.8	141.2	144.1	147.3	149.3	149.0
65.0°	130.2	130.9	132.2	134.2	137.1	139.6	141.5	141.3
70.0°	123.3	123.9	125.0	126.9	129.2	131.6	133.1	132.7
75.0°	116.2	116.8	117.9	119.3	121.5	123.4	124.6	124.3
80.0°	109.0	109.6	110.5	111.9	113.4	115.0	116.0	115.5
85.0°	101.8	102.5	103.2	104.4	105.5	106.7	107.3	106.9
90.0°	94.4	95.0	95.7	96.7	97.7	98.5	98.9	98.5
95.0°	87.2	87.6	88.0	88.8	89.5	90.0	90.2	90.0
100.0°	79.8	80.1	80.7	81.3	81.8	82.1	82.2	81.9
105.0°	72.6	73.0	73.4	74.0	74.3	74.4	74.4	74.1
110.0°	65.8	66.2	66.7	67.0	67.2	67.2	67.1	66.9
115.0°	59.2	59.6	60.0	60.3	60.4	60.4	60.2	60.0
120.0°	53.1	53.5	53.9	54.2	54.2	54.1	53.9	53.7
125.0°	47.4	47.8	48.0	48.3	48.3	48.1	48.0	48.0
130.0°	42.0	42.4	42.6	42.8	42.8	42.7	42.6	42.5
135.0°	36.9	37.2	37.5	37.6	37.6	37.5	37.4	37.4
140.0°	32.0	32.3	32.6	32.8	32.7	32.7	32.6	32.5
145.0°	27.7	27.9	28.2	28.3	28.3	28.3	28.2	28.2
150.0°	23.7	23.9	23.6	24.3	24.3	24.2	24.1	23.9
155.0°	20.0	20.3	18.9	15.5	20.7	20.5	20.1	19.2
160.0°	16.7	16.9	13.5	15.8	16.7	16.7	16.2	14.5
165.0°	13.3	12.9	8.9	12.4	12.9	12.5	11.9	8.0
170.0°	8.4	7.7	6.1	6.8	6.7	7.5	5.9	10.4
175.0°	3.0	3.1	2.0	1.2	2.4	3.0	4.3	3.0
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Luminous Intensity (cd) Distribution Data (cont.)

$\begin{matrix} C \\ \backslash \\ y \end{matrix}$	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	175.5	175.5	175.5	175.5	175.5	175.5	175.5	175.5
5.0°	176.6	176.4	175.6	175.3	174.6	174.2	174.2	174.0
10.0°	177.6	176.7	175.6	174.7	173.5	172.9	172.6	172.6
15.0°	178.1	177.0	175.1	173.7	172.4	171.3	170.8	170.6
20.0°	178.1	176.4	174.3	172.4	170.5	169.5	169.0	168.9
25.0°	177.7	175.6	172.8	170.5	168.6	167.3	166.7	166.7
30.0°	176.2	173.6	170.5	168.0	165.9	164.7	164.0	163.9
35.0°	173.8	170.8	167.5	164.8	162.6	161.4	160.8	160.8
40.0°	170.2	167.1	163.5	160.7	158.6	157.3	156.9	157.0
45.0°	165.6	162.1	158.6	155.9	153.8	152.8	152.4	152.4
50.0°	160.1	156.6	152.9	150.3	148.6	147.5	147.1	147.2
55.0°	153.4	150.0	146.6	144.2	142.5	141.7	141.4	141.5
60.0°	146.2	142.9	139.7	137.5	136.2	135.4	135.1	135.4
65.0°	138.4	135.4	132.3	130.5	129.2	128.6	128.6	128.8
70.0°	129.9	127.1	124.5	123.1	122.2	121.6	121.5	121.8
75.0°	121.3	118.9	116.7	115.4	114.8	114.3	114.3	114.5
80.0°	112.7	110.7	108.9	107.8	107.2	106.9	106.9	107.2
85.0°	104.2	102.6	101.0	100.2	99.7	99.4	99.4	99.9
90.0°	95.7	94.4	93.4	92.8	92.2	92.1	92.1	92.4
95.0°	87.6	86.6	85.9	85.3	85.0	84.9	84.8	85.0
100.0°	79.8	79.2	78.6	78.2	77.9	77.7	77.8	77.9
105.0°	72.6	72.1	71.6	71.2	71.1	70.8	70.8	71.1
110.0°	65.6	65.3	64.9	64.7	64.5	64.4	64.2	64.4
115.0°	59.0	58.8	58.6	58.5	58.3	58.0	58.0	58.2
120.0°	53.0	52.9	52.7	52.5	52.4	52.1	52.0	52.2
125.0°	47.1	47.0	47.0	47.0	46.7	46.5	46.4	46.4
130.0°	41.8	41.9	41.7	41.7	41.5	41.2	41.1	41.2
135.0°	36.8	36.9	36.9	36.8	36.5	36.3	36.1	36.1
140.0°	32.2	32.2	32.2	32.2	31.9	31.7	31.5	31.5
145.0°	27.9	27.9	27.9	27.8	27.6	27.4	27.2	27.2
150.0°	23.8	23.4	23.9	23.8	23.6	23.4	23.2	23.2
155.0°	14.8	18.4	20.2	20.3	20.1	19.9	19.7	19.7
160.0°	10.4	14.9	16.3	17.0	16.9	16.4	16.4	16.6
165.0°	14.4	11.9	12.5	12.6	13.2	12.4	12.6	13.2
170.0°	10.1	8.5	8.1	7.6	4.7	7.8	8.3	8.7
175.0°	3.0	2.0	1.2	1.2	1.1	1.2	1.1	1.4
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Zonal Lumen Density Measurement

Deg	Flux (lm)	%
0-5	4.2	0.34
5-10	12.5	1.04
10-15	20.8	1.72
15-20	28.7	2.37
20-25	36.3	3.00
25-30	43.3	3.58
30-35	49.6	4.10
35-40	55.0	4.57
40-45	59.6	4.93
45-50	63.0	5.22
50-55	65.4	5.41
55-60	66.7	5.51
60-65	66.7	5.52
65-70	65.8	5.44
70-75	64.0	5.29
75-80	61.3	5.05
80-85	58.0	4.80
85-90	54.2	4.48
90-95	49.9	4.14
95-100	45.4	3.76
100-105	40.8	3.37
105-110	36.1	2.99
110-115	31.7	2.61
115-120	27.3	2.26
120-125	23.2	1.92
125-130	19.4	1.61
130-135	16.0	1.32
135-140	12.8	1.05
140-145	10.0	0.83
145-150	7.5	0.63
150-155	5.5	0.45
155-160	3.7	0.31
160-165	2.4	0.19
165-170	1.2	0.10
170-175	0.4	0.03
175-180	0.0	0.00

Deg	Flux (lm)	%
0-5	4.2	0.35
0-10	16.7	1.38
0-15	37.5	3.10
0-20	66.2	5.48
0-25	102.4	8.48
0-30	145.7	12.06
0-35	195.4	16.17
0-40	250.6	20.73
0-45	310.3	25.67
0-50	373.4	30.89
0-55	438.8	36.31
0-60	505.5	41.82
0-65	572.2	47.34
0-70	637.9	52.78
0-75	701.8	58.07
0-80	763.1	63.13
0-85	821.0	67.93
0-90	875.2	72.41
0-95	925.1	76.54
0-100	970.5	80.30
0-105	1011.3	83.67
0-110	1047.5	86.66
0-115	1079.1	89.28
0-120	1106.4	91.54
0-125	1129.6	93.46
0-130	1149.1	95.07
0-135	1165.1	96.39
0-140	1177.9	97.45
0-145	1187.9	98.28
0-150	1195.5	98.91
0-155	1201.0	99.37
0-160	1204.7	99.67
0-165	1207.0	99.87
0-170	1208.2	99.96
0-175	1208.6	100.00
0-180	1208.6	100.00

6. Product Photo



Directions

1. The information marked "superscript #" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
2. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
3. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of the Company.
6. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

*****END OF REPORT*****