



ANSI/IES LM-79-19

MEASUREMENT AND TEST REPORT

For

GREEN CREATIVE LTD

Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong, China

Test Model: 15.5PAR38DIM/927FL40/SL+SL25D

Report Type:	Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution, THD
Reviewed By:	Hill Liu Hill Liu
Report Number:	KS2230727-43670E-EE
Test Date:	2023-08-09 to 2023-08-12
Report Date:	2023-08-25
Approved by:	Blake Zhang / EE Engineer
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 5/F(B-West) -7/F, the 3rd Phase of Wan Li Industrial Building D, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China. Tel: +86-755-33320018 Fax: +86-755-33320008
Test Facility:	Test facility was located at No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China.

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.(Shenzhen). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

1. Product Description#

General Information:

Two test samples were in good condition and received on 2023-07-27. One was tested in integrating sphere and the other was tested in goniophotometer

Model Tested: 15.5PAR38DIM/927FL40/SL+SL25D
 Manufacturer: GREEN CREATIVE LTD
 Brand Name: GREEN CREATIVE
 Product Designation: Directional LED Lamp
 Burning Time Before Test: 0hour(For New Products)

Rated Values:

Rated Voltage/Frequency: 120V AC 60Hz
 Rated Power: 15.5W
 Nominal CCT: 2700K
 Nominal Lumen Output: 1320lm

Family Declaration

The Model	Multiple Models	Differences Items	Details
15.5PAR38DIM/927FL40/SL+SL25D	15.5PAR38DIM/927NF25/SL	Model Number	15.5PAR38DIM/927FL40/SL+SL25D & 15.5PAR38DIM/927NF25/SL are the same product except for the model number.

2. Standards Used

- ANSI/IES LM-79-19: Approved method: Optical and Electrical Measurements of Solid-State Lighting Products
- ANSI C82.77-10-2014: Harmonic Emission Limits – Related Power Quality Requirements for Lighting
- *IES TM-30-18: IES Method for Evaluating Light Source Color Rendition (This method is not in NVLAP accreditation scope)

3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
2.0m integrating sphere	EVERFINE	R98	11010018	2022-11-10	2023-11-09
spectroradiometer	EVERFINE	HAAS-2000	G112048TS81331121	2022-11-10	2023-11-09
Digital Power Meter	EVERFINE	PF2010A	1011004	2022-11-10	2023-11-09
Digital CC&CV DC Power Supply	EVERFINE	WY305-V1	1101047	2022-11-10	2023-11-09
Standard Light Source	EVERFINE	D204	N/A	2023-05-12	2025-05-11
Special zero-voltage synchronous switching AC	EVERFINE	DPS1010-YF	1011001T	2022-11-10	2023-11-09
AC POWER SUPPLY	EVERFINE	VPS1030 PWM	1012017	2022-11-16	2023-11-15
Digital CC&CV DC Power Supply	EVERFINE	WY12010	1009009	2022-11-10	2023-11-09
Digital power meter	YOKOGAWA	WT-210	91j926132	2022-11-10	2023-11-09
full-field speed goniophotometer	EVERFINE	GO-R5000	YG108492N10120001	2022-11-10	2023-11-09
wireless remote thermohygrometer	N/A	AOK-5017B	N/A	2022-11-10	2023-11-09
Standard Light Source	EVERFINE	D908	1012003	2023-05-12	2025-05-11

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with ANSI/IES LM-79-19. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at $25^{\circ}\text{C}\pm 1.2^{\circ}\text{C}$ during measurement. And relative humidity is maintained between 10% and 65%. The air flow around the SSL product is less than 0.2m/s.

Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

4π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is $U=2.1\%$ ($K=2$), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is $U=22\text{K}$ ($K=2$), at the 95% confidence level. The uncertainty of the CRI is $U=2.1(K=2)$, at the 95% confidence level.

The uncertainty of power meter AC current $U=0.19\%$ of rdg, AC Voltage $U=0.18\%$ of rdg, Power $U=0.46\%$ ($K=2$), at the 95% confidence level.

Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The vertical angle (γ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

The uncertainty of the luminous intensity is $U=2.00\%$ ($K=2$), at the 95% confidence level.

Additional Test

The Additional Test item may not be covered by ANSI/IES LM-79-2019. Additional test including power factor, off-state power and THD, was measured by Digital Power Meter after stabilized at $25^{\circ}\text{C}\pm 1.2^{\circ}\text{C}$. Test voltage for THD and power factor test would be equal to rated voltage or, in case of a voltage range, maximum value of that range.

The uncertainty of power meter AC current $U=0.19\%$ of rdg, AC Voltage $U=0.18\%$ of rdg, Power $U=0.46\%$ ($K=2$), at the 95% confidence level.

Fidelity Index and Gamut Index Calculation

The R_i , R_g was calculated according to IES TM-30-18 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

5. Test Result

[Integrating Sphere System]

The Stabilization time: **30 minutes**

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Base Up**


Photometric and Electrical Measurement Result







Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.1328	15.38	0.9648	1336.4	86.91

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
5.1472	2711	-0.00023	0.4586	0.4097	0.2621	0.5268


Color Rendering Index

Ra			
97.9			
R1	R2	R3	R4
99	99	99	99
R5	R6	R7	R8
99	97	96	94
R9	R10	R11	R12
87	100	98	89
R13	R14	R15	
99	98	98	






Relative Spectral Power Distribution




nm	mW								
380	3.465E-01	421	7.219E-01	462	9.096E+00	503	1.011E+01	544	1.604E+01
381	3.141E-01	422	7.837E-01	463	8.737E+00	504	1.030E+01	545	1.614E+01
382	2.927E-01	423	8.578E-01	464	8.466E+00	505	1.047E+01	546	1.626E+01
383	2.897E-01	424	9.381E-01	465	8.221E+00	506	1.065E+01	547	1.639E+01
384	2.370E-01	425	1.020E+00	466	8.048E+00	507	1.083E+01	548	1.650E+01
385	2.245E-01	426	1.111E+00	467	7.916E+00	508	1.099E+01	549	1.662E+01
386	2.054E-01	427	1.205E+00	468	7.819E+00	509	1.116E+01	550	1.671E+01
387	1.819E-01	428	1.312E+00	469	7.741E+00	510	1.132E+01	551	1.685E+01
388	1.846E-01	429	1.409E+00	470	7.666E+00	511	1.146E+01	552	1.694E+01
389	1.578E-01	430	1.519E+00	471	7.584E+00	512	1.163E+01	553	1.704E+01
390	1.529E-01	431	1.642E+00	472	7.495E+00	513	1.179E+01	554	1.714E+01
391	1.415E-01	432	1.775E+00	473	7.403E+00	514	1.192E+01	555	1.725E+01
392	1.336E-01	433	1.906E+00	474	7.303E+00	515	1.208E+01	556	1.735E+01
393	1.358E-01	434	2.040E+00	475	7.161E+00	516	1.225E+01	557	1.745E+01
394	1.149E-01	435	2.187E+00	476	7.042E+00	517	1.237E+01	558	1.755E+01
395	1.158E-01	436	2.348E+00	477	6.924E+00	518	1.251E+01	559	1.765E+01
396	1.171E-01	437	2.524E+00	478	6.837E+00	519	1.267E+01	560	1.776E+01
397	1.196E-01	438	2.705E+00	479	6.777E+00	520	1.281E+01	561	1.785E+01
398	1.187E-01	439	2.911E+00	480	6.718E+00	521	1.294E+01	562	1.797E+01
399	1.258E-01	440	3.127E+00	481	6.718E+00	522	1.308E+01	563	1.805E+01
400	1.241E-01	441	3.355E+00	482	6.760E+00	523	1.323E+01	564	1.816E+01
401	1.267E-01	442	3.633E+00	483	6.800E+00	524	1.336E+01	565	1.826E+01
402	1.295E-01	443	3.909E+00	484	6.902E+00	525	1.349E+01	566	1.836E+01
403	1.411E-01	444	4.253E+00	485	7.011E+00	526	1.363E+01	567	1.846E+01
404	1.368E-01	445	4.634E+00	486	7.130E+00	527	1.377E+01	568	1.858E+01
405	1.528E-01	446	5.065E+00	487	7.267E+00	528	1.390E+01	569	1.867E+01
406	1.670E-01	447	5.532E+00	488	7.406E+00	529	1.404E+01	570	1.880E+01
407	1.767E-01	448	6.086E+00	489	7.577E+00	530	1.418E+01	571	1.890E+01
408	1.952E-01	449	6.660E+00	490	7.734E+00	531	1.431E+01	572	1.900E+01
409	2.132E-01	450	7.266E+00	491	7.888E+00	532	1.445E+01	573	1.913E+01
410	2.418E-01	451	7.900E+00	492	8.065E+00	533	1.459E+01	574	1.925E+01
411	2.520E-01	452	8.504E+00	493	8.225E+00	534	1.473E+01	575	1.937E+01
412	2.853E-01	453	9.062E+00	494	8.408E+00	535	1.486E+01	576	1.952E+01
413	3.130E-01	454	9.547E+00	495	8.571E+00	536	1.499E+01	577	1.964E+01
414	3.509E-01	455	9.922E+00	496	8.760E+00	537	1.513E+01	578	1.977E+01
415	3.952E-01	456	1.017E+01	497	8.961E+00	538	1.525E+01	579	1.994E+01
416	4.355E-01	457	1.026E+01	498	9.137E+00	539	1.539E+01	580	2.010E+01
417	4.815E-01	458	1.020E+01	499	9.310E+00	540	1.551E+01	581	2.026E+01
418	5.357E-01	459	1.004E+01	500	9.515E+00	541	1.567E+01	582	2.043E+01
419	5.941E-01	460	9.775E+00	501	9.698E+00	542	1.578E+01	583	2.061E+01
420	6.548E-01	461	9.452E+00	502	9.909E+00	543	1.590E+01	584	2.078E+01

nm	mW								
585	2.099E+01	626	3.045E+01	667	2.461E+01	708	1.097E+01	749	3.640E+00
586	2.119E+01	627	3.052E+01	668	2.428E+01	709	1.070E+01	750	3.535E+00
587	2.140E+01	628	3.061E+01	669	2.393E+01	710	1.045E+01	751	3.438E+00
588	2.164E+01	629	3.069E+01	670	2.359E+01	711	1.019E+01	752	3.342E+00
589	2.188E+01	630	3.075E+01	671	2.325E+01	712	9.945E+00	753	3.248E+00
590	2.211E+01	631	3.076E+01	672	2.288E+01	713	9.700E+00	754	3.155E+00
591	2.235E+01	632	3.080E+01	673	2.255E+01	714	9.460E+00	755	3.066E+00
592	2.260E+01	633	3.082E+01	674	2.218E+01	715	9.218E+00	756	2.977E+00
593	2.286E+01	634	3.084E+01	675	2.182E+01	716	8.989E+00	757	2.892E+00
594	2.309E+01	635	3.080E+01	676	2.147E+01	717	8.767E+00	758	2.816E+00
595	2.337E+01	636	3.082E+01	677	2.111E+01	718	8.550E+00	759	2.732E+00
596	2.360E+01	637	3.074E+01	678	2.074E+01	719	8.330E+00	760	2.659E+00
597	2.384E+01	638	3.071E+01	679	2.039E+01	720	8.119E+00	761	2.577E+00
598	2.409E+01	639	3.063E+01	680	2.002E+01	721	7.908E+00	762	2.499E+00
599	2.438E+01	640	3.059E+01	681	1.968E+01	722	7.712E+00	763	2.433E+00
600	2.468E+01	641	3.049E+01	682	1.932E+01	723	7.501E+00	764	2.357E+00
601	2.495E+01	642	3.040E+01	683	1.895E+01	724	7.306E+00	765	2.290E+00
602	2.521E+01	643	3.031E+01	684	1.860E+01	725	7.111E+00	766	2.221E+00
603	2.551E+01	644	3.019E+01	685	1.823E+01	726	6.920E+00	767	2.158E+00
604	2.576E+01	645	3.006E+01	686	1.789E+01	727	6.731E+00	768	2.096E+00
605	2.604E+01	646	2.990E+01	687	1.754E+01	728	6.556E+00	769	2.035E+00
606	2.632E+01	647	2.976E+01	688	1.720E+01	729	6.377E+00	770	1.980E+00
607	2.658E+01	648	2.959E+01	689	1.686E+01	730	6.207E+00	771	1.921E+00
608	2.683E+01	649	2.940E+01	690	1.652E+01	731	6.032E+00	772	1.869E+00
609	2.709E+01	650	2.922E+01	691	1.618E+01	732	5.868E+00	773	1.813E+00
610	2.736E+01	651	2.902E+01	692	1.584E+01	733	5.711E+00	774	1.763E+00
611	2.760E+01	652	2.882E+01	693	1.551E+01	734	5.548E+00	775	1.709E+00
612	2.787E+01	653	2.860E+01	694	1.517E+01	735	5.397E+00	776	1.660E+00
613	2.812E+01	654	2.838E+01	695	1.486E+01	736	5.243E+00	777	1.611E+00
614	2.835E+01	655	2.812E+01	696	1.452E+01	737	5.095E+00	778	1.565E+00
615	2.859E+01	656	2.788E+01	697	1.422E+01	738	4.959E+00	779	1.553E+00
616	2.880E+01	657	2.764E+01	698	1.390E+01	739	4.823E+00	780	1.556E+00
617	2.903E+01	658	2.735E+01	699	1.360E+01	740	4.679E+00		
618	2.923E+01	659	2.709E+01	700	1.328E+01	741	4.548E+00		
619	2.940E+01	660	2.681E+01	701	1.298E+01	742	4.422E+00		
620	2.960E+01	661	2.652E+01	702	1.268E+01	743	4.304E+00		
621	2.977E+01	662	2.621E+01	703	1.238E+01	744	4.186E+00		
622	2.991E+01	663	2.590E+01	704	1.210E+01	745	4.073E+00		
623	3.007E+01	664	2.560E+01	705	1.181E+01	746	3.960E+00		
624	3.021E+01	665	2.527E+01	706	1.153E+01	747	3.846E+00		
625	3.032E+01	666	2.494E+01	707	1.123E+01	748	3.740E+00		

CIE 1931 x y Chromaticity Diagram



7-Step Chromaticity Quadrangles



[Goniophotometer System]

The Stabilization time: **30 minutes**

Total operating time for luminous intensity distribution: **1.0 hour**

Test orientation: **Base up**


Electrical Measurement

Input Voltage (V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.09	60	0.1338	15.426	0.9602

Photometric Measurement

Luminous Flux (lm)	Efficacy (lm/W)	I _{max} (cd)	S/MH (C0/180)	S/MH (C90/270)
1350.81	87.57	6777.0	0.36	0.34

Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle (50% I _{max}):	20.2	20.2	20.3	20.2	20.2
Field Angle (10% I _{max}):	41.4	41.6	41.7	41.3	41.5

Luminous Intensity (cd) Distribution Data

C Y	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	6762	6762	6762	6762	6762	6762	6762	6762
5.0°	5754	5807	5843	5872	5931	5951	5959	5942
10.0°	3288	3367	3448	3537	3573	3559	3495	3439
15.0°	1461	1502	1555	1609	1653	1668	1634	1601
20.0°	688	714	751	776	801	808	784	769
25.0°	384	400	417	429	439	443	429	419
30.0°	230	241	251	255	260	253	247	238
35.0°	147	153	155	156	155	155	146	138
40.0°	97	101	104	105	103	102	96	94
45.0°	66	67	68	68	68	68	66	66
50.0°	46	47	48	48	49	49	48	48
55.0°	34	35	35	35	35	36	35	35
60.0°	27	27	28	27	28	28	27	27
65.0°	21	21	21	21	21	21	21	21
70.0°	15	16	16	16	16	16	16	15
75.0°	10	10	10	10	10	10	10	10
80.0°	5	6	6	6	6	6	6	6
85.0°	2	2	2	2	2	2	2	2
90.0°	0	0	0	0	0	0	0	0
95.0°	0	0	0	0	0	0	0	0
100.0°	0	0	0	0	0	0	0	0
105.0°	0	0	0	0	0	0	0	0
110.0°	0	0	0	0	0	0	0	0
115.0°	0	0	0	0	0	0	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	1	1	1	1	1	1	1	1
145.0°	2	2	2	2	2	2	2	2
150.0°	3	3	3	3	3	3	3	3
155.0°	4	4	4	4	4	4	4	4
160.0°	5	5	5	5	5	5	5	4
165.0°	4	4	4	4	4	4	4	4
170.0°	4	4	4	4	4	4	4	4
175.0°	3	3	3	3	3	3	3	3
180.0°	2	2	2	2	2	2	2	2

Luminous Intensity (cd) Distribution Data (cont.)

C Y	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	6762	6762	6762	6762	6762	6762	6762	6762
5.0°	6056	6003	5881	5804	5756	5756	5788	5844
10.0°	3560	3494	3401	3367	3342	3330	3350	3409
15.0°	1663	1610	1549	1511	1497	1478	1474	1506
20.0°	800	778	754	728	716	699	697	715
25.0°	431	428	417	400	393	383	386	395
30.0°	245	250	248	240	233	227	228	232
35.0°	149	156	156	152	146	145	143	144
40.0°	100	103	100	98	95	95	96	98
45.0°	68	67	67	66	65	64	65	68
50.0°	49	49	48	47	46	46	46	48
55.0°	35	36	36	35	35	35	35	36
60.0°	27	27	28	27	27	27	27	28
65.0°	21	21	21	21	21	21	21	21
70.0°	16	16	16	16	16	16	16	16
75.0°	11	10	10	10	10	10	10	10
80.0°	6	6	6	6	6	6	6	6
85.0°	2	2	2	2	2	2	2	2
90.0°	0	0	0	0	0	0	0	0
95.0°	0	0	0	0	0	0	0	0
100.0°	0	0	0	0	0	0	0	0
105.0°	0	0	0	0	0	0	0	0
110.0°	0	0	0	0	0	0	0	0
115.0°	0	0	0	0	0	0	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	0	0	0	0	0	0	0	0
145.0°	1	1	1	1	1	1	1	1
150.0°	1	1	1	1	1	1	1	1
155.0°	1	1	1	1	1	1	1	1
160.0°	1	1	1	1	1	1	1	1
165.0°	1	1	1	1	1	1	1	1
170.0°	1	1	1	1	1	1	1	1
175.0°	1	1	1	1	1	1	1	1
180.0°	2	2	2	2	2	2	2	2

Zonal Lumen Density Measurement

Deg	Flux (lm)	%
0-5	151.1	11.18
5-10	328.0	24.28
10-15	276.8	20.49
15-20	179.0	13.25
20-25	116.1	8.59
25-30	80.3	5.94
30-35	56.1	4.16
35-40	40.7	3.01
40-45	30.0	2.22
45-50	22.7	1.69
50-55	17.8	1.32
55-60	14.4	1.06
60-65	11.7	0.87
65-70	9.3	0.69
70-75	6.8	0.50
75-80	4.2	0.31
80-85	2.1	0.15
85-90	0.6	0.05
90-95	0.0	0.00
95-100	0.0	0.00
100-105	0.0	0.00
105-110	0.0	0.00
110-115	0.0	0.00
115-120	0.0	0.00
120-125	0.0	0.00
125-130	0.0	0.00
130-135	0.1	0.01
135-140	0.2	0.01
140-145	0.3	0.03
145-150	0.5	0.03
150-155	0.6	0.05
155-160	0.6	0.04
160-165	0.5	0.03
165-170	0.3	0.03
170-175	0.2	0.01
175-180	0.0	0.00

Deg	Flux (lm)	%
0-5	151.1	11.18
0-10	479.0	35.46
0-15	755.8	55.95
0-20	934.7	69.20
0-25	1050.8	77.79
0-30	1131.1	83.73
0-35	1187.2	87.89
0-40	1227.9	90.90
0-45	1257.9	93.12
0-50	1280.7	94.81
0-55	1298.5	96.13
0-60	1312.9	97.19
0-65	1324.6	98.06
0-70	1333.9	98.75
0-75	1340.6	99.25
0-80	1344.9	99.56
0-85	1346.9	99.71
0-90	1347.5	99.76
0-95	1347.5	99.76
0-100	1347.5	99.76
0-105	1347.5	99.76
0-110	1347.5	99.76
0-115	1347.6	99.76
0-120	1347.6	99.76
0-125	1347.6	99.76
0-130	1347.6	99.76
0-135	1347.7	99.77
0-140	1347.9	99.78
0-145	1348.2	99.81
0-150	1348.7	99.84
0-155	1349.3	99.89
0-160	1349.9	99.93
0-165	1350.3	99.96
0-170	1350.6	99.99
0-175	1350.8	100.00
0-180	1350.8	100.00

Test Item	Test Voltage (V)	Frequency (Hz)	Test Result
Total Harmonic Distortion:	120.0	60	15.88%

6. Product Photo



Directions

1. The information marked "superscript #" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
2. This report includes some test methods are not in NVLAP accreditation scope marked *.
3. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $K=2$ with the 95% confidence interval.
6. This report cannot be reproduced except in full, without prior written approval of the Company.
7. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

*****END OF REPORT*****