

# 7" ROUND DOWNLIGHT 15W 277V




15W REPLACES



**75W Inc.**

80% Energy Savings

**CRISP**



**\$197** Savings per lamp\*

- Innovative **CLICK** design
- SootheOptic** low glare technology
- 0-10V** dimming – Compatible with 120-277V circuits
- Fits most 4" J-boxes and 4" & 6" recessed housings
- Wet location** rated
- Exceptional color rendering **CRI 90**



50,000 H



DIMMABLE



LOW GLARE



5 YR WARRANTY



CRI (Ra)




WET LOCATION



## DOWNLIGHT PRODUCT FEATURES

### Edge Lighting Technology

The **CLICK DESIGN** SURFACE MOUNT SQUARE & ROUND DOWNLIGHTS use the latest in edge lighting technology to produce a smooth uniform lighting effect. These naturally low glare downlights integrate seamlessly into all ceiling applications.




- BACK PLATE
- WATERPROOF FOAM
- EDGE LIGHTING REFLECTOR
- LIGHT GUIDE PLATE
- SootheOptic** LOW GLARE
- TRIM

### SootheOptic Low Glare Technology

These downlights all feature **SootheOptic** technology that reduces high-angle light and minimizes visual glare. The smooth low glare diffuser gives each luminaire a soft cutoff without visible color separation.

#### Glare Control Diffuser



2.4mm Hex Pattern

#### Viewing Angle



0°

45°


>65°

# 7" ROUND DOWNLIGHT 15W 277V

## DUAL INSTALLATION


### 4" J-BOX FLUSHMOUNT

For all models



ACCESSORIES INCLUDED:

- Attach mounting bracket to J-box
- Click downlight into mounting bracket



Mounting Bracket



J-Box Screws




Wire Nuts



LED Adapter

### 4" & 6" CAN RECESSED

4" CAN - 5.5" & 7" models  
6" CAN - 7" model only



ACCESSORIES SOLD SEPARATELY:

- Connect E26 adapter to the LED adapter
- Insert mounting clips and push downlight up until flush with ceiling



E26 Adapter



Mounting Clips



Ground Screw



LED Adapter

## SPECIFICATIONS

Product Model	58265 15SMPR7DIM/930/277V	58266 15SMPR7DIM/940/277V
Type	7" SMPR	7" SMPR
Base	LED Adapter (E26 & GU24 optional)	LED Adapter (E26 & GU24 optional)
Power (W)	15	15
Voltage - Frequency	120-277V 50-60Hz	120-277V 50-60Hz
Color Temp. (ANSI)	Warm White 3000K	Cool White 4000K
CRI (Ra)	90	90
Typical lumens (lm)	850	870
Efficacy (LPW)	57	58
Beam Angle	100°	100°
Dimmable	Yes**	Yes**
Housing Compatibility	4" J-box / Most 4" & 6" housing	4" J-box / Most 4" & 6" housing
Power Factor	0.9	0.9
Rated Lifetime - L70 (hrs.)	50,000	50,000
Temperature rating	-4°F / -20°C - 95°F / 35°C	-4°F / -20°C - 95°F / 35°C
Dia. x MOL	7.17"x1.65" (182x42mm)	7.17"x1.65" (182x42mm)
Weight (lb. / g)	0.95lb. / 431g	0.95lb. / 431g

## ACCESSORY ORDERING INFORMATION

Model	Product	Description
SMP/ACC	58033	4" or 6" Recessed Can Accessories for 5.5" & 7" Round & Square (5.5" for Use in 4" Can Only, 7" for Use in 4" or 6" Can)

\* Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$4 incandescent with 1000-hr lifetime, \$35 LED with 50,000-hr lifetime

\*\* List of tested dimmer switches available on website