

PLL 17W DIR TITANIUM LED SERIES



PL:EDGE
SERIES

17W REPLACES



40W
CFL

60% Energy Savings

PRO




Support clip included

- Compatible with Instant Start & Programmed Start ballasts
- Easy to install - Plug & Play Direct
- Exceptional efficacy 124 LPW
- Suitable for use in totally enclosed fixtures
- Wide beam design: 280° light emitting area
- 0-10V dimming
- Fixture operating temperature: -4°F to 95°F (-20°C to 35°C)
- Lamp ambient temperature: -4°F to 113°F (-20°C to 45°C)
- Ballast Dependent. Please refer to www.greencreative.com for full ballast compatibility list.



50,000 H




BALLAST
COMPATIBLE




PLUG
&
PLAY
Direct



5
YR
WARRANTY



80
CRI (Ra)



ENCLOSED*



lighting
facts
LED Product Partner

EFFICIENCY AT WORK



SPECIFICATIONS

Product Model	97745 17PLL/830/DIR	97746 17PLL/835/DIR	97747 17PLL/840/DIR
Type	PLL	PLL	PLL
Base	2G11	2G11	2G11
Power (W)	17	17	17
Voltage - Frequency	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz
Color Temp. (ANSI)	Warm White 3000K	Neutral White 3500K	Cool White 4000K
CRI (Ra)	80	80	80
Typical lumens (lm)	2000	2050	2100
Efficacy (LPW)	118	121	124
Light Emitting Area	280°	280°	280°
Beam Angle	120°	120°	120°
Dimmable	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9
THD	<20%	<20%	<20%
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000
Dia. x MOL	1.71"x22.48" (44x571mm)	1.71"x22.48" (44x571mm)	1.71"x22.48" (44x571mm)
Weight (lb. / g)	0.31lb. / 140g	0.31lb. / 140g	0.31lb. / 140g

BALLAST PERFORMANCE

Bare Lamp (W)	System (W)	3000K Lumens	3500K Lumens	4000K Lumens
17	21	2000	2050	2100

* Suitable for use in totally enclosed fixtures

** Suitable for damp locations. Not for use where directly exposed to the weather or water