

Project Name:	Type:
Part Number:	Date:

HID LED 25W 277V

FEATURES


- Direct line voltage 120-277V installation; Need to bypass existing ballasts
- A23 bulb shape design, emitting 290° uniform light
- Frosted diffuser maintains low glare
- E26 base replaces 200W incandescent lamp
- EX39 base replaces 70-100W HID lamp
- Exceptional high efficacy 136LPW
- Suitable for use in enclosed fixture
- UL damp location
- Temperature rating: -4°F/-20°C - 113 °F/45 °C
- Rated lifetime (L70): 50,000hrs
- 5 years limited warranty
- Suitable for post-top / bollard / low-bay application



SPECIFICATIONS

Product	Model	CCT	Base	Wattage	Lumens	LPW	Power Factor	CRI	DIM	CERT
97972	25HID/830/277V/E26/R	3000K	E26	25	3200	128	0.9	82	No	Pending
97973	25HID/840/277V/E26/R	4000K	E26	25	3300	132	0.9	82	No	Pending
97974	25HID/850/277V/E26/R	5000K	E26	25	3400	136	0.9	82	No	Pending
97968	25HID/830/277V/EX39/R	3000K	EX39	25	3200	128	0.9	82	No	DLC
97969	25HID/840/277V/EX39/R	4000K	EX39	25	3300	132	0.9	82	No	DLC
97970	25HID/850/277V/EX39/R	5000K	EX39	25	3400	136	0.9	82	No	DLC

DIMENSION & WEIGHT



Base	E26	EX39
Mol.	6.34" (161mm)	6.81" (173mm)
Dia.	3.23" (82mm)	3.23" (82mm)
Weight	1.04lb/470g	1.10lb/500g

HID EQUIVALENCE

GREEN CREATIVE HID LED		Metal Halide		Mercury Vapor		High Pressure Sodium	
Power	Lumens	Power	Mean Lumens	Power	Mean Lumens	Power	Mean Lumens
25W	3300	70W	3400	100W	3300	50W	3600