

# SELECTFIT DOWNLIGHTS



GREENCREATIVE



## FEATURES

- 4", 6", 8" & 9.5" fixture sizes
- Choose from either 3000K / 3500K / 4000K or 2700K / 5000K with SelectKelvin technology
- Selectable lumen output with SelectDrive technology
- 120V line voltage or 0-10V dimming available
- Ambient temperature range: -4°F to 95°F (-20°C to 35°C)
- Wet location, IC and Air-tight rated
- L70 rated lifetime of 50,000 hours

- ENERGY STAR® certified
- ETL listed and classified
- 5 year warranty



## OFFICE



## APPLICATIONS

- Commercial
- Education
- Office
- Retail



# SELECFIT TECHNOLOGY AND BENEFIT

## SELECTABLE CCT

Make retrofit projects easier with the SELECFIT commercial downlight family of fixtures. Select the CCT before, during or after installation with just the flip of a switch and never worry about having the correct CCT for a project again.

Select Kelvin



## SELECTABLE OUTPUT

Get the right amount of light with SELECFIT, powered by SelectDrive technology. Choose either Low, Medium or High light output. With just the flip of a switch ensure that every space has just the right amount of light.

Select Drive

## QUALITY, DURABILITY AND SIMPLICITY

SELECFIT fixtures are made with high quality materials for easy installation and long lasting durability. The heavy duty spring clips ensure a quick, tight fit to the ceiling. The seamless integration of heat sink, recessed reflector and opaque lens ensure a smooth, uniform beam of light from an IC, Air-tight and Wet location rated fixture, suitable for most commercial downlighting needs.



## ORDERING

Series	Size	CRI	CCT	Dimming
<input checked="" type="checkbox"/> <b>SLFT</b> SELECFIT	<input type="checkbox"/> <b>4</b> 4" 500 / 700 / 1000lm	<input checked="" type="checkbox"/> <b>80</b> CRI 80	<input type="checkbox"/> <b>CCTS</b> Selectable CCT 3000K / 3500K / 4000K	<input type="checkbox"/> <b>DIM120V</b> 120V - Line voltage dimming
	<input type="checkbox"/> <b>6</b> 6" 700 / 1000 / 1500lm		<input type="checkbox"/> <b>CCT2750*</b> Selectable CCT 2700K / 5000K	<input type="checkbox"/> <b>DIM010UNV</b> 120-277V - 0-10V dimming
	<input type="checkbox"/> <b>8</b> 8" 1000 / 1500 / 2000lm			
	<input type="checkbox"/> <b>9.5</b> 9.5" 2000 / 2500 / 3200lm			

\*AVAILABLE IN DIM010UNV ONLY

## ACCESSORY ORDERING INFORMATION

Product	Model	Description
98569	GOOFRING4	4" goof ring - outer diameter 8-1/8"
98568	GOOFRING6	6" goof ring - outer diameter 10-7/16"
98567	GOOFRING8	8" goof ring - outer diameter 12-3/8"
98566	GOOFRING9.5	9.5" goof ring - outer diameter 14-3/16"
35121	NCFJB4	New Construction Frame for T-Grid ceilings and stud/joist mounting for use with 4" models
35122	NCFJB6	New construction frame for T-Grid ceilings and stud/joist mounting for use with 6" models
35123	NCFJB8	New Construction Frame for T-Grid ceilings and stud/joist mounting for use with 8" models
35124	NCFJB9.5	New Construction Frame for T-Grid ceilings and stud/joist mounting for use with 9.5" models
35125	NCFEMB	Field Installable Emergency Bracket For New Construction Frame
35126	NCFBFB	Field Installable Butterfly Brackets For New Construction Frame
98501	NCPLATE/T4689	New construction or remodel plate for T-grid ceilings for use with 4", 6", 8" and 9.5" models
98502	NCPLATE468	New construction plate for stud / joist mounting for use with 4", 6" and 8" models
98583	NCPLATEJB	Additional J-box for new construction installation
58012	35EMINVERTER	35W Emergency Inverter for use with 4", 6" and 8" models only
58013	35EMINVERTER/CEC	California Title 20 Compliant 35W Emergency Inverter
98235	50EMINVERTER	50W Emergency Inverter for use with 9.5" model