HID LED 20W WALL PACK E26









- Direct line voltage 120-277V Not compatible with ballasts
- Designed to replace traditional ED17 HID lamps
- Ompatible with E26 sockets
- 350° rotatable base
- Available in 4000K & 5000K
- Suitable for use in totally enclosed fixtures















HID LED WALL PACK PRODUCT FEATURES

Suitable for Enclosed Fixtures



This HID LED lamp replaces a 70-100W HID and is suitable for use in totally enclosed fixtures. Its high lumen output and exceptional efficacy make it an ideal choice for outdoor wall pack applications.


CoolSink Technology


The CoolSink passive cooling system allows air to flow freely through the lamp. This unique design uses an increased cooling surface area to reduce the operating temperature of the LED and power supply, thus resulting in longer lamp life and lumen maintenance.




HID LED 20W WALL PACK E26









SPECIFICATIONS

| Product Model | 98179 20HIDWP/840/277V/E26 | 98180 20HIDWP/850/277V/E26 | | | | | |
|-----------------------------|-------------------------------|-------------------------------|--|--|--|--|--|
| Туре | HID LED | HID LED | | | | | |
| Base | E26 | E26 | | | | | |
| Power (W) | 20 | 20 | | | | | |
| Voltage - Frequency | 120-277V | 120-277V | | | | | |
| Color Temp. (ANSI) | Cool White 4000K | Daylight 5000K | | | | | |
| CRI (Ra) (typ.) | 82 | 82 | | | | | |
| Bare Lamp lumens (Im) | 2800 | 2800 | | | | | |
| Bare Lamp efficacy (LPW) | 140 | 140 | | | | | |
| Beam Angle | 120° | 120° | | | | | |
| Dimmable | No | No | | | | | |
| Power Factor | 0.9 | 0.9 | | | | | |
| Rated Lifetime - L70 (hrs.) | 50,000 | 50,000 | | | | | |
| Temperature Rating | -4°F/-20°C - 95°F/35°C | -4°F/-20°C - 95°F/35°C | | | | | |
| Dia. x MOL | 3.62"x5.35" (92x136mm) | 3.62"x5.35" (92x136mm) | | | | | |
| Weight (lb. / g) | 1.09lb. / 493g | 1.09lb. / 493g | | | | | |

HID EQUIVALENCE

| GREEN CREATIVE HID LED | | Metal Halide | | Mercury Vapor | | High Pressure Sodium | |
|------------------------|--------|--------------|-------------|---------------|-------------|----------------------|-------------|
| Power | Lumens | Power | Mean Lumens | Power | Mean Lumens | Power | Mean Lumens |
| 20W | 2800 | 70W | 3400 | 100W | 3300 | 50W | 3600 |

Ref.#: DS258-HIDWP-LED-20W-277V-E26-130618

^{*} Suitable for use in totally enclosed fixtures
** Suitable for damp locations. Not for use where directly exposed to weather or water

^{***} Suitable for use in horizontal applications