

PRO



- Suitable for use in totally enclosed fixtures
- High efficacy 67 LPW in Warm White
- 20% more efficient than Tier 1 MR11 industry average
- Compact size 1:1 halogen form factor
- UL certified Class 1 & 2
- Warm White & Natural White CCT

















20W Hal.

80% Energy Savings














SUITABLE FOR ALL DISPLAY APPLICATIONS









ILLUMINANCE 3MR11/827NF30 3MR11/840NF30 Distance (ft) Diameter (ft) Distance (ft) Diameter (ft) - 1.6 - 1.6 67 69 17 3.2 17 3.2 4.8 4.8 12 6.4 12 4 6.4 4 15 -- 8.0 15 -- 8.0 3 3 **Footcandles Footcandles**

SPECIFICATIONS

Product Model	40713 3MR11/827NF30	40715 3MR11/840NF30
Туре	MR11	MR11
Base	Bi-pin GU4	Bi-pin GU4
Power (W)	3	3
Voltage - Frequency	12VAC 60Hz / 12VDC	12VAC 60Hz / 12VDC
Color Temp. (ANSI)	Warm White 2700K	Natural White 4000K
CRI (Ra)	82	82
Typical lumens (lm)	200	220
Efficacy (LPW)	67	73
Beam Angle	NF 30°	NF 30°
CBCP (cd)	600	620
Dimmable	No	No
Power Factor	0.9	0.9
Rated Lifetime - L70 (hrs.)	25,000	25,000
Dia. x MOL	1.38''x1.53''(35x39mm)	1.38''x1.53''(35x39mm)
Weight (lb. / g)	0.07lb. / 30g	0.07lb. / 30g

^{*} Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$4 halogen with 1000-hr lifetime, \$20 LED with 25,000-hr lifetime

^{**} Suitable for use in totally enclosed fixtures
*** Suitable for damp locations. Not for use where directly exposed to weather or water