

HID LED 40W WALL PACK E26

PRO



Horizontal lamp supports included

40W REPLACES



100-175W
HID


70% Energy Savings

- Ⓞ Direct line voltage 120-277V - Not compatible with ballasts
- Ⓞ Designed to replace traditional ED28 HID lamps
- Ⓞ Compatible with E26 sockets
- Ⓞ 350° rotatable base
- Ⓞ Available in 4000K & 5000K
- Ⓞ Suitable for use in totally enclosed fixtures



HID LED WALL PACK PRODUCT FEATURES


Suitable for Enclosed Fixtures



This HID LED lamp replaces a 100-175W HID and is suitable for use in totally enclosed fixtures. Its high lumen output and exceptional efficacy make it an ideal choice for outdoor wall pack applications.

CoolSink Technology

The CoolSink passive cooling system allows air to flow freely through the lamp. This unique design uses an increased cooling surface area to reduce the operating temperature of the LED and power supply, thus resulting in longer lamp life and lumen maintenance.



HID LED 40W WALL PACK E26

APPLICATIONS

General Lighting & Security



Loading Areas



Walkways & Entryways



SPECIFICATIONS

Product Model	98183 40HIDWP/840/277V/E26	98184 40HIDWP/850/277V/E26
Type	HID LED	HID LED
Base	E26	E26
Power (W)	40	40
Voltage - Frequency	120-277V	120-277V
Color Temp. (ANSI)	Cool White 4000K	Daylight 5000K
CRI (Ra) (typ.)	82	82
Bare Lamp lumens (lm)	5800	5800
Bare Lamp efficacy (LPW)	145	145
Beam Angle	120°	120°
Dimmable	No	No
Power Factor	0.9	0.9
Rated Lifetime - L70 (hrs.)	50,000	50,000
Temperature Rating	-4°F/-20°C - 95°F/35°C	-4°F/-20°C - 95°F/35°C
Dia. x MOL	3.62"x7.80" (92x198mm)	3.62"x7.80" (92x198mm)
Weight (lb. / g)	1.64lb. / 743g	1.64lb. / 743g

HID EQUIVALENCE

GREEN CREATIVE HID LED		Metal Halide		Mercury Vapor		High Pressure Sodium	
Power	Lumens	Power	Mean Lumens	Power	Mean Lumens	Power	Mean Lumens
40W	5800	100W	5800	175W	6250	70W	5350

* Suitable for use in totally enclosed fixtures

** Suitable for damp locations. Not for use where directly exposed to weather or water

*** Suitable for use in horizontal applications