



IES LM-79-08

MEASUREMENT AND TEST REPORT

For

GREEN CREATIVE LTD

Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, KL, Hong Kong

Test Model: 6.5MR16DIM/830FL35/35W

Report Type:	Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution
Project Engineer:	George Chen <i>George Chen</i>
Report Number:	KS2211025-54717E-10
Test Date:	2021-07-16 to 2021-07-22
Report Date:	2021-11-16
Reviewed By:	Blake Zhang / EE Engineer
Prepared By:	Bay Area Compliance Laboratories Corp. (Dongguan). No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China. Tel: +86-0769-86858888 Fax: +86-0769-86858588
Accreditation:	The IAS Accreditation Number TL-460.

1. Product Description[#]

General Information:

Two samples were received on 2021-07-06. One was tested in integrating sphere and the other was tested in goniophotometer.

Model Tested: 6.5MR16DIM/830FL35/35W
Manufacturer: GREEN CREATIVE LTD
Brand Name: GREEN CREATIVE
Product Designation: Directional LED Lamp
Burning Time Before Test: 0hour(For New Products)

Rated Values:

Rated Voltage/Frequency: 12 VAC 60Hz
Rated Power: 6.5W
Nominal CCT: 3000K
Nominal Lumen Output: 460lm

Note:

1. The applicant GREEN CREATIVE LTD declare that their products with model 6.5MR16DIM/830FL35/35W are the same to the products in report#KS2210706-27591E-10 and is authorized by original applicant to use their test data.
2. All the data in previous report (KS2210706-27591E-10) is shared in this report.

2. Standards Used

- IES LM-79-08: Approved Method: Electrical & Photometric Measurement of Solid-state Lighting Products
- ANSI C82.77-10-2014: Harmonic Emission Limits – Related Power Quality Requirements for Lighting Equipment
- IES TM-30-18: IES Method for Evaluating Light Source Color Rendition (This method is not in IAS accreditation scope)

3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
2.0m integrating sphere	EVERFINE	R98	11010018	2020-10-21	2021-10-20
spectroradiometer	EVERFINE	HAAS-2000	G112048TS81331121	2020-10-21	2021-10-20
Digital Power Meter	EVERFINE	PF2010A	1011004	2020-10-21	2021-10-20
Digital CC&CV DC Power Supply	EVERFINE	WY305-V1	1101047	2021-06-30	2022-06-29
Rapid Recording Photometer	EVERFINE	PHOTO-2000F	1007010	2020-11-05	2021-11-04
Standard Light Source	EVERFINE	D204	N/A	2020-10-20	2021-10-19
Special zero-voltage synchronous switching AC	EVERFINE	DPS1010-YF	1011001T	2021-01-04	2022-01-03
AC POWER SUPPLY	EVERFINE	VPS1030 PWM	1012017	2021-01-04	2022-01-03

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
Digital CC&CV DC Power Supply	EVERFINE	WY12010	1009009	2021-01-04	2022-01-03
Digital power meter	YOKOGAWA	WT-210	91j926132	2021-01-04	2022-01-03
full-field speed goniophotometer	EVERFINE	GO-R5000	YG108492N10120001	2021-03-12	2022-03-11
wireless remote thermohygrometer	N/A	433MHz	N/A	2021-03-12	2022-03-11
Standard Light Source	EVERFINE	D908	1012003	2020-10-20	2021-10-19

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with IES LM-79-08. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at 25°C±1°C during measurement. And relative humidity is less than 65%.

Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

4 π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is U=2.1% (K=2), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is U=22K (K=2), at the 95% confidence level. The uncertainty of the CRI is U=2.1(K=2), at the 95% confidence level.

The uncertainty of power meter AC current U=0.19 % of rdg, AC Voltage U=0.18% of rdg, Power U=0.46%) (K=2), at the 95% confidence level.

Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The vertical angle (γ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

The uncertainty of the luminous intensity is U=2.00% (K=2), at the 95% confidence level.

Fidelity Index and Gamut Index Calculation

The R_i , R_g was calculated according to IES TM-30-18 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

5. Test Result

[Integrating Sphere System]

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Base Up**


Photometric and Electrical Measurement Result







Voltage(V)	Frequency(Hz)	Current(A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy(lm/W)
12.0	60	0.5349	5.905	0.9201	469.10	79.44

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
1.4449	3082	-0.000512	0.4305	0.4005	0.2479	0.5190


Color Rendering Index

Ra			
83.5			
R1	R2	R3	R4
82	92	96	81
R5	R6	R7	R8
82	90	83	61
R9	R10	R11	R12
11	82	81	74
R13	R14	R15	
85	98	75	






Relative Spectral Power Distribution




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
380	1.421E-01	421	4.282E-01	462	3.572E+00	503	3.445E+00	544	5.507E+00
381	1.212E-01	422	4.666E-01	463	3.437E+00	504	3.524E+00	545	5.565E+00
382	1.661E-01	423	5.080E-01	464	3.327E+00	505	3.593E+00	546	5.612E+00
383	1.085E-01	424	5.539E-01	465	3.215E+00	506	3.676E+00	547	5.668E+00
384	1.031E-01	425	5.985E-01	466	3.112E+00	507	3.746E+00	548	5.720E+00
385	1.044E-01	426	6.575E-01	467	3.022E+00	508	3.814E+00	549	5.783E+00
386	8.983E-02	427	7.214E-01	468	2.921E+00	509	3.883E+00	550	5.850E+00
387	1.165E-01	428	7.860E-01	469	2.845E+00	510	3.943E+00	551	5.903E+00
388	7.222E-02	429	8.530E-01	470	2.751E+00	511	4.005E+00	552	5.969E+00
389	7.558E-02	430	9.366E-01	471	2.659E+00	512	4.053E+00	553	6.046E+00
390	6.391E-02	431	1.015E+00	472	2.574E+00	513	4.131E+00	554	6.111E+00
391	7.057E-02	432	1.106E+00	473	2.482E+00	514	4.183E+00	555	6.175E+00
392	6.213E-02	433	1.200E+00	474	2.397E+00	515	4.237E+00	556	6.245E+00
393	7.172E-02	434	1.307E+00	475	2.334E+00	516	4.296E+00	557	6.319E+00
394	6.056E-02	435	1.420E+00	476	2.270E+00	517	4.342E+00	558	6.393E+00
395	5.944E-02	436	1.555E+00	477	2.223E+00	518	4.386E+00	559	6.475E+00
396	5.118E-02	437	1.678E+00	478	2.187E+00	519	4.432E+00	560	6.552E+00
397	6.091E-02	438	1.837E+00	479	2.165E+00	520	4.485E+00	561	6.631E+00
398	6.049E-02	439	2.008E+00	480	2.163E+00	521	4.521E+00	562	6.721E+00
399	6.813E-02	440	2.188E+00	481	2.165E+00	522	4.570E+00	563	6.790E+00
400	6.850E-02	441	2.393E+00	482	2.170E+00	523	4.616E+00	564	6.881E+00
401	7.554E-02	442	2.605E+00	483	2.196E+00	524	4.650E+00	565	6.951E+00
402	7.166E-02	443	2.852E+00	484	2.221E+00	525	4.700E+00	566	7.042E+00
403	7.977E-02	444	3.102E+00	485	2.255E+00	526	4.742E+00	567	7.136E+00
404	8.010E-02	445	3.384E+00	486	2.287E+00	527	4.780E+00	568	7.216E+00
405	9.053E-02	446	3.665E+00	487	2.343E+00	528	4.812E+00	569	7.314E+00
406	9.517E-02	447	3.929E+00	488	2.377E+00	529	4.854E+00	570	7.409E+00
407	1.079E-01	448	4.207E+00	489	2.430E+00	530	4.896E+00	571	7.489E+00
408	1.219E-01	449	4.461E+00	490	2.486E+00	531	4.936E+00	572	7.589E+00
409	1.329E-01	450	4.668E+00	491	2.547E+00	532	4.977E+00	573	7.679E+00
410	1.371E-01	451	4.836E+00	492	2.607E+00	533	5.023E+00	574	7.765E+00
411	1.554E-01	452	4.919E+00	493	2.676E+00	534	5.059E+00	575	7.862E+00
412	1.775E-01	453	4.964E+00	494	2.748E+00	535	5.093E+00	576	7.947E+00
413	1.925E-01	454	4.938E+00	495	2.821E+00	536	5.131E+00	577	8.033E+00
414	2.108E-01	455	4.848E+00	496	2.899E+00	537	5.181E+00	578	8.122E+00
415	2.393E-01	456	4.699E+00	497	2.977E+00	538	5.235E+00	579	8.209E+00
416	2.677E-01	457	4.526E+00	498	3.052E+00	539	5.268E+00	580	8.288E+00
417	2.933E-01	458	4.313E+00	499	3.134E+00	540	5.312E+00	581	8.388E+00
418	3.252E-01	459	4.116E+00	500	3.217E+00	541	5.364E+00	582	8.461E+00
419	3.483E-01	460	3.911E+00	501	3.279E+00	542	5.409E+00	583	8.528E+00
420	3.929E-01	461	3.739E+00	502	3.369E+00	543	5.457E+00	584	8.633E+00

nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
585	8.694E+00	626	8.216E+00	667	3.788E+00	708	1.192E+00	749	3.487E-01
586	8.759E+00	627	8.137E+00	668	3.692E+00	709	1.157E+00	750	3.404E-01
587	8.835E+00	628	8.023E+00	669	3.599E+00	710	1.122E+00	751	3.332E-01
588	8.891E+00	629	7.928E+00	670	3.504E+00	711	1.090E+00	752	3.235E-01
589	8.957E+00	630	7.822E+00	671	3.420E+00	712	1.050E+00	753	3.124E-01
590	9.019E+00	631	7.723E+00	672	3.338E+00	713	1.031E+00	754	3.105E-01
591	9.066E+00	632	7.613E+00	673	3.246E+00	714	9.875E-01	755	3.011E-01
592	9.131E+00	633	7.488E+00	674	3.167E+00	715	9.598E-01	756	2.913E-01
593	9.163E+00	634	7.406E+00	675	3.084E+00	716	9.377E-01	757	2.866E-01
594	9.211E+00	635	7.286E+00	676	2.994E+00	717	9.057E-01	758	2.796E-01
595	9.239E+00	636	7.185E+00	677	2.916E+00	718	8.832E-01	759	2.689E-01
596	9.287E+00	637	7.065E+00	678	2.853E+00	719	8.493E-01	760	2.680E-01
597	9.324E+00	638	6.956E+00	679	2.765E+00	720	8.375E-01	761	2.633E-01
598	9.353E+00	639	6.837E+00	680	2.681E+00	721	8.076E-01	762	2.527E-01
599	9.368E+00	640	6.735E+00	681	2.619E+00	722	7.836E-01	763	2.460E-01
600	9.372E+00	641	6.620E+00	682	2.543E+00	723	7.531E-01	764	2.438E-01
601	9.394E+00	642	6.513E+00	683	2.488E+00	724	7.381E-01	765	2.294E-01
602	9.392E+00	643	6.386E+00	684	2.409E+00	725	7.151E-01	766	2.348E-01
603	9.394E+00	644	6.274E+00	685	2.341E+00	726	6.884E-01	767	2.220E-01
604	9.406E+00	645	6.149E+00	686	2.283E+00	727	6.717E-01	768	2.137E-01
605	9.384E+00	646	6.026E+00	687	2.219E+00	728	6.495E-01	769	2.077E-01
606	9.386E+00	647	5.914E+00	688	2.153E+00	729	6.308E-01	770	2.058E-01
607	9.368E+00	648	5.804E+00	689	2.097E+00	730	6.162E-01	771	1.991E-01
608	9.349E+00	649	5.683E+00	690	2.034E+00	731	5.953E-01	772	1.969E-01
609	9.318E+00	650	5.578E+00	691	1.972E+00	732	5.760E-01	773	1.862E-01
610	9.288E+00	651	5.459E+00	692	1.916E+00	733	5.582E-01	774	1.881E-01
611	9.269E+00	652	5.361E+00	693	1.860E+00	734	5.470E-01	775	1.781E-01
612	9.209E+00	653	5.252E+00	694	1.815E+00	735	5.267E-01	776	1.787E-01
613	9.147E+00	654	5.124E+00	695	1.755E+00	736	5.134E-01	777	1.739E-01
614	9.111E+00	655	5.014E+00	696	1.700E+00	737	4.997E-01	778	1.725E-01
615	9.052E+00	656	4.896E+00	697	1.661E+00	738	4.819E-01	779	1.727E-01
616	9.006E+00	657	4.795E+00	698	1.609E+00	739	4.685E-01	780	1.730E-01
617	8.959E+00	658	4.709E+00	699	1.565E+00	740	4.513E-01		
618	8.873E+00	659	4.595E+00	700	1.512E+00	741	4.416E-01		
619	8.800E+00	660	4.462E+00	701	1.475E+00	742	4.286E-01		
620	8.726E+00	661	4.369E+00	702	1.432E+00	743	4.164E-01		
621	8.659E+00	662	4.280E+00	703	1.393E+00	744	4.057E-01		
622	8.569E+00	663	4.173E+00	704	1.347E+00	745	3.943E-01		
623	8.481E+00	664	4.077E+00	705	1.305E+00	746	3.810E-01		
624	8.388E+00	665	3.975E+00	706	1.260E+00	747	3.731E-01		
625	8.315E+00	666	3.883E+00	707	1.234E+00	748	3.655E-01		

CIE 1931xy Chromaticity Diagram



7-StepChromaticity Quadrangles



[Goniophotometer System]

Total operating time for luminous intensity distribution: **1.0 hour**

Test orientation: **Base Up**


Electrical Measurement

Input Voltage(V)	Frequency(Hz)	Input Current(A)	Power (W)	Power Factor
12.00	60	0.5339	5.970	0.9316

Photometric Measurement

Luminous Flux(lm)	Efficacy(lm/W)	I _{max} (cd)	S/MH(C0/180)	S/MH(C90/270)
470.471	78.81	997.0	0.46	0.64

Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle(50%I _{max}):	29.8	29.9	29.9	29.9	29.9
Field Angle(10%I _{max}):	72.8	72.9	72.1	72.3	72.5

Luminous Intensity (cd) Distribution Data

C y	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	954	954	954	954	954	954	954	954
5.0°	910	875	838	807	788	784	795	820
10.0°	743	671	604	556	530	529	552	601
15.0°	523	445	387	353	336	334	351	388
20.0°	344	294	260	241	230	228	238	262
25.0°	239	207	184	172	164	162	168	186
30.0°	170	147	131	121	116	115	119	131
35.0°	118	102	91	81	77	79	82	90
40.0°	79	69	61	51	48	52	56	61
45.0°	51	45	39	32	30	33	36	39
50.0°	32	30	25	21	20	22	24	25
55.0°	21	20	18	15	15	16	17	17
60.0°	16	15	13	12	12	12	13	13
65.0°	12	11	10	9	9	9	9	10
70.0°	9	9	8	7	7	7	7	7
75.0°	7	6	6	5	5	5	5	5
80.0°	5	4	4	3	3	3	3	3
85.0°	3	2	2	1	1	1	1	2
90.0°	1	1	1	1	1	1	1	1
95.0°	1	0	0	0	0	0	0	0
100.0°	0	0	0	0	0	0	0	0
105.0°	0	0	0	0	0	0	0	0
110.0°	0	0	0	0	0	0	0	0
115.0°	0	0	0	0	0	0	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	0	0	0	0	0	0	0	0
145.0°	1	1	1	1	1	1	1	1
150.0°	1	1	1	1	1	1	1	1
155.0°	1	1	1	1	1	1	1	1
160.0°	1	1	1	1	1	1	1	1
165.0°	1	1	1	1	1	1	1	1
170.0°	1	1	1	1	1	1	1	1
175.0°	1	1	1	1	1	1	1	1
180.0°	1	1	0	0	0	1	1	1

Luminous Intensity (cd) Distribution Data (cont.)


C y	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	954	954	954	954	954	954	954	954
5.0°	844	886	932	975	997	988	958	926
10.0°	650	725	807	890	937	909	845	783
15.0°	434	508	592	676	730	717	658	582
20.0°	288	330	380	433	471	469	436	384
25.0°	203	228	254	282	303	301	286	262
30.0°	144	162	179	198	212	209	200	185
35.0°	100	112	126	140	149	147	140	128
40.0°	66	76	87	95	100	101	96	87
45.0°	41	50	58	62	63	68	65	57
50.0°	26	33	38	38	39	43	42	36
55.0°	18	22	25	24	25	27	28	23
60.0°	13	16	17	17	17	19	19	17
65.0°	10	12	13	13	13	14	14	13
70.0°	8	9	10	10	10	11	11	10
75.0°	6	7	8	8	8	8	8	7
80.0°	4	5	5	6	6	6	6	5
85.0°	2	3	3	4	4	4	4	3
90.0°	1	1	1	2	2	2	2	1
95.0°	1	1	1	1	1	1	1	1
100.0°	0	0	0	0	0	0	0	0
105.0°	0	0	0	0	0	0	0	0
110.0°	0	0	0	0	0	0	0	0
115.0°	0	0	0	0	0	0	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	0	0	0	0	0	0	0	0
145.0°	0	0	0	0	0	0	0	0
150.0°	0	0	0	0	0	0	0	0
155.0°	0	0	0	0	0	0	0	0
160.0°	0	0	0	0	0	0	0	0
165.0°	0	0	0	0	0	0	0	0
170.0°	0	0	0	0	0	0	0	0
175.0°	0	0	0	0	0	0	0	0
180.0°	1	1	1	0	0	0	1	1

Zonal Lumen Density Measurement

Deg	Flux (lm)	%
0-5	21.9	4.66
5-10	56.6	12.04
10-15	70.9	15.07
15-20	67.0	14.25
20-25	57.0	12.10
25-30	47.8	10.17
30-35	39.1	8.32
35-40	30.4	6.45
40-45	22.3	4.73
45-50	15.6	3.33
50-55	11.0	2.34
55-60	8.1	1.72
60-65	6.3	1.35
65-70	5.0	1.07
70-75	3.9	0.83
75-80	2.9	0.62
80-85	1.9	0.40
85-90	1.0	0.20
90-95	0.4	0.10
95-100	0.2	0.04
100-105	0.1	0.02
105-110	0.0	0.00
110-115	0.0	0.00
115-120	0.0	0.00
120-125	0.0	0.00
125-130	0.0	0.01
130-135	0.0	0.01
135-140	0.1	0.01
140-145	0.1	0.02
145-150	0.1	0.03
150-155	0.1	0.03
155-160	0.1	0.03
160-165	0.1	0.02
165-170	0.1	0.02
170-175	0.0	0.01
175-180	0.0	0.00

Deg	Flux (lm)	%
0-5	21.9	4.66
0-10	78.6	16.70
0-15	149.5	31.77
0-20	216.5	46.02
0-25	273.4	58.12
0-30	321.3	68.29
0-35	360.4	76.61
0-40	390.8	83.06
0-45	413.0	87.79
0-50	428.7	91.12
0-55	439.7	93.46
0-60	447.8	95.18
0-65	454.1	96.53
0-70	459.2	97.60
0-75	463.1	98.43
0-80	466.0	99.05
0-85	467.9	99.45
0-90	468.8	99.65
0-95	469.3	99.75
0-100	469.5	99.79
0-105	469.6	99.81
0-110	469.6	99.81
0-115	469.6	99.81
0-120	469.6	99.81
0-125	469.6	99.81
0-130	469.6	99.82
0-135	469.7	99.83
0-140	469.7	99.84
0-145	469.8	99.86
0-150	470.0	99.89
0-155	470.1	99.92
0-160	470.2	99.95
0-165	470.3	99.97
0-170	470.4	99.99
0-175	470.5	100.00
0-180	470.5	100.00

6. Product Photo



Directions

1. The information marked "superscript #" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
2. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
3. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of the Company.
6. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

*****END OF REPORT*****