



# ANSI/IES LM-79-19

## MEASUREMENT AND TEST REPORT

For

### GREEN CREATIVE LTD

Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong, China

**Test Model: 6.5PAR20DIM/950FL40/SL**

<b>Report Type:</b>	Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution, THD
<b>Reviewed By:</b>	Hill Liu <i>Hill Liu</i>
<b>Report Number:</b>	KS2230727-43599E-EE
<b>Test Date:</b>	2023-07-26 to 2023-07-27
<b>Report Date:</b>	2023-08-25
<b>Approved by:</b>	Blake Zhang / EE Engineer
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Shenzhen) 5/F(B-West) -7/F, the 3rd Phase of Wan Li Industrial Building D, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China. Tel: +86-755-33320018 Fax: +86-755-33320008
<b>Test Facility:</b>	Test facility was located at No.12, Pulong East 1 <sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China.

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.(Shenzhen). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

## 1. Product Description#

### General Information:

Two test samples were in good condition and received on 2023-07-27. One was tested in integrating sphere and the other was tested in goniophotometer

Model Tested:	6.5PAR20DIM/950FL40/SL
Manufacturer:	GREEN CREATIVE LTD
Brand Name:	GREEN CREATIVE
Product Designation:	Directional LED Lamp
Burning Time Before Test:	0hour(For New Products)

### Rated Values:

Rated Voltage/Frequency:	120V AC 60Hz
Rated Power:	6.5W
Nominal CCT:	5000K
Nominal Lumen Output:	580lm

## 2. Standards Used

- ANSI/IES LM-79-19: Approved method: Optical and Electrical Measurements of Solid-State Lighting Products
- ANSI C82.77-10-2014: Harmonic Emission Limits – Related Power Quality Requirements for Lighting
- \*IES TM-30-18: IES Method for Evaluating Light Source Color Rendition (This method is not in NVLAP accreditation scope)

### 3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
2.0m integrating sphere	EVERFINE	R98	11010018	2022-11-10	2023-11-09
spectroradiometer	EVERFINE	HAAS-2000	G112048TS81331121	2022-11-10	2023-11-09
Digital Power Meter	EVERFINE	PF2010A	1011004	2022-11-10	2023-11-09
Digital CC&CV DC Power Supply	EVERFINE	WY305-V1	1101047	2022-11-10	2023-11-09
Standard Light Source	EVERFINE	D204	N/A	2023-05-12	2025-05-11
Special zero-voltage synchronous switching AC	EVERFINE	DPS1010-YF	1011001T	2022-11-10	2023-11-09
AC POWER SUPPLY	EVERFINE	VPS1030 PWM	1012017	2022-11-16	2023-11-15
Digital CC&CV DC Power Supply	EVERFINE	WY12010	1009009	2022-11-10	2023-11-09
Digital power meter	YOKOGAWA	WT-210	91j926132	2022-11-10	2023-11-09
full-field speed goniophotometer	EVERFINE	GO-R5000	YG108492N10120001	2022-11-10	2023-11-09
wireless remote thermohygrometer	N/A	AOK-5017B	N/A	2022-11-10	2023-11-09
Standard Light Source	EVERFINE	D908	1012003	2023-05-12	2025-05-11

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

## 4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with ANSI/IES LM-79-19. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at  $25^{\circ}\text{C}\pm 1.2^{\circ}\text{C}$  during measurement. And relative humidity is maintained between 10% and 65%. The air flow around the SSL product is less than 0.2m/s.

### Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

$4\pi$  geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is  $U=2.1\%$  ( $K=2$ ), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is  $U=22\text{K}$  ( $K=2$ ), at the 95% confidence level. The uncertainty of the CRI is  $U=2.1(K=2)$ , at the 95% confidence level.

The uncertainty of power meter AC current  $U=0.19\%$  of rdg, AC Voltage  $U=0.18\%$  of rdg, Power  $U=0.46\%$  ( $K=2$ ), at the 95% confidence level.

### Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The vertical angle ( $\gamma$ ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

The uncertainty of the luminous intensity is  $U=2.00\%$  ( $K=2$ ), at the 95% confidence level.

### Additional Test

The Additional Test item may not be covered by ANSI/IES LM-79-2019. Additional test including power factor, off-state power and THD, was measured by Digital Power Meter after stabilized at  $25^{\circ}\text{C}\pm 1.2^{\circ}\text{C}$ . Test voltage for THD and power factor test would be equal to rated voltage or, in case of a voltage range, maximum value of that range.

The uncertainty of power meter AC current  $U=0.19\%$  of rdg, AC Voltage  $U=0.18\%$  of rdg, Power  $U=0.46\%$  ( $K=2$ ), at the 95% confidence level.

### Fidelity Index and Gamut Index Calculation

The  $R_i$ ,  $R_g$  was calculated according to IES TM-30-18 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

## 5. Test Result

### [Integrating Sphere System]

The Stabilization time: **30 minutes**

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Base Up**


### Photometric and Electrical Measurement Result







Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.05684	6.432	0.9428	584.84	90.93

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
2.151	4893	0.0041	0.3492	0.3632	0.2097	0.4908


### Color Rendering Index

Ra			
<b>97.0</b>			
R1	R2	R3	R4
97	98	97	97
R5	R6	R7	R8
98	98	96	95
R9	R10	R11	R12
89	98	97	77
R13	R14	R15	
96	98	95	






Relative Spectral Power Distribution




nm	mW								
380	2.759E-01	421	7.136E-01	462	8.204E+00	503	7.650E+00	544	8.565E+00
381	2.829E-01	422	7.882E-01	463	8.055E+00	504	7.701E+00	545	8.537E+00
382	2.053E-01	423	8.612E-01	464	7.902E+00	505	7.752E+00	546	8.498E+00
383	2.441E-01	424	9.655E-01	465	7.721E+00	506	7.818E+00	547	8.460E+00
384	2.112E-01	425	1.060E+00	466	7.535E+00	507	7.880E+00	548	8.429E+00
385	1.807E-01	426	1.174E+00	467	7.322E+00	508	7.925E+00	549	8.418E+00
386	1.703E-01	427	1.316E+00	468	7.093E+00	509	7.982E+00	550	8.381E+00
387	1.917E-01	428	1.445E+00	469	6.860E+00	510	8.032E+00	551	8.336E+00
388	1.654E-01	429	1.616E+00	470	6.629E+00	511	8.074E+00	552	8.295E+00
389	1.612E-01	430	1.794E+00	471	6.432E+00	512	8.128E+00	553	8.265E+00
390	1.487E-01	431	1.983E+00	472	6.301E+00	513	8.157E+00	554	8.225E+00
391	1.265E-01	432	2.192E+00	473	6.161E+00	514	8.204E+00	555	8.184E+00
392	1.364E-01	433	2.432E+00	474	6.069E+00	515	8.254E+00	556	8.144E+00
393	1.308E-01	434	2.695E+00	475	6.014E+00	516	8.296E+00	557	8.096E+00
394	1.321E-01	435	2.995E+00	476	5.985E+00	517	8.314E+00	558	8.063E+00
395	1.176E-01	436	3.303E+00	477	5.991E+00	518	8.357E+00	559	8.028E+00
396	1.077E-01	437	3.652E+00	478	6.025E+00	519	8.389E+00	560	7.981E+00
397	1.106E-01	438	4.055E+00	479	6.053E+00	520	8.428E+00	561	7.927E+00
398	1.194E-01	439	4.495E+00	480	6.096E+00	521	8.460E+00	562	7.889E+00
399	1.254E-01	440	4.991E+00	481	6.127E+00	522	8.487E+00	563	7.839E+00
400	1.268E-01	441	5.581E+00	482	6.192E+00	523	8.524E+00	564	7.807E+00
401	1.337E-01	442	6.217E+00	483	6.258E+00	524	8.547E+00	565	7.768E+00
402	1.479E-01	443	6.933E+00	484	6.292E+00	525	8.567E+00	566	7.725E+00
403	1.410E-01	444	7.697E+00	485	6.345E+00	526	8.582E+00	567	7.678E+00
404	1.511E-01	445	8.505E+00	486	6.422E+00	527	8.597E+00	568	7.643E+00
405	1.629E-01	446	9.343E+00	487	6.476E+00	528	8.623E+00	569	7.604E+00
406	1.700E-01	447	1.014E+01	488	6.526E+00	529	8.641E+00	570	7.574E+00
407	1.874E-01	448	1.080E+01	489	6.590E+00	530	8.659E+00	571	7.552E+00
408	1.996E-01	449	1.136E+01	490	6.671E+00	531	8.665E+00	572	7.507E+00
409	2.179E-01	450	1.170E+01	491	6.736E+00	532	8.670E+00	573	7.493E+00
410	2.452E-01	451	1.185E+01	492	6.837E+00	533	8.646E+00	574	7.462E+00
411	2.594E-01	452	1.175E+01	493	6.900E+00	534	8.666E+00	575	7.439E+00
412	2.908E-01	453	1.148E+01	494	6.996E+00	535	8.669E+00	576	7.426E+00
413	3.145E-01	454	1.107E+01	495	7.063E+00	536	8.668E+00	577	7.399E+00
414	3.453E-01	455	1.056E+01	496	7.142E+00	537	8.669E+00	578	7.391E+00
415	3.866E-01	456	1.006E+01	497	7.225E+00	538	8.658E+00	579	7.359E+00
416	4.174E-01	457	9.605E+00	498	7.296E+00	539	8.656E+00	580	7.364E+00
417	4.767E-01	458	9.183E+00	499	7.364E+00	540	8.643E+00	581	7.346E+00
418	5.273E-01	459	8.848E+00	500	7.449E+00	541	8.619E+00	582	7.346E+00
419	5.806E-01	460	8.560E+00	501	7.518E+00	542	8.600E+00	583	7.340E+00
420	6.443E-01	461	8.373E+00	502	7.584E+00	543	8.592E+00	584	7.345E+00

nm	mW								
585	7.342E+00	626	8.950E+00	667	6.745E+00	708	2.795E+00	749	8.818E-01
586	7.351E+00	627	8.967E+00	668	6.636E+00	709	2.719E+00	750	8.528E-01
587	7.369E+00	628	8.981E+00	669	6.527E+00	710	2.660E+00	751	8.293E-01
588	7.379E+00	629	8.971E+00	670	6.410E+00	711	2.587E+00	752	8.054E-01
589	7.411E+00	630	8.993E+00	671	6.320E+00	712	2.505E+00	753	7.853E-01
590	7.430E+00	631	8.974E+00	672	6.213E+00	713	2.455E+00	754	7.628E-01
591	7.452E+00	632	8.983E+00	673	6.101E+00	714	2.385E+00	755	7.382E-01
592	7.485E+00	633	8.980E+00	674	5.994E+00	715	2.328E+00	756	7.213E-01
593	7.509E+00	634	8.981E+00	675	5.888E+00	716	2.265E+00	757	7.006E-01
594	7.547E+00	635	8.962E+00	676	5.786E+00	717	2.202E+00	758	6.819E-01
595	7.595E+00	636	8.930E+00	677	5.693E+00	718	2.157E+00	759	6.616E-01
596	7.621E+00	637	8.907E+00	678	5.581E+00	719	2.090E+00	760	6.405E-01
597	7.647E+00	638	8.877E+00	679	5.469E+00	720	2.036E+00	761	6.229E-01
598	7.695E+00	639	8.848E+00	680	5.363E+00	721	1.971E+00	762	6.023E-01
599	7.744E+00	640	8.824E+00	681	5.246E+00	722	1.921E+00	763	5.882E-01
600	7.793E+00	641	8.786E+00	682	5.155E+00	723	1.877E+00	764	5.764E-01
601	7.841E+00	642	8.737E+00	683	5.064E+00	724	1.813E+00	765	5.595E-01
602	7.889E+00	643	8.698E+00	684	4.939E+00	725	1.770E+00	766	5.366E-01
603	7.941E+00	644	8.645E+00	685	4.839E+00	726	1.715E+00	767	5.258E-01
604	8.009E+00	645	8.587E+00	686	4.740E+00	727	1.674E+00	768	5.030E-01
605	8.049E+00	646	8.546E+00	687	4.659E+00	728	1.623E+00	769	4.964E-01
606	8.125E+00	647	8.479E+00	688	4.530E+00	729	1.581E+00	770	4.793E-01
607	8.150E+00	648	8.413E+00	689	4.446E+00	730	1.529E+00	771	4.704E-01
608	8.214E+00	649	8.337E+00	690	4.343E+00	731	1.491E+00	772	4.531E-01
609	8.259E+00	650	8.284E+00	691	4.251E+00	732	1.443E+00	773	4.396E-01
610	8.322E+00	651	8.213E+00	692	4.148E+00	733	1.399E+00	774	4.282E-01
611	8.382E+00	652	8.120E+00	693	4.055E+00	734	1.364E+00	775	4.138E-01
612	8.434E+00	653	8.045E+00	694	3.953E+00	735	1.327E+00	776	4.073E-01
613	8.480E+00	654	7.969E+00	695	3.868E+00	736	1.290E+00	777	3.917E-01
614	8.514E+00	655	7.873E+00	696	3.796E+00	737	1.250E+00	778	3.880E-01
615	8.572E+00	656	7.787E+00	697	3.695E+00	738	1.218E+00	779	3.888E-01
616	8.621E+00	657	7.708E+00	698	3.613E+00	739	1.182E+00	780	3.895E-01
617	8.675E+00	658	7.615E+00	699	3.522E+00	740	1.144E+00		
618	8.718E+00	659	7.533E+00	700	3.445E+00	741	1.111E+00		
619	8.743E+00	660	7.443E+00	701	3.339E+00	742	1.075E+00		
620	8.774E+00	661	7.343E+00	702	3.265E+00	743	1.051E+00		
621	8.821E+00	662	7.238E+00	703	3.185E+00	744	1.014E+00		
622	8.859E+00	663	7.149E+00	704	3.100E+00	745	9.948E-01		
623	8.879E+00	664	7.032E+00	705	3.027E+00	746	9.607E-01		
624	8.908E+00	665	6.939E+00	706	2.952E+00	747	9.271E-01		
625	8.925E+00	666	6.852E+00	707	2.864E+00	748	9.010E-01		

**CIE 1931 x y Chromaticity Diagram**



**7-Step Chromaticity Quadrangles**



**[Goniophotometer System]**

The Stabilization time: **30 minutes**

Total operating time for luminous intensity distribution: **1.0 hour**

Test orientation: **Base up**


**Electrical Measurement**

Input Voltage (V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.01	60	0.0574	6.4700	0.9392

**Photometric Measurement**

Luminous Flux (lm)	Efficacy (lm/W)	I <sub>max</sub> (cd)	S/MH (C0/180)	S/MH (C90/270)
590.953	91.34	1306	0.54	0.6

**Luminous Intensity Distribution**



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle (50% I <sub>max</sub> ):	34.2	34.1	34.0	34.1	34.1
Field Angle (10% I <sub>max</sub> ):	67.0	66.5	65.8	66.4	66.4

**Luminous Intensity (cd) Distribution Data**

C \ Y	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	1292	1292	1292	1292	1292	1292	1292	1292
5.0°	1258	1244	1231	1212	1196	1181	1173	1169
10.0°	1127	1090	1048	1004	977	958	951	953
15.0°	822	790	756	725	698	682	676	677
20.0°	538	525	516	498	477	464	458	454
25.0°	340	336	333	324	308	299	295	287
30.0°	203	202	199	195	185	180	178	170
35.0°	114	114	112	108	103	101	100	97
40.0°	62	62	58	56	54	54	54	53
45.0°	33	33	32	32	30	30	30	29
50.0°	20	20	19	19	19	19	19	18
55.0°	15	14	14	14	14	14	14	14
60.0°	12	12	11	11	11	11	11	11
65.0°	9	9	8	8	8	8	8	8
70.0°	6	6	6	6	5	5	5	5
75.0°	4	4	4	4	3	3	3	3
80.0°	2	2	2	2	2	2	2	2
85.0°	1	1	1	1	1	1	1	1
90.0°	0	0	0	0	0	0	0	0
95.0°	0	0	0	0	0	0	0	0
100.0°	0	0	0	0	0	0	0	0
105.0°	0	0	0	0	0	0	0	0
110.0°	0	0	0	0	0	0	0	0
115.0°	0	0	0	0	0	0	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	0	0	0	0	0	1	1	1
145.0°	1	1	1	1	1	1	1	1
150.0°	1	1	1	1	1	1	1	1
155.0°	1	1	1	1	1	1	1	1
160.0°	2	2	2	2	2	2	2	2
165.0°	1	1	1	1	1	1	1	1
170.0°	1	1	1	1	1	1	1	1
175.0°	1	1	1	1	1	1	1	1
180.0°	1	1	1	1	1	1	1	1

Luminous Intensity (cd) Distribution Data (cont.)

C Y	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	1292	1292	1292	1292	1292	1292	1292	1292
5.0°	1186	1205	1231	1256	1277	1288	1289	1280
10.0°	991	1007	1038	1071	1107	1144	1159	1164
15.0°	715	733	757	792	833	871	887	882
20.0°	479	486	501	523	546	568	574	571
25.0°	301	302	307	317	326	339	345	349
30.0°	180	179	177	182	181	189	197	203
35.0°	102	98	95	97	96	103	109	114
40.0°	54	52	53	52	52	55	59	62
45.0°	29	30	30	30	30	31	33	34
50.0°	19	19	19	19	19	20	21	21
55.0°	14	14	14	14	14	14	15	15
60.0°	11	11	11	12	12	12	12	12
65.0°	8	8	8	9	9	9	9	9
70.0°	6	6	6	6	6	6	7	6
75.0°	4	4	4	4	4	4	4	4
80.0°	2	2	2	2	2	3	3	3
85.0°	1	1	1	1	1	1	1	1
90.0°	0	0	0	0	0	0	0	0
95.0°	0	0	0	0	0	0	0	0
100.0°	0	0	0	0	0	0	0	0
105.0°	0	0	0	0	0	0	0	0
110.0°	0	0	0	0	0	0	0	0
115.0°	0	0	0	0	0	0	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	0	0	0	0	0	0	0	0
145.0°	0	0	0	0	0	0	0	0
150.0°	0	0	0	0	0	0	0	0
155.0°	0	0	0	0	0	0	0	0
160.0°	0	0	0	0	0	0	0	0
165.0°	0	0	0	0	0	0	0	0
170.0°	1	1	1	1	1	1	1	1
175.0°	1	1	1	1	1	1	1	1
180.0°	1	1	1	1	1	1	1	1

**Zonal Lumen Density Measurement**

Deg	Flux (lm)	%
0-5	30.1	5.09
5-10	81.7	13.82
10-15	107.1	18.12
15-20	103.6	17.54
20-25	85.3	14.44
25-30	62.6	10.59
30-35	41.8	7.07
35-40	25.7	4.35
40-45	15.5	2.62
45-50	9.8	1.67
50-55	7.1	1.20
55-60	5.8	0.99
60-65	4.8	0.81
65-70	3.6	0.61
70-75	2.5	0.43
75-80	1.6	0.26
80-85	0.8	0.13
85-90	0.3	0.05
90-95	0.0	0.00
95-100	0.0	0.00
100-105	0.0	0.00
105-110	0.0	0.00
110-115	0.0	0.00
115-120	0.0	0.00
120-125	0.0	0.00
125-130	0.0	0.01
130-135	0.0	0.01
135-140	0.1	0.01
140-145	0.1	0.02
145-150	0.2	0.03
150-155	0.2	0.04
155-160	0.2	0.03
160-165	0.2	0.03
165-170	0.1	0.02
170-175	0.1	0.01
175-180	0.0	0.00

Deg	Flux (lm)	%
0-5	30.1	5.09
0-10	111.7	18.91
0-15	218.8	37.03
0-20	322.5	54.57
0-25	407.8	69.01
0-30	470.4	79.60
0-35	512.2	86.67
0-40	537.9	91.02
0-45	553.4	93.64
0-50	563.2	95.31
0-55	570.3	96.51
0-60	576.2	97.50
0-65	581.0	98.31
0-70	584.6	98.92
0-75	587.1	99.35
0-80	588.6	99.61
0-85	589.4	99.74
0-90	589.7	99.79
0-95	589.7	99.79
0-100	589.7	99.79
0-105	589.7	99.79
0-110	589.7	99.79
0-115	589.7	99.79
0-120	589.7	99.79
0-125	589.7	99.79
0-130	589.8	99.80
0-135	589.8	99.81
0-140	589.9	99.82
0-145	590.0	99.84
0-150	590.2	99.87
0-155	590.4	99.91
0-160	590.6	99.94
0-165	590.8	99.97
0-170	590.9	99.99
0-175	590.9	100.00
0-180	591.0	100.00

Test Item	Test Voltage (V)	Frequency (Hz)	Test Result
Total Harmonic Distortion:	120.0	60	14.18%

## 6. Product Photo



## Directions

1. The information marked "superscript #" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
2. This report includes some test methods are not in NVLAP accreditation scope marked \*.
3. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $K=2$  with the 95% confidence interval.
6. This report cannot be reproduced except in full, without prior written approval of the Company.
7. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

\*\*\*\*\*END OF REPORT\*\*\*\*\*