## PL H 6W BYP E26 TITANIUM LED SERIES











- Built-in universal voltage driver Bypass installation
- Ompatible with E26 bases
- Exceptional efficacy 93 LPW
- Lasts 4 times longer than CFL
- Compact form factor fits most fixtures
- Available in 3000K, 3500K & 4000K
- Lamp ambient temperature: -4°F to 113°F (-20°C to 45°C)
















### PL PRODUCT FEATURES

#### **BYPass Installation**

This PL H lamp requires bypassing the ballast during installation and runs directly off line voltage to eliminate compatibility problems, incidental power loss, lifetime issues, and maintenance costs associated with ballasts.




#### Adjustable Base





This PL H lamp features a base that can be rotated 310° to fit any socket configuration. After installation simply rotate the lamp to achieve maximum light output.

# PL H 6W BYP E26 TITANIUM LED SERIES










Base: E26

**Voltage:** 120-277V

Dimmable: No PF: 0.9

Lifetime: 50,000 hrs
Weight: 0.15lb / 68g



## SPECIFICATIONS\*

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
6PLH/830/BYP/E26	57925	6	Warm White 3000K	80	550	92	110°
6PLH/835/BYP/E26	57926	6	Neutral White 3500K	80	550	92	110°
6PLH/840/BYP/E26	57927	6	Cool White 4000K	80	560	93	110°

- \* Specification data is preliminary and may be subject to change
- \*\* Suitable for damp locations. Not for use where directly exposed to weather or water
- \*\*\* Not intended for use in enclosed fixtures
- \*\*\*\* Full installation guide and more details available on website