



IES LM-79-08

MEASUREMENT AND TEST REPORT

For

GREEN CREATIVE LTD

Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, KL, Hong Kong

Test Model: 7MR16DIM/927NF25/RC

| | |
|-----------------------|---|
| Report Type: | Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution |
| Reviewed By: | George Chen <i>George Chen</i> |
| Report Number: | KS2211025-54679E-10 |
| Test Date: | 2021-03-04 to 2021-03-05 |
| Report Date: | 2021-11-16 |
| Reviewed By: | Bill Xiong / EE Engineer |
| Approved by: | Bay Area Compliance Laboratories Corp. (Dongguan). No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China. Tel: +86-0769-86858888 Fax: +86-0769-86858588 |

1. Product Description[#]

General Information:

Two samples were received on 2021-03-04. One was tested in integrating sphere and the other was tested in goniophotometer.

Model Tested: 7MR16DIM/927NF25/RC
Manufacturer: GREEN CREATIVE LTD
Brand Name: GREEN CREATIVE
Product Designation: Directional LED Lamp
Burning Time Before Test: 0hour(For New Products)

Rated Values:

Rated Voltage/Frequency: 12 VAC 60Hz
Rated Power: 7W
Nominal CCT: 2700K
Nominal Lumen Output: 490lm

Note:

- The applicant GREEN CREATIVE LTD declare that their products with model 7MR16DIM/927NF25/RC are the same to the products in report#KS2210303-27529E-10-3 and is authorized by original applicant to use their test data.
- All the data in previous report (KS2210303-27529E-10-3) is shared in this report.

2. Standards Used

- IES LM-79-08: Approved Method: Electrical & Photometric Measurement of Solid-state Lighting Products
- ANSI C82.77-10-2014: Harmonic Emission Limits – Related Power Quality Requirements for Lighting Equipment.
- IES TM-30-18: IES Method for Evaluating Light Source Color Rendition (This method is not in IAS accreditation scope)

3. Description of Test Equipment

| Device | Manufacture | Model No | Serial No | Calibration date | Calibration due date |
|---|-------------|-------------|-------------------|------------------|----------------------|
| 2.0m integrating sphere | EVERFINE | R98 | 11010018 | 2020-10-21 | 2021-10-20 |
| spectroradiometer | EVERFINE | HAAS-2000 | G112048TS81331121 | 2020-10-21 | 2021-10-20 |
| Digital Power Meter | EVERFINE | PF2010A | 1011004 | 2020-10-21 | 2021-10-20 |
| Digital CC&CV DC Power Supply | EVERFINE | WY305-V1 | 1101047 | 2020-07-01 | 2021-06-30 |
| Rapid Recording Photometer | EVERFINE | PHOTO-2000F | 1007010 | 2020-11-05 | 2021-11-04 |
| Standard Light Source | EVERFINE | D204 | N/A | 2020-10-20 | 2021-10-19 |
| Special zero-voltage synchronous switching AC | EVERFINE | DPS1010-YF | 1011001T | 2021-01-04 | 2022-01-03 |
| AC POWER SUPPLY | EVERFINE | VPS1030 PWM | 1012017 | 2021-01-04 | 2022-01-03 |

| Device | Manufacture | Model No | Serial No | Calibration date | Calibration due date |
|----------------------------------|-------------|----------|-------------------|------------------|----------------------|
| Digital CC&CV DC Power Supply | EVERFINE | WY12010 | 1009009 | 2021-01-04 | 2022-01-03 |
| Digital power meter | YOKOGAWA | WT-210 | 91j926132 | 2021-01-04 | 2022-01-03 |
| full-field speed goniophotometer | EVERFINE | GO-R5000 | YG108492N10120001 | 2020-03-13 | 2021-03-12 |
| Wireless Remote Sensor | N/A | 433MHz | N/A | 2020-03-12 | 2021-03-11 |
| Standard Light Source | EVERFINE | D908 | 1012003 | 2020-10-20 | 2021-10-19 |

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with IES LM-79-08. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at 25°C±1°C during measurement. And relative humidity is less than 65%.

Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

4 π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is U=2.1% (K=2), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is U=22K (K=2), at the 95% confidence level. The uncertainty of the CRI is U=2.1(K=2), at the 95% confidence level.

The uncertainty of power meter AC current U=0.19 % of rdg, AC Voltage U=0.18% of rdg, Power U=0.46% (K=2), at the 95% confidence level.

Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The vertical angle (γ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

The uncertainty of the luminous intensity is U=2.00% (K=2), at the 95% confidence level.

Fidelity Index and Gamut Index Calculation

The R_i , R_g was calculated according to IES TM-30-18 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

5. Test Result

[Integrating Sphere System]

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Base Up**


Photometric and Electrical Measurement Result







| Voltage(V) | Frequency(Hz) | Current(A) | Power (W) | Power Factor | Luminous Flux(lm) | Efficacy(lm/W) |
|------------|---------------|------------|-----------|--------------|-------------------|----------------|
| 12.0 | 60 | 0.5572 | 6.255 | 0.9355 | 528.64 | 84.51 |

| Radiant Flux (W) | CCT (K) | Duv | x | y | u' | v' |
|------------------|---------|----------|--------|--------|--------|--------|
| 1.929 | 2756 | 0.001510 | 0.4579 | 0.4142 | 0.2596 | 0.5284 |


Color Rendering Index

| | | | |
|------------|------------|------------|------------|
| Ra | | | |
| 96.3 | | | |
| R1 | R2 | R3 | R4 |
| 97 | 99 | 99 | 96 |
| R5 | R6 | R7 | R8 |
| 97 | 98 | 95 | 89 |
| R9 | R10 | R11 | R12 |
| 77 | 96 | 98 | 85 |
| R13 | R14 | R15 | |
| 98 | 98 | 94 | |






Relative Spectral Power Distribution




| nm | mW | nm | mW | nm | mW | nm | mW | nm | mW |
|-----|-----------|-----|-----------|-----|-----------|-----|-----------|-----|-----------|
| 380 | 1.916E-01 | 421 | 2.001E-01 | 462 | 3.507E+00 | 503 | 4.057E+00 | 544 | 6.355E+00 |
| 381 | 1.792E-01 | 422 | 2.187E-01 | 463 | 3.358E+00 | 504 | 4.126E+00 | 545 | 6.411E+00 |
| 382 | 1.313E-01 | 423 | 2.374E-01 | 464 | 3.210E+00 | 505 | 4.205E+00 | 546 | 6.467E+00 |
| 383 | 1.251E-01 | 424 | 2.619E-01 | 465 | 3.094E+00 | 506 | 4.282E+00 | 547 | 6.511E+00 |
| 384 | 1.294E-01 | 425 | 2.841E-01 | 466 | 3.016E+00 | 507 | 4.328E+00 | 548 | 6.559E+00 |
| 385 | 1.004E-01 | 426 | 3.144E-01 | 467 | 2.981E+00 | 508 | 4.394E+00 | 549 | 6.621E+00 |
| 386 | 1.042E-01 | 427 | 3.436E-01 | 468 | 2.975E+00 | 509 | 4.474E+00 | 550 | 6.667E+00 |
| 387 | 8.742E-02 | 428 | 3.750E-01 | 469 | 2.958E+00 | 510 | 4.537E+00 | 551 | 6.720E+00 |
| 388 | 8.750E-02 | 429 | 4.144E-01 | 470 | 2.952E+00 | 511 | 4.592E+00 | 552 | 6.759E+00 |
| 389 | 7.731E-02 | 430 | 4.586E-01 | 471 | 2.947E+00 | 512 | 4.641E+00 | 553 | 6.806E+00 |
| 390 | 6.308E-02 | 431 | 4.893E-01 | 472 | 2.927E+00 | 513 | 4.700E+00 | 554 | 6.852E+00 |
| 391 | 6.794E-02 | 432 | 5.300E-01 | 473 | 2.879E+00 | 514 | 4.759E+00 | 555 | 6.909E+00 |
| 392 | 7.096E-02 | 433 | 5.672E-01 | 474 | 2.829E+00 | 515 | 4.817E+00 | 556 | 6.953E+00 |
| 393 | 6.731E-02 | 434 | 6.190E-01 | 475 | 2.772E+00 | 516 | 4.869E+00 | 557 | 6.994E+00 |
| 394 | 5.838E-02 | 435 | 6.736E-01 | 476 | 2.710E+00 | 517 | 4.916E+00 | 558 | 7.054E+00 |
| 395 | 6.108E-02 | 436 | 7.349E-01 | 477 | 2.651E+00 | 518 | 4.970E+00 | 559 | 7.085E+00 |
| 396 | 5.555E-02 | 437 | 7.880E-01 | 478 | 2.597E+00 | 519 | 5.027E+00 | 560 | 7.135E+00 |
| 397 | 4.858E-02 | 438 | 8.623E-01 | 479 | 2.559E+00 | 520 | 5.072E+00 | 561 | 7.171E+00 |
| 398 | 4.849E-02 | 439 | 9.438E-01 | 480 | 2.543E+00 | 521 | 5.121E+00 | 562 | 7.220E+00 |
| 399 | 4.589E-02 | 440 | 1.026E+00 | 481 | 2.538E+00 | 522 | 5.157E+00 | 563 | 7.256E+00 |
| 400 | 4.498E-02 | 441 | 1.120E+00 | 482 | 2.549E+00 | 523 | 5.228E+00 | 564 | 7.302E+00 |
| 401 | 5.317E-02 | 442 | 1.228E+00 | 483 | 2.592E+00 | 524 | 5.271E+00 | 565 | 7.344E+00 |
| 402 | 4.759E-02 | 443 | 1.343E+00 | 484 | 2.628E+00 | 525 | 5.337E+00 | 566 | 7.395E+00 |
| 403 | 4.810E-02 | 444 | 1.463E+00 | 485 | 2.692E+00 | 526 | 5.384E+00 | 567 | 7.435E+00 |
| 404 | 5.014E-02 | 445 | 1.626E+00 | 486 | 2.760E+00 | 527 | 5.439E+00 | 568 | 7.489E+00 |
| 405 | 5.212E-02 | 446 | 1.799E+00 | 487 | 2.826E+00 | 528 | 5.490E+00 | 569 | 7.521E+00 |
| 406 | 5.156E-02 | 447 | 1.987E+00 | 488 | 2.900E+00 | 529 | 5.536E+00 | 570 | 7.575E+00 |
| 407 | 6.238E-02 | 448 | 2.216E+00 | 489 | 2.978E+00 | 530 | 5.599E+00 | 571 | 7.622E+00 |
| 408 | 5.783E-02 | 449 | 2.470E+00 | 490 | 3.050E+00 | 531 | 5.659E+00 | 572 | 7.662E+00 |
| 409 | 6.364E-02 | 450 | 2.727E+00 | 491 | 3.123E+00 | 532 | 5.698E+00 | 573 | 7.726E+00 |
| 410 | 6.811E-02 | 451 | 3.030E+00 | 492 | 3.188E+00 | 533 | 5.757E+00 | 574 | 7.777E+00 |
| 411 | 7.613E-02 | 452 | 3.325E+00 | 493 | 3.259E+00 | 534 | 5.812E+00 | 575 | 7.825E+00 |
| 412 | 8.117E-02 | 453 | 3.601E+00 | 494 | 3.339E+00 | 535 | 5.871E+00 | 576 | 7.876E+00 |
| 413 | 9.508E-02 | 454 | 3.855E+00 | 495 | 3.410E+00 | 536 | 5.935E+00 | 577 | 7.947E+00 |
| 414 | 9.727E-02 | 455 | 4.041E+00 | 496 | 3.482E+00 | 537 | 5.987E+00 | 578 | 8.004E+00 |
| 415 | 1.079E-01 | 456 | 4.155E+00 | 497 | 3.562E+00 | 538 | 6.041E+00 | 579 | 8.049E+00 |
| 416 | 1.248E-01 | 457 | 4.219E+00 | 498 | 3.647E+00 | 539 | 6.091E+00 | 580 | 8.128E+00 |
| 417 | 1.295E-01 | 458 | 4.169E+00 | 499 | 3.723E+00 | 540 | 6.134E+00 | 581 | 8.179E+00 |
| 418 | 1.516E-01 | 459 | 4.046E+00 | 500 | 3.797E+00 | 541 | 6.198E+00 | 582 | 8.254E+00 |
| 419 | 1.622E-01 | 460 | 3.904E+00 | 501 | 3.894E+00 | 542 | 6.255E+00 | 583 | 8.312E+00 |
| 420 | 1.817E-01 | 461 | 3.726E+00 | 502 | 3.968E+00 | 543 | 6.311E+00 | 584 | 8.395E+00 |

| nm | mW | nm | mW | nm | mW | nm | mW | nm | mW |
|-----|-----------|-----|-----------|-----|-----------|-----|-----------|-----|-----------|
| 585 | 8.464E+00 | 626 | 1.172E+01 | 667 | 8.639E+00 | 708 | 3.511E+00 | 749 | 1.091E+00 |
| 586 | 8.536E+00 | 627 | 1.172E+01 | 668 | 8.494E+00 | 709 | 3.421E+00 | 750 | 1.055E+00 |
| 587 | 8.633E+00 | 628 | 1.173E+01 | 669 | 8.351E+00 | 710 | 3.344E+00 | 751 | 1.026E+00 |
| 588 | 8.698E+00 | 629 | 1.175E+01 | 670 | 8.228E+00 | 711 | 3.248E+00 | 752 | 1.008E+00 |
| 589 | 8.787E+00 | 630 | 1.175E+01 | 671 | 8.090E+00 | 712 | 3.149E+00 | 753 | 9.709E-01 |
| 590 | 8.869E+00 | 631 | 1.173E+01 | 672 | 7.926E+00 | 713 | 3.070E+00 | 754 | 9.430E-01 |
| 591 | 8.961E+00 | 632 | 1.175E+01 | 673 | 7.805E+00 | 714 | 2.987E+00 | 755 | 9.203E-01 |
| 592 | 9.047E+00 | 633 | 1.170E+01 | 674 | 7.650E+00 | 715 | 2.918E+00 | 756 | 8.876E-01 |
| 593 | 9.136E+00 | 634 | 1.171E+01 | 675 | 7.512E+00 | 716 | 2.831E+00 | 757 | 8.623E-01 |
| 594 | 9.244E+00 | 635 | 1.167E+01 | 676 | 7.371E+00 | 717 | 2.768E+00 | 758 | 8.425E-01 |
| 595 | 9.321E+00 | 636 | 1.167E+01 | 677 | 7.225E+00 | 718 | 2.675E+00 | 759 | 8.148E-01 |
| 596 | 9.424E+00 | 637 | 1.163E+01 | 678 | 7.101E+00 | 719 | 2.608E+00 | 760 | 8.011E-01 |
| 597 | 9.508E+00 | 638 | 1.159E+01 | 679 | 6.962E+00 | 720 | 2.547E+00 | 761 | 7.694E-01 |
| 598 | 9.595E+00 | 639 | 1.153E+01 | 680 | 6.796E+00 | 721 | 2.463E+00 | 762 | 7.543E-01 |
| 599 | 9.696E+00 | 640 | 1.150E+01 | 681 | 6.680E+00 | 722 | 2.395E+00 | 763 | 7.330E-01 |
| 600 | 9.787E+00 | 641 | 1.143E+01 | 682 | 6.551E+00 | 723 | 2.341E+00 | 764 | 7.111E-01 |
| 601 | 9.904E+00 | 642 | 1.135E+01 | 683 | 6.403E+00 | 724 | 2.273E+00 | 765 | 6.893E-01 |
| 602 | 9.985E+00 | 643 | 1.130E+01 | 684 | 6.258E+00 | 725 | 2.212E+00 | 766 | 6.755E-01 |
| 603 | 1.009E+01 | 644 | 1.123E+01 | 685 | 6.149E+00 | 726 | 2.142E+00 | 767 | 6.532E-01 |
| 604 | 1.018E+01 | 645 | 1.116E+01 | 686 | 6.020E+00 | 727 | 2.079E+00 | 768 | 6.272E-01 |
| 605 | 1.029E+01 | 646 | 1.108E+01 | 687 | 5.870E+00 | 728 | 2.026E+00 | 769 | 6.140E-01 |
| 606 | 1.038E+01 | 647 | 1.098E+01 | 688 | 5.739E+00 | 729 | 1.965E+00 | 770 | 5.919E-01 |
| 607 | 1.046E+01 | 648 | 1.091E+01 | 689 | 5.616E+00 | 730 | 1.913E+00 | 771 | 5.723E-01 |
| 608 | 1.056E+01 | 649 | 1.082E+01 | 690 | 5.499E+00 | 731 | 1.849E+00 | 772 | 5.640E-01 |
| 609 | 1.066E+01 | 650 | 1.072E+01 | 691 | 5.361E+00 | 732 | 1.792E+00 | 773 | 5.458E-01 |
| 610 | 1.073E+01 | 651 | 1.059E+01 | 692 | 5.241E+00 | 733 | 1.746E+00 | 774 | 5.334E-01 |
| 611 | 1.083E+01 | 652 | 1.052E+01 | 693 | 5.124E+00 | 734 | 1.700E+00 | 775 | 5.114E-01 |
| 612 | 1.092E+01 | 653 | 1.039E+01 | 694 | 4.996E+00 | 735 | 1.645E+00 | 776 | 5.022E-01 |
| 613 | 1.101E+01 | 654 | 1.029E+01 | 695 | 4.884E+00 | 736 | 1.600E+00 | 777 | 4.868E-01 |
| 614 | 1.107E+01 | 655 | 1.018E+01 | 696 | 4.772E+00 | 737 | 1.564E+00 | 778 | 4.703E-01 |
| 615 | 1.117E+01 | 656 | 1.008E+01 | 697 | 4.655E+00 | 738 | 1.511E+00 | 779 | 4.709E-01 |
| 616 | 1.122E+01 | 657 | 9.947E+00 | 698 | 4.544E+00 | 739 | 1.459E+00 | 780 | 4.715E-01 |
| 617 | 1.128E+01 | 658 | 9.827E+00 | 699 | 4.433E+00 | 740 | 1.418E+00 | | |
| 618 | 1.136E+01 | 659 | 9.687E+00 | 700 | 4.328E+00 | 741 | 1.375E+00 | | |
| 619 | 1.144E+01 | 660 | 9.573E+00 | 701 | 4.209E+00 | 742 | 1.340E+00 | | |
| 620 | 1.147E+01 | 661 | 9.439E+00 | 702 | 4.110E+00 | 743 | 1.303E+00 | | |
| 621 | 1.152E+01 | 662 | 9.323E+00 | 703 | 4.013E+00 | 744 | 1.266E+00 | | |
| 622 | 1.156E+01 | 663 | 9.185E+00 | 704 | 3.903E+00 | 745 | 1.220E+00 | | |
| 623 | 1.160E+01 | 664 | 9.038E+00 | 705 | 3.791E+00 | 746 | 1.190E+00 | | |
| 624 | 1.163E+01 | 665 | 8.909E+00 | 706 | 3.700E+00 | 747 | 1.160E+00 | | |
| 625 | 1.168E+01 | 666 | 8.780E+00 | 707 | 3.604E+00 | 748 | 1.124E+00 | | |

CIE 1931xy Chromaticity Diagram



7-Step Chromaticity Quadrangles



[Goniophotometer System]

Total operating time for luminous intensity distribution: **1.0 hour**

Test orientation: **Base Up**


Electrical Measurement

| Input Voltage(V) | Frequency(Hz) | Input Current(A) | Power (W) | Power Factor |
|------------------|---------------|------------------|-----------|--------------|
| 12.00 | 60 | 0.5593 | 6.276 | 0.9347 |

Photometric Measurement

| Luminous Flux(lm) | Efficacy(lm/W) | $I_{max}(cd)$ | S/MH(C0/180) | S/MH(C90/270) |
|-------------------|----------------|---------------|--------------|---------------|
| 533.347 | 84.98 | 3141 | 0.33 | 0.33 |

Luminous Intensity Distribution



| | C0/180 | C45/225 | C90/270 | C135/315 | AVG. |
|------------------------------|--------|---------|---------|----------|------|
| Beam Angle(50% I_{max}): | 20.7 | 21.0 | 21.0 | 20.6 | 20.8 |
| Field Angle(10% I_{max}): | 36.4 | 37.1 | 36.9 | 36.0 | 36.6 |

Luminous Intensity (cd) Distribution Data

| C y | 0° | 22.5° | 45° | 67.5° | 90° | 112.5° | 135° | 157.5° |
|--------|------|-------|------|-------|------|--------|------|--------|
| 0.0° | 3138 | 3138 | 3138 | 3138 | 3138 | 3138 | 3138 | 3138 |
| 5.0° | 2739 | 2785 | 2834 | 2859 | 2845 | 2814 | 2810 | 2808 |
| 10.0° | 1712 | 1753 | 1797 | 1828 | 1813 | 1781 | 1740 | 1731 |
| 15.0° | 633 | 656 | 685 | 697 | 697 | 676 | 646 | 636 |
| 20.0° | 241 | 248 | 262 | 259 | 257 | 252 | 241 | 244 |
| 25.0° | 129 | 138 | 149 | 149 | 140 | 130 | 126 | 127 |
| 30.0° | 66 | 73 | 80 | 83 | 77 | 67 | 64 | 63 |
| 35.0° | 37 | 40 | 44 | 44 | 42 | 37 | 33 | 31 |
| 40.0° | 23 | 24 | 25 | 25 | 26 | 25 | 24 | 22 |
| 45.0° | 15 | 15 | 15 | 16 | 16 | 16 | 16 | 16 |
| 50.0° | 10 | 11 | 11 | 12 | 12 | 11 | 11 | 10 |
| 55.0° | 8 | 8 | 9 | 9 | 9 | 8 | 8 | 8 |
| 60.0° | 6 | 6 | 6 | 6 | 6 | 5 | 6 | 5 |
| 65.0° | 4 | 5 | 5 | 5 | 5 | 4 | 5 | 4 |
| 70.0° | 3 | 4 | 4 | 4 | 3 | 4 | 4 | 4 |
| 75.0° | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| 80.0° | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| 85.0° | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 90.0° | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 0 |
| 95.0° | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| 100.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 105.0° | 0 | 2 | 2 | 0 | 0 | 2 | 1 | 0 |
| 110.0° | 0 | 1 | 0 | 0 | 0 | 1 | 1 | 0 |
| 115.0° | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 |
| 120.0° | 1 | 4 | 4 | 0 | 3 | 5 | 4 | 0 |
| 125.0° | 0 | 1 | 0 | 0 | 1 | 2 | 1 | 0 |
| 130.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 135.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 140.0° | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 |
| 145.0° | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 150.0° | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 155.0° | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| 160.0° | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| 165.0° | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| 170.0° | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| 175.0° | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 180.0° | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |

Luminous Intensity (cd) Distribution Data (cont.)

| C y | 180° | 202.5° | 225° | 247.5° | 270° | 292.5° | 315° | 337.5° |
|--------|------|--------|------|--------|------|--------|------|--------|
| 0.0° | 3138 | 3138 | 3138 | 3138 | 3138 | 3138 | 3138 | 3138 |
| 5.0° | 2686 | 2691 | 2687 | 2673 | 2637 | 2612 | 2623 | 2631 |
| 10.0° | 1592 | 1589 | 1579 | 1589 | 1576 | 1554 | 1549 | 1555 |
| 15.0° | 567 | 561 | 568 | 571 | 569 | 555 | 540 | 549 |
| 20.0° | 235 | 243 | 256 | 252 | 250 | 239 | 224 | 224 |
| 25.0° | 124 | 137 | 150 | 150 | 142 | 127 | 119 | 119 |
| 30.0° | 60 | 68 | 76 | 81 | 73 | 63 | 59 | 59 |
| 35.0° | 30 | 31 | 35 | 37 | 35 | 32 | 31 | 33 |
| 40.0° | 20 | 20 | 20 | 20 | 21 | 21 | 23 | 22 |
| 45.0° | 14 | 13 | 13 | 13 | 14 | 14 | 15 | 14 |
| 50.0° | 9 | 9 | 8 | 8 | 9 | 9 | 9 | 9 |
| 55.0° | 7 | 7 | 7 | 6 | 6 | 7 | 7 | 7 |
| 60.0° | 5 | 5 | 5 | 6 | 5 | 5 | 5 | 5 |
| 65.0° | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| 70.0° | 3 | 4 | 4 | 4 | 3 | 4 | 4 | 3 |
| 75.0° | 2 | 3 | 3 | 2 | 2 | 3 | 3 | 2 |
| 80.0° | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| 85.0° | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 90.0° | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 |
| 95.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 100.0° | 0 | 1 | 0 | 0 | 0 | 1 | 1 | 0 |
| 105.0° | 0 | 1 | 0 | 0 | 0 | 1 | 1 | 0 |
| 110.0° | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 |
| 115.0° | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| 120.0° | 1 | 3 | 2 | 0 | 0 | 2 | 3 | 0 |
| 125.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 130.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 135.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 140.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 145.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 150.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 155.0° | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 160.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 165.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 170.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 175.0° | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 180.0° | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |

Zonal Lumen Density Measurement

| Deg | Flux (lm) | % |
|---------|-----------|-------|
| 0-5 | 70.2 | 13.16 |
| 5-10 | 155.7 | 29.20 |
| 10-15 | 126.0 | 23.63 |
| 15-20 | 63.5 | 11.90 |
| 20-25 | 38.2 | 7.16 |
| 25-30 | 25.0 | 4.68 |
| 30-35 | 14.7 | 2.77 |
| 35-40 | 9.4 | 1.77 |
| 40-45 | 6.7 | 1.26 |
| 45-50 | 5.0 | 0.93 |
| 50-55 | 3.8 | 0.71 |
| 55-60 | 3.0 | 0.55 |
| 60-65 | 2.4 | 0.46 |
| 65-70 | 2.0 | 0.38 |
| 70-75 | 1.6 | 0.30 |
| 75-80 | 1.1 | 0.22 |
| 80-85 | 0.7 | 0.13 |
| 85-90 | 0.4 | 0.07 |
| 90-95 | 0.2 | 0.04 |
| 95-100 | 0.2 | 0.04 |
| 100-105 | 0.3 | 0.05 |
| 105-110 | 0.3 | 0.06 |
| 110-115 | 0.2 | 0.04 |
| 115-120 | 0.5 | 0.09 |
| 120-125 | 0.5 | 0.10 |
| 125-130 | 0.1 | 0.02 |
| 130-135 | 0.1 | 0.01 |
| 135-140 | 0.1 | 0.02 |
| 140-145 | 0.2 | 0.03 |
| 145-150 | 0.2 | 0.04 |
| 150-155 | 0.3 | 0.05 |
| 155-160 | 0.3 | 0.05 |
| 160-165 | 0.2 | 0.04 |
| 165-170 | 0.1 | 0.03 |
| 170-175 | 0.1 | 0.01 |
| 175-180 | 0.0 | 0.00 |

| Deg | Flux (lm) | % |
|-------|-----------|--------|
| 0-5 | 70.2 | 13.16 |
| 0-10 | 225.9 | 42.36 |
| 0-15 | 352.0 | 65.99 |
| 0-20 | 415.4 | 77.89 |
| 0-25 | 453.6 | 85.05 |
| 0-30 | 478.6 | 89.73 |
| 0-35 | 493.3 | 92.50 |
| 0-40 | 502.8 | 94.27 |
| 0-45 | 509.5 | 95.53 |
| 0-50 | 514.5 | 96.46 |
| 0-55 | 518.2 | 97.17 |
| 0-60 | 521.2 | 97.72 |
| 0-65 | 523.6 | 98.18 |
| 0-70 | 525.6 | 98.56 |
| 0-75 | 527.3 | 98.86 |
| 0-80 | 528.4 | 99.08 |
| 0-85 | 529.1 | 99.21 |
| 0-90 | 529.5 | 99.28 |
| 0-95 | 529.7 | 99.32 |
| 0-100 | 529.9 | 99.36 |
| 0-105 | 530.2 | 99.41 |
| 0-110 | 530.5 | 99.47 |
| 0-115 | 530.7 | 99.51 |
| 0-120 | 531.2 | 99.60 |
| 0-125 | 531.7 | 99.70 |
| 0-130 | 531.8 | 99.72 |
| 0-135 | 531.9 | 99.73 |
| 0-140 | 532.0 | 99.75 |
| 0-145 | 532.2 | 99.78 |
| 0-150 | 532.4 | 99.82 |
| 0-155 | 532.7 | 99.87 |
| 0-160 | 532.9 | 99.92 |
| 0-165 | 533.1 | 99.96 |
| 0-170 | 533.3 | 99.99 |
| 0-175 | 533.3 | 100.00 |
| 0-180 | 533.3 | 100.00 |

6. Product Photo



Directions

1. The information marked "superscript #" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
2. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
3. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of the Company.
6. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

*****END OF REPORT*****