

LM-79-08 TEST REPORT

for

GREEN CREATIVE LTD

Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, KL,
Hong Kong

LED Lamp

Model: 9FA19DIM/950

Laboratory: Leading Testing Laboratories

NVLAP CODE: 200960-0

3rd Floor, Bld. 2, NO. 96 Longchuanwu Rd Qianjiang Economy Dev. Zone, YuhangDist,
Hangzhou, Zhejiang Province, China 311100

Tel: +86571 86376106

www.ledtestlab.com

Report No.: HZ21120007av

The laboratory that conducted the testing detailed in this report has been accredited for SSL by NVLAP.

Review by:



Engineer: April Zou

Mar. 01, 2022

Approved by:



Manager: Jim Zhang

Mar. 01, 2022

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TEST SUMMARY

Sample Tested: 9FA19DIM/950

Luminous Efficacy (Lumens /Watt)	Total Luminous Flux (Lumens)	Power (Watts)	Power Factor
126.6	968.7	7.65	0.8155
CCT (K)	CRI	Stabilization Time (Light & Power)	
5169	92.7	60	

Table 1: Executive Data Summary

Note: The above results are recorded/ derived from measurements made using an Integrating Sphere.

Test specifications:

Date of Receipt	: Dec. 03, 2021
Date of Test	: Feb. 25, 2022
Test item	: Total Luminous Flux, Luminous Distribution Intensity, Luminous Efficacy, Correlated Color Temperature, Color Rendering Index, Chromaticity Coordinate, Electrical parameters
Reference Standard	: IESNA LM-79-2008 Approved Method for the Electrical and Photometric Measurements of Solid-State Lighting Products ANSI/IES TM-30-18 IES Method for Evaluating Light Source Color Rendition

TABLE OF CONTENT

LM-79-08 TEST REPORT.....	1
TEST SUMMARY	2
SAMPLE PHOTO	4
TEST RESULTS	5
Sphere-Spectroradiometer Method.....	5
Goniophotometer Method	6
Spectral Power Distribution - Sphere Spectroradiometer Method	7
Chromaticity Diagram - Sphere Spectroradiometer Method.....	8
Nominal CCT Quadrangles – Sphere Spectroradiometer Method	9
Color Rendition Report – Sphere Spectroradiometer Method	10
Zonal Lumen Tabulation- Goniophotometer Method	11
Illuminance Plots- Goniophotometer Method	12
Luminous Intensity Distribution Plots- Goniophotometer Method.....	13
Luminous Intensity Data- Goniophotometer Method	14
EQUIPMENT LIST	15
TEST METHODS	15
Seasoning of SSL Product.....	15
Sphere-Spectroradiometer Method- Photometric and Electrical Measurements.....	15
Goniophotometer Method	16
Photometric and Electrical Measurements	16
Color Characteristics Measurements.....	16
Color Spatial Uniformity.....	16

SAMPLE PHOTO



Figure 1- Overview of the sample

Equipment Under Test(EUT)

Name	: LED Lamp
Model	: 9FA19DIM/950
Electrical Ratings	: 120V, 60Hz, 9W
Product Description	: 5000K
Manufacturer	: GREEN CREATIVE LTD
Address	: Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, KL, Hong Kong

TEST RESULTS

Test ambient temperature was 26.0 °C.

Base orientation was horizontal. Test was conducted without a dimmer in the circuit.

The stabilization time of the sample was 60 minutes, and the total operating time including stabilization was 65 minutes.

Sphere-Spectroradiometer Method

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.078
Power Factor	0.8155
Test Power (W)	7.65
THD A%	57.39
Luminous Efficacy (lm/W)	126.6
Total Luminous Flux (lm)	968.7
Color Rendering Index (CRI)	92.7
R9	70.4
Correlated Color Temperature (CCT)(K)	5169
Chromaticity Chroma x	0.3405
Chromaticity Chroma y	0.3494
Chromaticity Chroma u	0.2092
Chromaticity Chroma v	0.3220
Duv	0.0008
Chromaticity Chroma u'	0.2092
Chromaticity Chroma v'	0.4829

Special Color Rendering Indices	
R1	93.3
R2	96.1
R3	95.2
R4	91.3
R5	91.5
R6	91.2
R7	94.4
R8	88.4
R9	70.4
R10	88.4
R11	90.8
R12	67.6
R13	94.7
R14	97.3

Table 2: Test data per Sphere-Spectroradiometer Method

Note: According to CIE 1976 (u',v') diagram, $u' = u = 4x/(-2x+12y+3)$, $v' = 3v/2 = 9y/(-2x+12y+3)$.

Goniophotometer Method

Test ambient temperature was 25.1 °C.

The photometric distance is 2.47 m.

Luminous data was taken at 0.5 vertical intervals and 10 horizontal intervals.

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.078
Power Factor	0.8197
Power (W)	7.70
Luminous Efficacy (lm/W)	128.4
Total Luminous Flux (lm)	988.7
Beam Angle (°)	302.6 (0°-180°) / 297.8 (90°-270°)
Center Beam Candle Power (cd)	54.5
Maximum Beam Candle Power (cd)	112.0 (At: C=202.5, Gamma=80.0)
Spacing Criteria	2.27 (0°-180°) / 2.11 (90°-270°)
Zonal Lumens in the 0 °-60 °Zone	25.80%
Zonal Lumens in the 60 °-90 °Zone	31.30%
Zonal Lumens in the 90 °-120 °Zone	28.79%
Zonal Lumens in the 120 °-180 °Zone	14.12%

Table 3: Test data per Goniophotometer Method

Spectral Power Distribution - Sphere Spectroradiometer Method




Chart 1: Spectral Power Distribution

Spectral Distribution over Visible Wavelength							
WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)
380	1.13E-04	485	8.23E-03	590	1.36E-02	695	5.12E-03
385	1.17E-04	490	8.42E-03	595	1.35E-02	700	4.43E-03
390	1.20E-04	495	8.98E-03	600	1.34E-02	705	3.92E-03
395	1.20E-04	500	9.86E-03	605	1.34E-02	710	3.46E-03
400	1.30E-04	505	1.08E-02	610	1.33E-02	715	3.05E-03
405	1.56E-04	510	1.16E-02	615	1.33E-02	720	2.68E-03
410	2.33E-04	515	1.24E-02	620	1.31E-02	725	2.33E-03
415	4.02E-04	520	1.29E-02	625	1.29E-02	730	2.03E-03
420	7.23E-04	525	1.33E-02	630	1.27E-02	735	1.76E-03
425	1.33E-03	530	1.37E-02	635	1.23E-02	740	1.51E-03
430	2.36E-03	535	1.39E-02	640	1.19E-02	745	1.32E-03
435	4.18E-03	540	1.41E-02	645	1.14E-02	750	1.14E-03
440	7.23E-03	545	1.42E-02	650	1.09E-02	755	9.74E-04
445	1.26E-02	550	1.43E-02	655	1.03E-02	760	8.56E-04
450	2.14E-02	555	1.43E-02	660	9.64E-03	765	7.32E-04
455	2.69E-02	560	1.42E-02	665	8.96E-03	770	6.26E-04
460	2.16E-02	565	1.41E-02	670	8.24E-03	775	5.36E-04
465	1.60E-02	570	1.41E-02	675	7.55E-03	780	4.67E-04
470	1.33E-02	575	1.40E-02	680	6.86E-03		
475	1.05E-02	580	1.38E-02	685	6.20E-03		
480	8.58E-03	585	1.37E-02	690	5.59E-03		

Table 4: Spectral Power Distribution Numerical Data per Sphere - Spectroradiometer Method

Chromaticity Diagram - Sphere Spectroradiometer Method




Chart 2: Chromaticity Diagram per Sphere - Spectroradiometer Method

Note: The location on the diagram of the tristimulus coordinates are indicated by the blue diamond.

Nominal CCT Quadrangles – Sphere Spectroradiometer Method




Chart 3: Plot of Lamp x/y coordinates on CIE 1931 Chromaticity Diagram

Color Rendition Report – Sphere Spectroradiometer Method


ANSI/IES TM-30-18 Color Rendition Report

Source: LED

Manufacturer: GREEN CREATIVE LTD

Date: 2022/02/25

Model: 9FA19DIM/950



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3405
 y 0.3494
 u' 0.2092
 v' 0.4829

CIE 13.3-1995
(CRI)
 R_a 93
 R_g 70

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

Chart 4: Full Report Created with the IES TM-30 Calculator

Note: The values in this diagram might be a little different from the values in Table 2 due to rounding.

Zonal Lumen Tabulation- Goniophotometer Method

$\gamma(^{\circ})$	Lumens	% Total
0- 10	5.495	0.56%
10- 20	17.431	1.76%
20- 30	32.805	3.32%
30- 40	49.685	5.03%
40- 50	66.743	6.75%
50- 60	82.881	8.38%
60- 70	96.084	9.72%
70- 80	104.96	10.62%
80- 90	108.42	10.97%
90-100	105.634	10.68%
100-110	96.703	9.78%
110-120	82.281	8.32%
120-130	63.433	6.42%
130-140	42.911	4.34%
140-150	23.409	2.37%
150-160	8.702	0.88%
160-170	1.12	0.11%
170-180	0.015	0.00%
Total	988.7	100%

$\gamma(^{\circ})$	Lumens	% Total
0-130	912.555	92.30%
130-180	76.157	7.70%
0-180	988.7	100%

Table 5: Zonal Lumen

Illuminance Plots- Goniophotometer Method




Chart 5: Illuminance Plot (Footcandles)

Luminous Intensity Distribution Plots- Goniophotometer Method




Chart 6: Isocandela Plot




Chart 7: Polar Candela Distribution

Luminous Intensity Data- Goniophotometer Method

Table--1 UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	54.5	54.5	54.5	54.5	54.5	54.5	54.5	54.5	54.5	54.5	54.5	54.5	54.5	54.5	54.5	54.5			
5	57.2	56.8	56.6	56.1	57.1	58.4	58.0	57.1	57.5	58.3	58.6	57.1	56.0	56.3	57.0	57.6			
10	56.0	56.7	59.8	60.6	60.8	62.6	62.0	58.4	57.1	59.5	61.2	58.1	54.1	54.6	55.8	57.1			
15	55.4	57.2	60.0	60.7	59.1	66.3	64.1	59.9	58.7	65.2	67.6	59.7	57.1	58.6	58.9	58.1			
20	60.0	65.2	65.3	59.3	58.6	75.2	71.5	64.8	66.8	72.8	79.4	63.0	60.7	66.2	64.8	59.9			
25	65.2	75.7	71.3	63.1	60.3	76.2	74.8	70.1	72.3	78.9	82.8	67.9	65.9	72.4	69.8	64.1			
30	69.6	85.4	76.8	67.8	65.5	76.3	77.0	75.3	77.5	85.3	82.5	72.2	70.8	76.0	71.8	69.3			
35	75.1	91.0	81.7	72.3	72.2	78.3	79.3	79.3	82.1	89.1	84.5	76.4	75.3	78.6	75.1	73.7			
40	80.6	92.2	85.7	76.7	77.9	80.9	82.3	83.4	86.4	92.5	86.9	80.5	79.5	80.6	78.3	77.8			
45	85.6	94.3	89.0	81.1	82.8	84.0	85.3	87.3	90.6	96.0	89.7	84.6	82.6	82.3	81.1	81.7			
50	88.8	97.0	91.7	85.5	87.2	87.2	88.5	91.0	95.0	99.8	93.3	88.4	85.3	83.9	83.2	85.1			
55	91.8	99.4	94.6	89.3	90.5	90.4	92.0	95.1	98.4	103	96.0	91.6	87.5	86.0	84.9	87.8			
60	93.7	102	97.2	92.8	93.0	93.4	95.0	99.0	102	106	98.6	93.9	88.9	87.6	85.7	89.6			
65	95.5	104	99.6	95.7	95.3	96.1	97.4	102	104	109	100	95.8	89.4	89.0	86.2	90.9			
70	96.9	106	102	98.0	97.3	98.5	99.4	104	105	111	102	96.9	89.7	89.8	86.9	91.9			
75	97.5	107	103	99.4	99.2	100	100	106	106	112	102	97.0	90.3	89.9	87.5	92.6			
80	97.7	107	103	100	100	101	101	106	107	112	103	97.1	90.2	89.2	87.2	92.8			
85	98.0	107	103	100	101	101	101	106	106	111	102	96.5	90.3	88.1	86.9	92.5			
90	97.7	107	103	99.8	101	100	99.9	105	105	110	101	95.2	89.3	86.0	85.8	91.8			
95	96.6	105	102	98.5	100	98.9	98.4	103	104	107	99.0	92.9	87.5	83.2	84.1	90.1			
100	95.0	103	100.0	96.3	98.9	96.6	96.1	100.0	102	104	96.2	90.1	85.2	80.2	81.8	87.8			
105	92.7	99.4	97.2	93.4	96.5	93.5	93.1	96.5	99.5	100	92.8	86.7	82.2	76.6	78.9	84.8			
110	89.8	95.4	93.6	89.7	93.0	89.4	89.4	92.3	96.2	95.3	88.7	82.7	78.5	72.3	75.5	81.2			
115	85.7	90.3	89.1	85.3	88.8	84.5	85.1	87.2	91.7	89.1	83.2	77.9	73.7	67.3	71.2	76.9			
120	80.8	84.1	83.6	80.4	83.6	78.9	79.9	81.8	86.2	81.4	77.3	72.4	68.3	62.2	66.2	72.3			
125	75.2	77.5	77.5	75.1	77.5	72.9	74.1	75.5	79.3	62.5	70.7	66.0	61.8	57.1	60.5	67.5			
130	68.8	70.6	70.5	69.2	70.9	66.0	67.3	68.6	71.4	45.4	63.6	58.0	53.7	51.5	54.6	61.6			
135	60.6	63.0	62.9	61.9	62.9	58.4	59.9	60.5	59.6	40.5	54.6	48.7	45.8	44.6	48.0	54.2			
140	51.4	55.1	54.2	53.7	53.0	50.9	52.0	51.6	40.3	35.1	43.0	38.6	38.0	36.4	41.2	45.9			
145	42.0	45.3	44.8	43.9	42.6	42.5	43.1	41.6	33.0	27.3	30.6	29.1	29.1	28.0	32.3	37.1			
150	31.6	34.9	34.4	33.2	32.5	33.8	32.3	30.9	28.0	13.3	19.0	20.6	19.2	18.9	23.2	28.2			
155	20.9	23.5	23.9	24.0	23.8	24.5	20.2	20.0	19.0	9.30	10.7	12.7	11.2	11.8	15.1	17.8			
160	11.9	15.2	16.0	15.9	15.5	12.9	11.4	12.1	9.75	5.08	5.66	3.54	6.01	6.34	7.36	10.1			
165	1.64	3.75	4.96	4.97	4.12	3.16	1.44	1.95	0.55	0.44	0.50	0.43	0.53	0.79	0.96	1.23			
170	0.27	0.28	0.31	0.32	0.31	0.30	0.27	0.25	0.23	0.22	0.19	0.16	0.18	0.21	0.22	0.24			
175	0.09	0.10	0.10	0.10	0.11	0.15	0.15	0.14	0.14	0.15	0.14	0.13	0.12	0.11	0.10	0.08			
180	0.08	0.09	0.08	0.08	0.08	0.08	0.05	0.09	0.08	0.10	0.10	0.08	0.08	0.08	0.08	0.08			

Table 6: Luminous Intensity Data

EQUIPMENT LIST

Test Equipment	Model	Equipment No.	Calibration Date	Calibration Due date
Goniophotometer system	GO-R5000	HZTE011-01	Aug. 05, 2021	Aug. 04, 2022
Digital Power Meter	PF2010A	HZTE028-01	Aug. 05, 2021	Aug. 04, 2022
AC Power Supply	DPS1060	HZTE001-06	Aug. 05, 2021	Aug. 04, 2022
DC Power Supply	WY12010	HZTE004-03	Aug. 05, 2021	Aug. 04, 2022
Temperature recorder	JM624U	HZTE018-08	Aug. 05, 2021	Aug. 04, 2022
Temperature and humidity recorder	JR900	HZTE018-01	Aug. 05, 2021	Aug. 04, 2022
Standard source	D908	HZTE012-01	Aug. 05, 2021	Aug. 04, 2022
Integrate Sphere system	3M	HZTE015-04	Aug. 05, 2021	Aug. 04, 2022
Digital Power Meter	WT210	HZTE008-01	Aug. 05, 2021	Aug. 04, 2022
AC Power Supply	PCR 500L	HZTE001-07	Aug. 05, 2021	Aug. 04, 2022
DC Power Supply	IT6154	HZTE004-04	Aug. 05, 2021	Aug. 04, 2022
Standard source	SCL-1400	HZTE012-02	Aug. 05, 2021	Aug. 04, 2022
Temperature and humidity recorder	JR900	HZTE018-02	Aug. 05, 2021	Aug. 04, 2022
Temperature Meter	TES1310	HZTE017-01	Aug. 05, 2021	Aug. 04, 2022

Table 7: Test Equipment List

TEST METHODS

Seasoning of SSL Product

For the purpose of rating new SSL products, SSL products shall be tested with no seasoning. Therefore, no seasoning was performed.

Sphere-Spectroradiometer Method- Photometric and Electrical Measurements

A Labsphere Model CDS 2100 Spectroradiometer and Two Meter Sphere was used to measure correlated color temperature, chromaticity coordinates, and the color rendering index for each SSL unit. The coating reflectance of each sphere is 98%. The measure geometry is 4π . Self-absorption correction is conducted in testing. Bandwidth of spectroradiometer is 350nm-1050nm.

Ambient temperature was measured at a position inside the sphere. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

The standard reference of the integrated sphere system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Standards and Technology.

The uncertainty of integrating sphere system reported in this document is expanded uncertainty is 2.1% with a coverage factor $k=2$.

Goniophotometer Method

Photometric and Electrical Measurements

An EVERFINE Type C Model GO-R5000 Goniophotometer was used to measure the intensity at each angle of distribution for each sample. The photometric distance is 2.475m for near-field measurement or 30m for far-field measurement. Bandwidth of spectroradiometer is 380nm-780nm.

Ambient temperature was measured at the same height of the sample mounted on the Goniophotometer equipment. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Everfine Digital Power Meter.

Some graphics were created with Photometric Plus software.

The standard reference of the Goniophotometer system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Metrology P.R. China.

The uncertainty of goniophotometer system reported in this document is expanded uncertainty is 2.3% with a coverage factor $k=2$.

Color Characteristics Measurements


The color characteristics of SSL products include chromaticity coordinates, correlated color temperature, and color rendering index. These characteristics of SSL products may be spatially non-uniform, and thus, in order that they can be specified accurately, the color quantities shall be measured as values that are spatially average, weighted to intensity, over the angular range where light is intentionally emitted from the SSL product. The color characteristics measurements are using gonio-spectroradiometer.

Color Spatial Uniformity

The characteristics of SSL products may be spatially non-uniform, the chromaticity coordinate shall be measured at two vertical planes ($C=0^\circ/180^\circ$ and $C=90^\circ/270^\circ$) and at 10° or less intervals for vertical angle until the light output dropped to below 10% of the peak intensity. The averaged weighted chromaticity coordinate

was calculated from these points. The data was then analyzed to check for delta color differences of the u' , v' chromaticity coordinates. The spatial non-uniformity of chromaticity, $\Delta u'v'$, is determined as the maximum deviation (distance on the CIE (u' , v') diagram) among all measured points from the spatially averaged chromaticity coordinate.

The geometry for the chromaticity measurement using gonio-spectroradiometer is shown as following.



*** End of Report ***

This report is considered invalidated without the Special Seal for Inspection of the LTL. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of LTL, this test report shall not be copied except in full and published as advertisement.