Project Name:	Туре:
Part Number:	Date:



## A21 LED 16.5W HO 277V

## **FEATURES**

- Direct line voltage 120-277V installation; Need to bypass existing ballasts
- A21 bulb shape design, emitting 330° uniform light
- Frosted diffuser maintains low glare
- Replaces 125W incandescent lamps
- High lumen output up to 2050lm
- Suitable for use in enclosed fixtures
- Exceptional high efficacy up to 124LPW
- UL damp location
- Temperature rating: -4°F/20°C 113°F/45°C
- Rated lifetime (L70): 40,000hrs
- 5 years limited warranty
- Suitable for Post-top / Bollard application








SPECIFICATION											
Product	Model	CCT	Base	Wattage	Lumens	CRI	Efficacy (LPW)	Power Factor	THD	Dim.	Cert.
58238	16.5A21/830/277V/R	3000K	E26	16.5	2000	82	121	0.9	<20%	No	ES pending
58239	16.5A21/840/277V/R	4000K	E26	16.5	2000	82	121	0.9	<20%	No	ES pending
58240	16.5A21/850/277V/R	5000K	E26	16.5	2050	82	124	0.9	<20%	No	ES pending

## **DIMENSION & WEIGHT**



Model	16.5A21/xxx/277V/R
Base	E26
MOL	5.0" (127mm)
Dia.	2.55" (65mm)
Weight	0.50lb / 227g

Where xxx means 824-965 which indicates CRI and color temperature