
















































































# COMMERCIAL DOWNLIGHT SELECTION GUIDE



SELECTION GUIDE		 		DualDim  		 		DualDim  		DualDim 			
		 		 		 		 		 			
The Contractor's Choice		The Problem Solver		The Best in Class		The All In One		The Shallow One					
Size		6", 8"		4", 6", 8", 9.5"		4", 6", 8", 9.5"		4", 6", 8"		4", 6", 8"			
Shape		Round		Round		Round / Square		Round / Square		Round			
Application	Retail	●●●		●●●		●●●		●●●		●●●			
	Education	●●●		●●●		●●●		●●●		●●●			
	Healthcare	●●●		●●●		●●●		●●●		●●●			
	Hospitality	●●●		●●●		●●●		●●●		●●●			
	Office	●●●		●●●		●●●		●●●		●●●			
	Retrofit	✓		✓		✓		✓		✓			
	New Construction	✓ <sup>1</sup>		✓ <sup>1</sup>		✓ <sup>1</sup>		✓		✓ <sup>1</sup>			
Specifications	Max Lumen/size @40K	1600 (6") / 2125 (8")		1400 (4") / 2100 (6") / 3000 (8") / 3650 (9.5")		900 (4") / 1650 (6") / 2900 (6" HO) / 2100 (8") / 4200 (8" HO) / 4000 (9.5")		2500 (4") / 5000 (6") / 5000 (8") / 5000 (9.5")		2000 (4" RD&SQ, 6" SQ) / 4000 (6" RD) / 6000 (8" RD)		650 (4") / 1100 (6") / 1850 (8")	
	LPW	Up to 125		Up to 140		Up to 100		Up to 92		Up to 110		Up to 90	
	CRI	80		80		90		90 / 97 <sup>2</sup>		90		90	
	Optical Distribution	WD		WD		WD / MD		VN / NR / MD / WD / Wall Wash <sup>3</sup>		WD / MD / Wall Wash		Very Wide (110°)	
	Reflector Depth	Shallow		Shallow		Deep		Very Deep		Deep		Flush or Very Shallow	
	Visual Cut-off	75° to 80°		75° to 80°		55°		35° to 45°		57° to 72°		N/A	
	Trim Style & Finish	White Baffle		White Baffle		Clear / Matte White		Clear / Matte White / Matte Black		Clear / White Baffle / Black Baffle / Matte White / Matte Black		White and Trimless	
	CCT	35K / 40K		Selectable 30K / 35K / 40K		Selectable 27K / 30K / 35K / 40K / 50K		27K / 30K / 35K / 40K / 50K		Selectable 27K / 30K / 35K / 40K / 50K		Selectable 27K / 30K / 35K / 40K / 50K	
	Environmental rating	Wet		Wet		Wet		Damp / Wet		Wet		Wet	
	IC-Rated	✓		✓		✓ <sup>4</sup>				✓		✓	
	Air-Tight	✓		✓		✓				✓		✓	
	Voltage	120-277V		120V / 120-277V		120V / 120-277V		120V / 120-277V / 347V (opt.)		120-277V		120-277V	
	EnergyStar	✓		✓		✓		✓		✓		✓	
	Title 24 JA8	✓		✓		✓				✓		✓	
	Emergency	Field Installed EM Inverter <sup>5</sup>		Field Installed EM Inverter <sup>5</sup>		Field Installed EM Inverter <sup>5</sup>		Factory Installed EM Driver or Field Installable EM Inverter <sup>5</sup>		Factory Installed EM Driver or Field Installable EM Inverter <sup>5</sup>		Field Installable EM Inverter <sup>5</sup>	
Special Features	SelectDrive 	✓		✓		✓		✓		✓		✓	
	SelectKelvin 	✓		✓		✓		✓		✓		✓	
	DualDim 	✓		✓		✓		✓		✓		✓	
	TRUE CHROMA 							✓ <sup>6</sup>					
Dimming & Control Options	Line Voltage Dimming (Forward & Reverse Phase)	✓ <sup>7</sup>		✓		✓		✓		✓		✓	
	0-10V Dimming	✓		✓		✓		✓		✓		✓	
	Enlighted							✓					
	Lutron EcoSystem							✓					
	Philips EasySense							✓					

1. New Construction Accessory sold separately. 2. SPECFIT CRI 97 with TRUE CHROMA feature is available in 3000K only. 3. SPECFIT Wall Wash Optical Distribution is available with field installable wall wash accessory. 4. SLFT 9.5" and HO versions are not IC rated. 5. Compatibility details refer to <https://greencreative.com/emergency-accessories/>. 6. TRUE CHROMA is available with CRI97 only. 7. Line Voltage Dimming are only available for 6" and 8".



Ceiling Crossover Guide		GREEN CREATIVE Fixture					Installed Lamp Type		
Ceiling Height	Lumens	INNOFIT SERIES	SELECTFIT SERIES	SPECFIT SERIES	NYX SERIES	MULTIFIT SERIES	CFL	Metal Halide	Incandescent
<b>Ceiling 8'-20'</b>	500lm to 1,500lm	 4" (INNOFIT PLUS)  6" (INNOFIT G2 & INNOFIT PLUS)  8" (INNOFIT G2 & INNOFIT PLUS)	 4"  6"  8"	 4"  6"  8"  9.5"	 4"  6"  8"	 4"  6"  8"	 1x32W  1x26W  1x18W	 50W	 150W A21  120W BR40  65W BR30
<b>Ceiling 20'-30'</b>	2,000lm to 3,000lm	 8" (INNOFIT G2 & INNOFIT PLUS)  9.5" (INNOFIT PLUS)	 6" HO  8" HO  8" HO  9.5" HO	 4"  6"  8"  9.5"	 4"  6"  8"	 2x32W  1x57W  2x26W  1x42W	 70W	 200W A21	
<b>Ceiling 30'-40'</b>	3,000lm to 5,000lm	 9.5" (INNOFIT PLUS)	 8" HO  9.5" HO	 6"  8"  9.5"	 6" (RD)  8"	 2x57W  2x42W	 150W  100W  70W	 300W BR40	