

COMMERCIAL DOWNLIGHT SELECTION GUIDE

GREEN CREATIVE offers a wide selection of innovative commercial downlight products. Select from a large range of product features and benefits to fulfill your commercial lighting needs. From the everyday downlight, to the flexible problem solver, to the high end specification grade luminaire, GREEN CREATIVE has the right fixture for the job.



SELECTION GUIDE

		 The Contractor's Choice	 The Problem Solver	 The Best in Class	
Size		6", 8"	4", 6", 8", 9.5"	4", 6", 6" HO, 8", 8" HO, 9.5"	4", 6", 8", 9.5"
Shape		Round		Round	Round / Square
Application	Retail				
	Education				
	Healthcare				
	Hospitality				
	Office				
	Retrofit	✓	✓	✓	✓
	New Construction	✓ ¹	✓ ¹	✓ ¹	✓
Specifications	Max Lumen/size @40K	1600 (6") / 2125 (8")	1400 (4") / 2100 (6") / 3000 (8") / 3650 (9.5")	900 (4") / 1650 (6") / 2900 (6" HO) / 2100 (8") / 4200 (8" HO) / 4000 (9.5")	2500 (4") / 5000 (6") / 5000 (8") / 5000 (9.5")
	LPW	Up to 125	Up to 140	Up to 100	Up to 92
	CRI	80 (min.)	80 (min.)	90 (min.)	90 / 97 ²
	Optical Distribution	WD	WD	WD / MD	VN / NR / FL / WD / Wall Wash ³
	Reflector Depth	Shallow	Shallow	Deep	Very Deep
	Trim Style & Finish	White Baffle	White Baffle	Clear / Matte White	Clear / Matte White / Matte Black
	CCT	35K / 40K	Selectable 30K / 35K / 40K	Selectable 27K / 30K / 35K / 40K / 50K	27K / 30K / 35K / 40K / 50K
	Environmental rating	Wet	Wet	Wet	Damp / Wet
	IC-Rated	✓	✓	✓ ⁴	
	Air-Tight	✓	✓	✓	
	Voltage	120-277V	120V / 120-277V	120V / 120-277V	120V / 120-277V / 347V (opt)
	EnergyStar	✓	✓	✓	✓
	Emergency	Field Installed 23W Emergency Driver		Field Installed 23W Emergency Driver	Factory Installed 10W Emergency Driver
Special Features	SelectDrive	✓	✓	✓	✓
	SelectKelvin		✓	✓	
	DualDim			✓	
	TRUE CHROMA				✓ ⁶
Dimming & Control Options	Line Voltage Dimming (Forward & Reverse Phase)		✓ ⁷	✓	✓
	0-10V Dimming	✓	✓	✓	✓
	Enlighted				✓
	Lutron EcoSystem				✓
	Philips EasySense				✓

1. New Construction Accessory sold separately. 2. SPECFIT CRI 97 with TRUE CHROMA feature is available in 3000K only. 3. SPECFIT Wall Wash Optical Distribution is available with field installable wall wash accessory. 4. SLFT 9.5" and HO versions are not IC rated. 5. The 23W GREEN CREATIVE Driver is field installed and suitable for up to 8" only for INNOFIT Plus and SELECTFIT. 6. TRUE CHROMA is available with CRI97 only. 7. Line Voltage Dimming are only available for 6" and 8".



Ceiling Crossover Guide		GREEN CREATIVE Fixture			Installed Lamp Type		
Ceiling Height	Lumens	INNOFIT ⁺ SERIES	SELECTFIT SERIES	SPECFIT SERIES	CFL	Metal Halide	Incandescent
Ceiling 8'-20'	500lm to 1,500lm	 4" (INNOFIT PLUS) 6" (INNOFIT G2 & INNOFIT PLUS) 8" (INNOFIT G2 & INNOFIT PLUS)	 4" 6" 8"	 4" 6" 8" 9.5"	 1x32W 1x26W 1x18W	 50W	 150W A21 120W BR40 65W BR30
Ceiling 20'-30'	2,000lm to 3,000lm	 8" (INNOFIT G2 & INNOFIT PLUS) 9.5" (INNOFIT PLUS)	 6" HO 8" 8" HO 9.5"	 4" 6" 8" 9.5"	 2x32W 1x57W 2x26W 1x42W	 70W	 200W A21
Ceiling 30'-40'	3,000lm to 5,000lm	 9.5" (INNOFIT PLUS)	 8" HO 9.5"	 6" 8" 9.5"	 2x57W 2x42W	 150W 100W 70W	 300W BR40

041023