





COMMERCIAL DOWNLIGHT SELECTION GUIDE

GREEN CREATIVE offers a wide selection of innovative commercial downlight products. Select from a large range of product features and benefits to fulfill your commercial lighting needs. From the everyday downlight, to the flexible problem solver, to the high end specification grade luminaire, GREEN CREATIVE has the right fixture for the job.



SELECTION GUIDE

| | |  |  |  |
|---------------------------|--|---|--|---|
| | | The Contractor's Choice | The Problem Solver | The Best in Class |
| | |  |  |  |
| Size | | 4", 6", 8", 9.5" | 4", 6", 8", 9.5" | 4", 6", 8", 9.5" |
| Shape | | Round | Round | Round / Square |
| Application | Retail |  |  |  |
| | Education |  |  |  |
| | Healthcare |  |  |  |
| | Hospitality |  |  |  |
| | Office |  |  |  |
| | Retrofit | ✓ | ✓ | ✓ |
| | New Construction | ✓ ¹ | ✓ ¹ | ✓ |
| Specifications | Max Lumen/size @40K | 1090 / 1768 / 2354 / 3621 | 969 / 1557 / 1953 / 3135 | 2500 / 5000 / 5000 / 5000 |
| | LPW/Fixture size @40K | 109 / 136 / 140 / 139 | 81 / 104 / 103 / 105 | 92 / 87 / 87 / 87 |
| | CRI | 82 (min.) | 82 (min.) | 90 / 97 ² |
| | Optical Distribution | WD | WD | VN / NR / FL / WD / Wall Wash ³ |
| | Reflector Depth | Shallow | Deep | Very Deep |
| | Trim Style & Finish | White Baffle | Matte White | Clear / Matte White / Matte Black |
| | CCT | 27K / 30K / 35K / 40K / 50K | Selectable 27K / 50K or 30K / 35K / 40K | 27K / 30K / 35K / 40K / 50K |
| | Environmental rating | Wet | Wet | Damp |
| | IC-Rated | ✓ | ✓ ⁴ | |
| | Air-Tight | ✓ | ✓ | |
| | Voltage | 120V / 120-277V | 120V / 120-277V | 120V / 120-277V / 347V (opt.) |
| | EnergyStar | ✓ | ✓ | ✓ |
| | Emergency | Field Installed 23W Emergency Driver | Field Installed 23W Emergency Driver | Factory Installed 10W Emergency Driver |
| Special Features | SelectDrive  | ✓ | ✓ | ✓ |
| | SelectKelvin  | | ✓ | |
| | TRUE CHROMA  | | | ✓ ⁶ |
| Dimming & Control Options | Line Voltage Dimming (Forward & Reverse Phase) | ✓ | ✓ | ✓ |
| | 0-10V Dimming | ✓ | ✓ | ✓ |
| | Enlighted | | | ✓ |
| | Lutron EcoSystem | | | ✓ |
| | Philips EasySense | | | ✓ |




















¹New Construction Accessory sold separately. ²SPECFIT CRI 97 with TRUE CHROMA feature is available in 3000K only. ³SPECFIT Wall Wash Optical Distribution is available with field installable wall wash accessory. ⁴SELECTFIT 9.5" is not IC-rated. ⁵The 23W GREEN CREATIVE Driver is field installed and suitable for up to 8" only for INNOFIT and SELECTFIT. ⁶TRUE CHROMA is available with CRI97 only.



Ceiling Crossover Guide

GREEN CREATIVE Fixture

Installed Lamp Type

| Ceiling Height | Lumens | INNOFIT SERIES | SELECTFIT SERIES | SPECFIT SERIES | CFL | Metal Halide | Incandescent |
|--|--------------------------|---|---|---|---|--|--|
|  Ceiling 8'-20' | 500lm to 1,500lm |  4" 6" 8" |  4" 6" 8" |  4" 6" 8" 9.5" |  1x32W 1x26W 1x18W |  50W |  150W A21 120W BR40 65W BR30 |
|  Ceiling 20'-30' | 2,000lm to 3,000lm |  8" 9.5" |  8" 9.5" |  4" 6" 8" 9.5" |  2x32W 1x57W 2x26W 1x42W |  70W |  200W A21 |
|  Ceiling 30'-40' | 3,000lm to 5,000lm |  9.5" |  9.5" |  6" 8" 9.5" |  2x57W 2x42W |  150W 100W 70W |  300W BR40 |

032322