


Project Name:	Type:
Part Number:	Date:

# DIRECT T8 VALUE SELECT

## FEATURES

- Plug & Play – Easy to install
- Only compatible with Instant Start ballasts
- Replaces 32W T8 4' Fluorescent lamp
- Exceptional high efficacy up to 157LPW
- Opaque glass body reduces glare
- 310° extra wide light emitting area
- Suitable for use in enclosed fixture
- Meets NSF Requirements (use of a shatter guard required)
- UL damp location
- Temperature rating: -4°F/-20 °C- 95 °F/35 °C
- Rated lifetime (L70): 50,000hrs
- 5 years limited warranty
- Suitable for all indoor general lighting application



## SPECIFICATIONS

Product	Model	Equiv.	Input Voltage*	Wattage	Lumens	CCT	CRI	Efficacy (LPW)	Power Factor	THD	Beam Angle	Dim.	Fixture Rating	DLC
98551	10.5T8/4F/830/IS/DIR	32W	120-277V	10.5	1600	3000K	82	152	0.9	<20%	160°	No	Enclosed	✓
98552	10.5T8/4F/835/IS/DIR	32W	120-277V	10.5	1600	3500K	82	152	0.9	<20%	160°	No	Enclosed	✓
98553	10.5T8/4F/840/IS/DIR	32W	120-277V	10.5	1650	4000K	82	157	0.9	<20%	160°	No	Enclosed	✓
98554	10.5T8/4F/850/IS/DIR	32W	120-277V	10.5	1650	5000K	82	157	0.9	<20%	160°	No	Enclosed	✓
98557	13T8/4F/840/IS/DIR	32W	120-277V	13	2000	4000K	82	154	0.9	<20%	160°	No	Enclosed	✓
98558	13T8/4F/850/IS/DIR	32W	120-277V	13	2000	5000K	82	154	0.9	<20%	160°	No	Enclosed	✓

\* Ballast Dependent. Please refer to [www.greencreative.com](http://www.greencreative.com) for full compatibility list

## BALLAST PERFORMANCE


Ballast Factor	Bare Lamp Wattage	System Wattage	3000K Lumens	3500K Lumens	4000K Lumens	5000K Lumens
Low Ballast Factor (0.77)	10.5	11	1250	1250	1300	1300
Normal Ballast Factor (0.88)	10.5	13	1600	1600	1650	1650
High Ballast Factor (1.15)	10.5	18.5	2100	2100	2150	2150
Low Ballast Factor (0.77)	13	13.8	-	-	1700	1700
Normal Ballast Factor (0.88)	13	16.5	-	-	2000	2000
High Ballast Factor (1.15)	13	23	-	-	2640	2640

Testing Method: Above system power is half the total system power of a 2-tube installation using an Instant Start ballast. Power and lumen output will vary based on ballast and fixture type. Above data is indicative only. Please visit [www.greencreative.com](http://www.greencreative.com) for full ballast compatibility list



# DIRECT T8 VALUE SELECT

## DIMENSION & WEIGHT



Model	13T8/4F/xxx/IS/DIR 10.5T8/4F/xxx/IS/DIR
Base	G13
MOL	47-6/8"
Dia.	1-3/16"
Weight	0.67lb

Where xxx means 824-965 which indicates CRI and color temperature