


Project Name:	Type:
Part Number:	Date:

10W EMERGENCY LED DRIVER

FEATURES

- Suitable for use with select GREEN CREATIVE lamps.
For details of compatibility with specific product models, please refer to the Products Emergency Compatibility Matrix file available on <https://greencreative.com/emergency-accessories/>
- UL 924 Listed
- cUL Listed to CSA C22 No. 141
- Dual voltage 120/277 VAC 60Hz input
- Constant power output in emergency mode for a minimum of 90 minutes
- Meets or exceeds all National Electrical Code and Life Safety Code Emergency Lighting Requirements
- Integral short circuit protection
- Includes test switch accessory kit
- Recyclable long-life high temperature Lithium-Ion battery
- Low Voltage Disconnect (LVD)
- Rated for use in damp locations
- Driver ambient temperature: 32°F to 122°F (0°C to 50°C)
- 5 year limited warranty




062824



SPECIFICATIONS

Product	34959
Model	10EMDRIVER
Input Voltage	120 – 277VAC, 50/60Hz
Input Current	100mA MAX.
Input Power	10W MAX.
Output Power	10W
Charge Time	24 hours
Emergency Run Time	90 minutes
Driver Ambient Temperature	32°F to 122°F (0°C to 50°C)
Battery	Hi-temp rechargeable Lithium-Ion
Approval	UL 924 Listed for US and Canada, CSA C22 No. 141 Unit Equipment for Emergency, CEC Compliant

DIMENSION & WEIGHT






Model	10EMDRIVER
Length	12-11/16"
Width	1-11/16"
Height	1-3/16"
Weight	1.32lb



10W EMERGENCY LED DRIVER


INSTALLATION

INSTALLING THE EMERGENCY LED DRIVER



INSTALLING THE TEST SWITCH



Refer to the illustrations above and install the test switch through the inverter channel cover of a troffer or through the side of a strip fixture. Drill a 1/2" hole and install the switch as shown. Wire the test switch so that it removes AC power from the unswitched hot line to the emergency LED driver.



INSTALLING THE CHARGING INDICATOR LIGHT

Install the CHARGING INDICATOR LIGHT as shown in the illustration above so that it will be visible after the fixture is installed.

WIRING DIAGRAMS



ORDERING INFORMATION

Model	Master Carton			Shipping Carton		
	Case Qty	Case Dimensions (LxWxH)	Case Weight	Case Qty	Case Dimensions (LxWxH)	Case Weight
10EMDRIVER	N.A.	N.A.	N.A.	12PCS	14-3/16" x 10-1/4" x 7-5/8"	18.9lb

Where xxx means 824-965 which indicates CRI and color temperature
Note: All rights reserved. All sizes and specifications are subject to change at any time without notice