Project Name:	Туре:
Part Number:	Date:



FEATURES

- Replaces 36W / 40W 4-pin (2G11) CFL lamps
- Compatible with GREEN CREATIVE external drivers only
- Flicker Free (percent flicker and flicker index are less than three percent)
- High efficacy up to 157 LPW
- Opaque glass eliminates pixilation and reduces glare
- Plastic film prevents glass from shattering
- Field select from three lumen outputs using SelectDrive driver
- 0-10V dimming* dims to OFF with SelectDrive driver, dims to 10% with single wattage driver
- Suitable for use in totally enclosed fixtures and damp locations
- Fixture operating temperature: -4°F to 95°F (-20°C to 35°C)
- Lamp ambient temperature: -4°F to 113°F (-20°C to 45°C)
- Rated lifetime (L70): 60,000hrs
- 5 year limited warranty** / 10 year available (see EXTENDED WARRANTIES table for information)
- Each lamp is supplied with one support clip with adhesive back for quick installation





DIGITAL NAVIGATION Explore the spec sheet through the links below

SYSTEM PERFORMANCE DIMENSION & WEIGHT INSTALLATION ACCESSORY ORDERING INFORMATION EXTENDED WARRANTIES LOGISTIC INFORMATION **CERTIFICATION INFORMATION**

SPECIFICATIONS

		U														
Product	Model	Equiv.	Input Voltage	Wattage	Lumens	ССТ	Efficacy (LPW)	Life (hrs)	CRI	Power Factor	THD	Beam Angle	DIM.*	Fixture Rating	DLC	DOE
36704	13PLL/835/EXT	36W	120-277V	13	1,800	3500K	138	60,000	82	0.9	<20%	110°	Yes	Enclosed	N.A.	1
36705	13PLL/840/EXT	36W	120-277V	13	2,000	4000K	154	60,000	82	0.9	<20%	110°	Yes	Enclosed	N.A.	1
36707	14PLL/835/EXT	40W	120-277V	14	2,000	3500K	143	60,000	82	0.9	<20%	140°	Yes	Enclosed	\checkmark	1
36708	14PLL/840/EXT	40W	120-277V	14	2,200	4000K	157	60,000	82	0.9	<20%	140°	Yes	Enclosed	\checkmark	1
36710	19PLL/835/EXT	40W	120-277V	19	2,600	3500K	137	60,000	82	0.9	<20%	140°	Yes	Enclosed	\checkmark	1
36711	19PLL/840/EXT	40W	120-277V	19	2,800	4000K	147	60,000	82	0.9	<20%	140°	Yes	Enclosed	\checkmark	1

FOOTNOTES:

* This lamp might not be compatible with all dimmers. Please visit www.greencreative.com for compatibility information.
** Please visit www.greencreative.com for Limited Warranty terms
Note, Factory setting at highest lumen output.

SUPPLIED ACCESSORY									
Product	Model	Description	Picture	Dimension	Weight				
98015	PLLCUP	Support clip with adhesive back for quick installation One support clip for each lamp included in the package		1-3/8" 1-3/8" 1-3/8" 1-3/10	0.08oz				

SYSTEM COMPATIBILITY							
COMPATIBILITY TABLE - LA	AMP & DRIVER						
Model	15T8T5HEDRIVER/SD/2CH 15T8T5HEDRIVER/2CH/R	15T8T5HEDRIVER/SD/4CH 15T8T5HEDRIVER/4CH/R	24T5HODRIVER/2CH/R	24T5HODRIVER/4CH/R			
13PLL/xxx/EXT	1 lamp / 2 lamps	1 lamp / 2 lamps / 3 lamps / 4 lamps	N.A.	N.A.			
14PLL/xxx/EXT	1 lamp / 2 lamps	1 lamp / 2 lamps / 3 lamps / 4 lamps	N.A.	N.A.			
19PLL/xxx/EXT	N.A.	N.A.	1 lamp / 2 lamps	1 lamp / 2 lamps / 3 lamps / 4 lamps			

Where xxx means 824-965 which indicates CRI and color temperature.

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.



SYSTEM PERFORMANCE


LAMP & SelectDrive EXTERNAL DRIVER LUMEN OUTPUT GUIDE


Product	Model		15T8T	Lamp & Driver sys 5HEDRIVER/SD/2CH	tem lumen output 15T8T5HEDRIVER/Si	D/4CH	
		Low (Power)	Low (Lumens)	Med (Power)	Med (Lumens)	High (Power)	High (Lumens)
36704	13PLL/835/EXT	8.8	1,200	10.5	1,450	13	1,800
36705	13PLL/840/EXT	8.8	1,300	10.5	1,600	13	2,000
36707	14PLL/835/EXT	9.4	1,300	11.2	1,600	14	2,000
36708	14PLL/840/EXT	9.4	1,450	11.2	1,750	14	2,200

3-Lamps

4-Lamps

DIMENSION & WEIGHT







Model	Base	MOL	Width	Weight
13PLL/xxx/EXT	2G11	16-7/16"	1-11/16"	0.30 lb
14PLL/xxx/EXT	2G11	22-1/2"	1-11/16"	0.37 lb
19PLL/xxx/EXT	2G11	22-1/2"	1-11/16"	0.37 lb


Product	Model	Length	Width	Height	Weight
98259	15T8T5HEDRIVER/2CH/R				
98260	15T8T5HEDRIVER/4CH/R				
35896	15T8T5HEDRIVER/SD/2CH	9-1/2"	1-5/16"	1-3/16"	1.0 lb
35897	15T8T5HEDRIVER/SD/4CH]			
98261	24T5HODRIVER/2CH/R				
98262	24T5HODRIVER/4CH/R	9-1/2"	1-3/4"	1-3/16"	1.4 lb

INSTALLATION

EXTERNAL DRIVER INSTALLATION








Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.



INSTALLATION

FULHAM EMERGENCY DRIVER INSTALLATION

Max 4 LAMPS



COMPATIBILITY WITH FULHAM EMERGENCY DRIVER									
Туре	FULHAM EM DRIVER	Lumen output le	vel at EM mode						
	Model No	FHSCP-UNV-10.7WL	FHSCP-UNV-17WI						
	13PLL/8XX/EXT	87%	135%						
PLL	14PLL/8XX/EXT	79%	124%						
	19PLL/8XX/EXT	62%	96%						

ACCESSO	ACCESSORY ORDERING INFORMATION								
Product	Model	Description	Pictures	Dimensions	Compatible Skus				
37934	8EMINVERTER	California Title 20 Compliant 8W Emergency LED Inverter (Field Installation)	Cat	9-1/2" 	13PLL/8xx/EXT 14PLL/8xx/EXT 19PLL/8xx/EXT				
38096	24EMINVERTER	California Title 20 Compliant 24W Emergency LED Inverter (Field Installation)	Carl in		13PLL/8xx/EXT 14PLL/8xx/EXT 19PLL/8xx/EXT				
FHSCP-UNV-10.7WL	FHSCP-UNV-10.7WL	10.7W EM Driver 120-277V California Title 20 Compliant (Field Installation)		1-1/2" 15-3/8" 14-11/16" РибсРими 15.7%	13PLL/8xx/EXT 14PLL/8xx/EXT 19PLL/8xx/EXT				
FHSCP-UNV-17WL	FHSCP-UNV-17WL	17W EM Driver 120-277V California Title 20 Compliant (Field Installation)		1-5/8* 19-3/18* 19-9/18*	13PLL/8xx/EXT 14PLL/8xx/EXT 19PLL/8xx/EXT				

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.



EXTENDED WARRANTIES**

Model	Description***
13PLL/EXT/10YEARWARRANTY	10 Year warranty for 13PLL/8xx/EXT/yy
14PLL/EXT/10YEARWARRANTY	10 Year warranty for 14PLL/8xx/EXT/yy
19PLL/EXT/10YEARWARRANTY	10 Year warranty for 19PLL/8xx/EXT/yy

FOOTNOTES:

*** Warranty based on a maximum of 4,368 annual operating hours (per year for ten years) and exposure to a maximum fixture operating temperature of 80°F / 27°C, *** xx – Refers to the CCT yy – Refers to model generations within the same nominal performance. Typically blank, 'R', or 'RC'

LOGISTIC INFORMATION									
Model		Master Carton			Shipping Carton				
Model	Case Qty	Case Dimensions (LxWxH)	Case Weight	Case Qty	Case Dimensions (LxWxH)	Case Weight			
13PLL/xxx/EXT	6PCS	19-3/16" x 4-3/8" x 3-9/16"	3lb	24PCS	19-15/16" x 9-7/16" x 7-7/8"	13lb			
14PLL/xxx/EXT	6PCS	25" x 4-3/8" x 3-9/16"	3.5lb	24PCS	25-7/8" x 9-7/16" x 7-7/8"	15.5lb			
19PLL/xxx/EXT	6PCS	25" x 4-3/8" x 3-9/16"	3.5lb	24PCS	25-7/8" x 9-7/16" x 7-7/8"	15.5lb			

Where xxx means 824-965 which indicates CRI and color temperature.

CERTIFICATION INFORMATION

LC KITS REFERENCES				
Model No. (DLC)	Lamp Model	Lamp Qty	External Driver Model	DLC Product ID
14PLL/835/EXT/A2/R		2	98259 15T8T5HEDRIVER/2CH/R	S-C3T2GF
14PLL/835/EXT/SD/A2	36707	2	35896 15T8T5HEDRIVER/SD/2CH	PM6ZV7JJ
14PLL/835/EXT/A3/R	14PLL/835/EXT	3	98260 15T8T5HEDRIVER/4CH/R	S-401BY6
14PLL/835/EXT/SD/A3		3	35897 15T8T5HEDRIVER/SD/4CH	PIIW8SF8
14PLL/840/EXT/A2/R		2	98259 15T8T5HEDRIVER/2CH/R	S-9TR6E5
14PLL/840/EXT/SD/A2	36708	2	35896 15T8T5HEDRIVER/SD/2CH	PI76P6D9
14PLL/840/EXT/SD/A3	14PLL/840/EXT	3	35897 15T8T5HEDRIVER/SD/4CH	PFCWFMNW
14PLL/840/EXT/A3/R		3	98260 15T8T5HEDRIVER/4CH/R	S-4RA78I
19PLL/835/EXT/A2/R	36710	2	98261 24T5HODRIVER/2CH/R	S-017W6L
19PLL/835/EXT/A3/R	19PLL/835/EXT	3	98262 24T5HODRIVER/4CH/R	S-S9T24R
19PLL/840/EXT/A2/R	36711	2	98261 24T5HODRIVER/2CH/R	S-0JDNLU
19PLL/840/EXT/A3/R	19PLL/840/EXT	3	98262 24T5HODRIVER/4CH/R	S-PUIN1R