

5-6" DOWNLIGHT 12W TITANIUM CRI^{SP} LED SERIES



CRI^{SP}



12W REPLACES



75W Inc.

80% Energy Savings

\$219 Savings per lamp*

- Suitable for installation in 5" or 6" housing
- Wet location rated
- Exceptional color rendering CRI 90
- Richer reds and natural skin tones (R9 64, R13 95)
- Smooth dimming with existing dimmers
- GU24 connector available



50,000 H



DIMMABLE




70 LPW

EFFICACY



5 YR WARRANTY



CRI (Ra)




WET LOCATION




DOWNLIGHT PRODUCT FEATURES

5-6" Housing Installation

This downlight is suitable for use in most standard 5" and 6" housings that have spring retaining brackets. Simply adjust the mounting springs accordingly for easy installation.



Exceptional Color Rendering



The CRI^{SP} SERIES DOWNLIGHT 12W lamp features a typical CRI 90, R9 64 and R13 95, providing crisp and vibrant colors across the whole spectrum. Its exceptional R9-R14 values (R9 & R13) provide redder reds, natural looking skin tones and whiter whites. In addition, this lamp's color temperatures fall within a 4-step Macadam ellipse to ensure minimal color deviation across lamps.

5-6" DOWNLIGHT 12W TITANIUM CRI^{SP} LED SERIES




APPLICATIONS

General Lighting



Recessed Lighting



Accent Lighting



SPECIFICATIONS**

Product Model	97991 12DL6DIM/927	97992 12DL6DIM/930	97993 12DL6DIM/940
Type	5-6" Downlight	5-6" Downlight	5-6" Downlight
Base	E26 / LED Adapter (GU24 optional)	E26 / LED Adapter (GU24 optional)	E26 / LED Adapter (GU24 optional)
Power (W)	12	12	12
Voltage - Frequency	120V 60Hz	120V 60Hz	120V 60Hz
Color Temp. (ANSI)	Soft White 2700K	Warm White 3000K	Cool White 4000K
CRI (Ra)	90	90	90
R9 / R13 (typ.)	64 / 95	64 / 95	64 / 95
Typical lumens (lm)	840	840	840
Efficacy (LPW)	70	70	70
Beam Angle	100°	100°	100°
Dimmable	Yes***	Yes***	Yes***
Housing Compatibility	Most 5" and 6" housing	Most 5" and 6" housing	Most 5" and 6" housing
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000
Dia. x MOL	7.52"x3.03"(191x77mm)	7.52"x3.03"(191x77mm)	7.52"x3.03"(191x77mm)
Weight (lb. / g)	0.57lb. / 259g	0.57lb. / 259g	0.57lb. / 259g

* Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$4 incandescent with 1000-hr lifetime, \$20 LED with 50,000-hr lifetime

** Specification data is preliminary and may be subject to change

*** List of tested dimmer switches available on website

ACCESSORY ORDERING INFORMATION

Model	Product	Description
23EMDRIVER	98003	California Title 20 Compliant 23W Emergency LED Driver (Field Installation)
21EMINVERTER	37935	California Title 20 Compliant 21W Emergency LED Inverter (Field Installation)