

# GREEN CREATIVE RECESSED DOWNLIGHT PRODUCTS COLLECTIONS



GREENCREATIVE

MULTIFIT Flat	MULTIFIT Gimbal	MULTIFIT Cloud	INNOFIT G2	INNOFIT Plus	SELECTFIT G2	SPECFIT Retrofit	NYX	SPECFIT New Construction
<b>Good</b>	<b>Good</b>	<b>Good</b>	<b>Good</b>	<b>Good</b>	<b>Better</b>	<b>Best</b>	<b>Better</b>	<b>Best</b>

Application	Retrofit / Remodel					Retrofit / Remodel					Retrofit / Remodel					Retrofit / Remodel					New Construction											
Size	4"	6"	6" HO	8"	8" HO	4"	6"	6" HO	4"	6"	8"	9.5"	4"	6"	6" HO	8"	8" HO	9.5"	4"	6"	6" HO	8"	9.5"	4"	6"	4"	6"	8"	9.5"			
Installation Options	New Construction Frame	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
New Construction with IC Cover																																
Shape	Round	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Adjustable																																
Technology	SelectDrive																															
SelectKelvin	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
True Chroma																																
DualDim	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Max. Lumens @40K	670	770	1,110	1,510	2,000	650	910	650	910	1,110	1,600	2,120	1,400	2,100	3,000	3,650	880	1,650	2,900	2,100	4,200	4,000	2,650	5,200	5,200	5,200	2,000	4,000	2,650	5,200	5,200	5,200
Max. LPW @40K	80	83	76	88	84	78	91	78	91	76	123	125	117	131	130	130	91	97	97	97	97	100	84	87	87	87	100	100	84	87	87	87
Voltage	120-277V					120-277V					120-277V					120-277V					120-277V					120-277V						
CCT	Field Selectable 27K/30K/35K/40K/50K					Field Selectable 27K/30K/35K/40K/50K					Field Selectable 27K/30K/35K/40K/50K					Field Selectable 27K/30K/35K/40K/50K					Field Selectable 27K/30K/35K/40K/50K					27K/30K/35K/40K/50K						
CRI	min. 90					min. 90					min. 80					min. 80					min. 90					min. 90 (Standard)						
LED Binning (SDCM)	≤4					≤4					≤4					≤3					≤3					≤3						
Reflector Depth	Very Shallow					N.A.					Shallow					Shallow					Deep					Very Deep						
L70 Calculated Lifetime (Hrs)	100,000					100,000					100,000					100,000					100,000					100,000						
IC-Rated	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Air Tight	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Wet Location	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
ETL	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Energy Star	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Title 24 / JA8	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Forward & Reverse Dimmable @120V	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
0-10V Dimmable	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Optic	Wide Beam (>90°)					Medium Beam (60°-70°)					Narrow Beam (40°)					Very Narrow Beam (25°)					Spot Beam (15°)					Wall Wash						
Reflector Options	White					Clear					Black					White Baffle					Black Baffle					White						
Flange Options	White					Clear					Black					Flangeless					White					White						
Control Options	Philips EasySense					Lutron Athena Node					Lutron EcoSystem					Enlighted Compact Sensor					GREEN CREATIVE 23W Emergency Driver					Philips 6W Emergency K-Case						
Emergency Options	Fulham 25W Emergency Inverter					Factory Installed 10.7W Emergency Driver					5 Year Standard Warranty					10 Year Optional Warranty					✓					✓						
Warranty	✓					✓					✓					✓					✓					✓						