

## LM-79-08 TEST REPORT

for

### GREEN CREATIVE LTD

756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

### LED Lamp

**Model: 6.5B13DIM/827**

### Laboratory: Leading Testing Laboratories

**NVLAP CODE: 200960-0**

3rd Floor, Bld. 2, NO. 96 Longchuanwu Rd Qianjiang Economy Dev. Zone, YuhangDist,  
Hangzhou, Zhejiang Province, China 311100

Tel: +86571 86376106

www.ledtestlab.com

Report No.: HZ19120032c

The laboratory that conducted the testing detailed in this report has been accredited for SSL by NVLAP.

Review by:



Engineer: April Zou  
Jan. 06, 2020

Approved by:



Manager: Jim Zhang  
Jan. 06, 2020

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

## TEST SUMMARY

Sample Tested: 6.5B13DIM/827

Luminous Efficacy (Lumens /Watt)	Total Luminous Flux (Lumens)	Power (Watts)	Power Factor
84.6	511.6	6.05	0.9393
CCT (K)	CRI	Stabilization Time (Light & Power)	
2742	83.3	60	

Table 1: Executive Data Summary

Note: The above results are recorded/ derived from measurements made using an Integrating Sphere.

### Test specifications:

<b>Date of Receipt</b>	: Dec. 31, 2019
<b>Date of Test</b>	: Jan. 03, 2020
<b>Test item</b>	: Total Luminous Flux, Luminous Distribution Intensity, Luminous Efficacy, Correlated Color Temperature, Color Rendering Index, Chromaticity Coordinate, Electrical parameters
<b>Reference Standard</b>	: IESNA LM-79-2008 Approved Method for the Electrical and Photometric Measurements of Solid-State Lighting Products ANSI/IES TM-30-18 IES Method for Evaluating Light Source Color Rendition

## TABLE OF CONTENT

LM-79-08 TEST REPORT .....	1
TEST SUMMARY .....	2
SAMPLE PHOTO .....	4
TEST RESULTS .....	5
Sphere-Spectroradiometer Method.....	5
Goniophotometer Method .....	6
Spectral Power Distribution - Sphere Spectroradiometer Method .....	7
Chromaticity Diagram - Sphere Spectroradiometer Method.....	8
Nominal CCT Quadrangles – Sphere Spectroradiometer Method .....	9
Color Rendition Report – Sphere Spectroradiometer Method .....	10
Zonal Lumen Tabulation- Goniophotometer Method .....	11
Illuminance Plots- Goniophotometer Method .....	12
Luminous Intensity Distribution Plots- Goniophotometer Method.....	13
Luminous Intensity Data- Goniophotometer Method .....	14
EQUIPMENT LIST .....	16
TEST METHODS .....	16
Seasoning of SSL Product.....	16
Sphere-Spectroradiometer Method- Photometric and Electrical Measurements.....	16
Goniophotometer Method .....	17
Photometric and Electrical Measurements .....	17
Color Characteristics Measurements.....	17
Color Spatial Uniformity .....	17

## SAMPLE PHOTO



Figure 1- Overview of the sample

### Equipment Under Test(EUT)

<b>Name</b>	: LED Lamp
<b>Model</b>	: 6.5B13DIM/827
<b>Electrical Ratings</b>	: 120V, 60Hz, 6.5W
<b>Product Description</b>	: 2700K
<b>Manufacturer</b>	: GREEN CREATIVE LTD
<b>Address</b>	: 756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

## TEST RESULTS

Test ambient temperature was 26.0 °C.

Base orientation was base up. Test was conducted without a dimmer in the circuit.

The stabilization time of the sample was 60 minutes, and the total operating time including stabilization was 65 minutes.

### Sphere-Spectroradiometer Method

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.054
Power Factor	0.9393
Test Power (W)	6.05
THD A%	22.10
Luminous Efficacy (lm/W)	84.6
Total Luminous Flux (lm)	511.6
Color Rendering Index (CRI)	83.3
R9	10.8
Correlated Color Temperature (CCT)(K)	2742
Chromaticity Chroma x	0.4557
Chromaticity Chroma y	0.4087
Chromaticity Chroma u	0.2607
Chromaticity Chroma v	0.3507
Duv	0.0004
Chromaticity Chroma u'	0.2607
Chromaticity Chroma v'	0.5260

Special Color Rendering Indices	
R1	82.8
R2	94.2
R3	92.8
R4	80.6
R5	83.5
R6	94.2
R7	80.6
R8	57.9
R9	10.8
R10	87.2
R11	81
R12	78.7
R13	85.8
R14	96.7

Table 2: Test data per Sphere-Spectroradiometer Method

Note: According to CIE 1976 ( $u', v'$ ) diagram,  $u' = u = 4x/(-2x+12y+3)$ ,  $v' = 3v/2 = 9y/(-2x+12y+3)$ .

### Goniophotometer Method

Test ambient temperature was 24.9 °C.

The photometric distance is 2.47 m.

Luminous data was taken at 0.5 vertical intervals and 10 horizontal intervals.

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.054
Power Factor	0.9389
Power (W)	6.06
Luminous Efficacy (lm/W)	84.7
Total Luminous Flux (lm)	513.1
Beam Angle ( ° )	235.6 (0°-180°) / 238.0 (90°-270°)
Center Beam Candle Power (cd)	20.0
Maximum Beam Candle Power (cd)	152.1 (At: C=140.0, Gamma=37.5)
Spacing Criteria	3.19 (0°-180°) / 3.13 (90°-270°)
Zonal Lumens in the 0 °-60 °Zone	54.01%
Zonal Lumens in the 60 °-90 °Zone	30.04%
Zonal Lumens in the 90 °-120 °Zone	14.62%
Zonal Lumens in the 120 °-180 °Zone	1.33%

Table 3: Test data per Goniophotometer Method

## Spectral Power Distribution - Sphere Spectroradiometer Method





Chart 1: Spectral Power Distribution

Spectral Distribution over Visible Wavelength							
WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)
380	2.38E-05	485	2.34E-03	590	1.03E-02	695	2.25E-03
385	2.14E-05	490	2.56E-03	595	1.08E-02	700	1.93E-03
390	2.43E-05	495	2.87E-03	600	1.11E-02	705	1.66E-03
395	2.24E-05	500	3.24E-03	605	1.12E-02	710	1.42E-03
400	2.54E-05	505	3.61E-03	610	1.12E-02	715	1.23E-03
405	2.91E-05	510	3.93E-03	615	1.10E-02	720	1.06E-03
410	4.90E-05	515	4.23E-03	620	1.06E-02	725	9.10E-04
415	8.68E-05	520	4.47E-03	625	1.01E-02	730	7.73E-04
420	1.56E-04	525	4.67E-03	630	9.58E-03	735	6.63E-04
425	2.67E-04	530	4.88E-03	635	8.95E-03	740	5.65E-04
430	4.42E-04	535	5.09E-03	640	8.30E-03	745	4.84E-04
435	7.37E-04	540	5.33E-03	645	7.62E-03	750	4.16E-04
440	1.23E-03	545	5.61E-03	650	6.95E-03	755	3.58E-04
445	2.08E-03	550	5.92E-03	655	6.29E-03	760	3.07E-04
450	3.43E-03	555	6.31E-03	660	5.64E-03	765	2.63E-04
455	4.40E-03	560	6.76E-03	665	5.02E-03	770	2.25E-04
460	4.00E-03	565	7.28E-03	670	4.44E-03	775	1.91E-04
465	3.33E-03	570	7.89E-03	675	3.91E-03	780	1.66E-04
470	2.96E-03	575	8.51E-03	680	3.42E-03		
475	2.55E-03	580	9.16E-03	685	2.98E-03		
480	2.29E-03	585	9.79E-03	690	2.59E-03		

Table 4: Spectral Power Distribution Numerical Data per Sphere - Spectroradiometer Method

## Chromaticity Diagram - Sphere Spectroradiometer Method



Tristimulus values (x, y): (0.4557, 0.4087)

Chart 2: Chromaticity Diagram per Sphere - Spectroradiometer Method

Note: The location on the diagram of the tristimulus coordinates are indicated by the blue diamond.



### Nominal CCT Quadrangles – Sphere Spectroradiometer Method





Chart 3: Plot of Lamp x/y coordinates on CIE 1931 Chromaticity Diagram

## Color Rendition Report – Sphere Spectroradiometer Method



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

$x$  0.4557  
 $y$  0.4087  
 $u'$  0.2607  
 $v'$  0.5260

Chart 4: Full Report Created with the IES TM-30 Calculator

Note: The values in this diagram might be a little different from the values in Table 2 due to rounding.

### Zonal Lumen Tabulation- Goniophotometer Method

$\gamma(^{\circ})$	Lumens	% Total
0- 10	2.42	0.47%
10- 20	13.263	2.58%
20- 30	31.676	6.17%
30- 40	75.117	14.64%
40- 50	79.552	15.50%
50- 60	75.1	14.64%
60- 70	76.002	14.81%
70- 80	44.175	8.61%
80- 90	33.936	6.61%
90-100	39.282	7.66%
100-110	22.685	4.42%
110-120	13.057	2.54%
120-130	4.957	0.97%
130-140	1.47	0.29%
140-150	0.247	0.05%
150-160	0.109	0.02%
160-170	0.042	0.01%
170-180	0.008	0.00%
Total	513.1	100%

$\gamma(^{\circ})$	Lumens	% Total
0-110	493.208	96.12%
110-180	19.89	3.88%
0-180	513.1	100%

Table 5: Zonal Lumen

## Illuminance Plots- Goniophotometer Method




Chart 5: Illuminance Plot (Footcandles)

## Luminous Intensity Distribution Plots- Goniophotometer Method




Chart 6: Isocandela Plot




Chart 7: Polar Candela Distribution

## Luminous Intensity Data- Goniophotometer Method

Table---1

UNIT: cd

C (DEG) Y (DEG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
5	22.4	22.6	22.8	22.9	22.6	22.3	22.3	22.3	22.2	22.4	22.3	22.0	21.7	21.4	21.1	21.0	20.8	20.9	22.3
10	31.2	31.5	31.0	31.6	31.3	29.3	29.1	29.7	30.4	29.3	29.4	29.3	28.6	28.6	28.9	29.9	29.1	27.2	31.0
15	56.0	56.6	56.6	60.9	57.0	49.5	48.6	47.4	50.8	53.4	49.7	53.2	51.2	52.1	52.0	48.5	49.1	46.8	45.2
20	57.5	54.9	53.1	54.3	56.7	55.9	57.4	58.5	58.9	59.6	54.5	55.3	52.8	54.4	59.4	58.8	58.0	57.4	52.9
25	63.9	65.3	68.3	72.5	73.4	67.7	68.3	68.7	64.2	62.6	63.1	64.3	65.1	65.1	65.2	67.0	70.5	68.2	67.9
30	91.4	95.1	101	102	97.6	93.0	91.6	99.8	96.6	93.2	90.9	87.3	85.9	87.8	86.8	87.8	89.5	93.7	91.0
35	108	123	141	144	135	122	122	133	148	148	136	122	120	126	138	146	132	123	114
40	118	113	107	101	108	121	131	128	122	123	129	138	150	150	135	130	132	120	114
45	96.5	93.5	89.1	85.3	96.4	103	106	110	100	99.2	107	118	122	112	108	106	100	115	113
50	90.0	91.9	87.6	82.5	91.9	98.2	97.1	92.0	95.1	92.3	98.8	104	96.5	97.6	91.8	86.3	93.5	94.0	97.7
55	74.5	78.0	75.9	74.5	82.5	80.7	81.7	90.7	83.5	82.9	85.2	80.4	87.9	88.7	75.1	71.2	79.3	91.4	94.3
60	82.7	78.8	84.9	93.6	87.4	79.1	84.8	79.6	91.3	95.2	87.1	80.0	81.6	83.6	91.5	97.3	92.0	82.4	77.1
65	68.8	72.2	75.2	76.2	74.4	74.8	71.0	74.5	77.1	73.3	77.1	76.4	83.5	85.0	83.7	83.5	83.4	85.8	82.6
70	64.4	53.7	44.3	42.0	47.8	61.7	64.5	55.8	48.1	47.3	54.3	66.7	68.2	61.7	54.5	54.2	58.0	66.9	73.1
75	38.1	36.4	32.0	31.3	34.6	40.4	45.9	40.2	33.1	32.2	38.8	46.8	50.9	47.1	40.3	37.4	43.5	45.5	49.9
80	28.2	28.3	28.3	28.4	28.7	29.1	31.5	31.1	29.2	29.2	30.0	29.4	28.2	28.9	32.0	31.8	30.7	28.2	28.1
85	23.2	28.5	34.4	33.3	33.7	29.4	25.1	29.3	33.4	34.9	34.2	28.7	24.2	29.2	35.2	38.4	34.2	28.5	30.3
90	32.6	32.6	31.1	31.1	32.7	36.1	36.8	35.2	30.6	30.5	34.3	35.3	33.3	32.8	34.7	32.1	34.9	38.0	37.6
95	36.2	36.4	35.0	34.9	36.0	32.0	34.4	37.8	37.2	37.7	38.8	41.2	43.7	43.0	41.5	42.5	40.4	37.0	34.6
100	26.8	28.3	27.4	27.1	26.8	27.2	27.6	28.2	28.4	30.3	29.5	29.1	28.9	28.3	31.4	33.0	30.0	30.7	29.8
105	21.3	22.5	23.7	24.2	22.7	19.8	19.7	19.9	21.3	23.5	21.3	20.3	18.2	19.9	21.0	22.1	20.1	18.5	18.7
110	16.6	17.1	18.2	19.6	18.7	16.5	16.4	15.1	18.3	17.9	15.7	15.6	16.3	15.5	16.5	17.5	17.2	14.6	13.7
115	11.6	12.2	13.6	14.4	13.9	12.8	12.5	13.6	15.1	14.6	14.6	14.1	14.5	14.7	14.5	14.8	15.7	13.8	11.9
120	6.86	7.42	8.15	8.84	8.87	8.47	9.13	9.65	10.0	10.2	10.4	9.80	10.7	10.1	9.04	9.01	9.85	10.4	8.85
125	4.11	4.43	4.76	4.68	4.78	4.86	5.01	5.68	5.56	5.19	5.48	5.78	5.83	5.96	5.68	5.33	6.53	7.53	6.43
130	2.80	2.65	2.53	2.55	2.81	3.17	3.44	3.66	3.37	3.18	3.65	4.07	4.42	4.05	3.42	3.17	3.73	4.81	4.55
135	1.44	1.41	1.45	1.49	1.56	1.72	1.68	1.75	1.73	1.70	1.81	1.96	2.11	2.03	1.99	1.94	2.07	2.26	2.20
140	0.48	0.44	0.45	0.46	0.47	0.52	0.52	0.53	0.58	0.62	0.69	0.84	0.98	1.00	0.96	0.94	1.01	1.07	1.12
145	0.30	0.30	0.31	0.31	0.31	0.31	0.31	0.31	0.32	0.32	0.33	0.34	0.36	0.37	0.36	0.35	0.35	0.37	0.39
150	0.25	0.25	0.25	0.26	0.26	0.26	0.26	0.26	0.27	0.27	0.27	0.27	0.27	0.27	0.27	0.28	0.28	0.28	0.29
155	0.21	0.21	0.22	0.22	0.22	0.22	0.22	0.23	0.23	0.24	0.24	0.24	0.24	0.24	0.24	0.25	0.25	0.25	0.25
160	0.17	0.17	0.18	0.18	0.18	0.18	0.18	0.18	0.19	0.19	0.19	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
165	0.12	0.13	0.13	0.13	0.13	0.13	0.14	0.14	0.14	0.14	0.14	0.15	0.15	0.15	0.15	0.16	0.16	0.15	0.16
170	0.08	0.08	0.08	0.09	0.08	0.08	0.08	0.08	0.09	0.09	0.09	0.09	0.09	0.09	0.10	0.10	0.11	0.11	0.11
175	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.08
180	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08

Table 6: Luminous Intensity Data



Table--2

UNIT: cd

C (DEG) Y (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0		
5	22.8	22.8	22.8	22.9	22.9	22.8	22.9	23.4	23.6	23.8	23.6	23.5	23.8	23.5	23.6	23.7	23.6		
10	31.4	31.8	31.5	30.8	32.7	31.8	30.3	30.8	31.7	31.6	30.8	30.8	31.9	31.6	31.6	32.4	30.9		
15	46.5	49.6	47.4	45.8	43.0	42.5	44.4	44.0	44.3	42.1	42.4	44.5	43.5	44.2	45.6	46.8	53.3		
20	54.2	53.8	55.4	51.9	54.4	55.9	54.9	58.5	53.8	51.8	49.9	52.3	53.1	55.5	56.3	56.6	57.8		
25	63.5	62.6	63.1	62.8	59.9	61.0	61.1	60.9	61.5	62.5	67.4	65.1	66.2	64.9	63.9	62.7	64.9		
30	88.1	83.0	81.6	83.3	84.9	81.0	81.7	82.8	81.3	80.4	84.4	87.3	86.3	86.1	90.7	91.4	91.6		
35	116	119	125	120	113	119	121	124	121	121	111	111	128	145	146	124	110		
40	118	121	119	126	125	127	123	126	126	120	115	116	118	105	99.4	107	120		
45	99.2	93.9	98.1	100.0	99.3	110	103	100	97.4	103	105	100	86.5	79.5	84.3	87.7	95.7		
50	95.6	86.0	86.1	87.0	85.4	89.6	87.0	86.4	83.7	92.5	87.6	82.2	81.9	77.8	79.5	89.9	92.5		
55	86.5	75.6	72.8	80.7	80.8	84.8	79.2	78.9	75.8	79.0	79.9	85.1	83.1	74.5	74.8	84.0	79.2		
60	84.0	97.2	95.2	76.4	75.7	78.4	81.8	94.2	92.4	85.7	83.1	87.5	81.8	86.7	90.3	80.8	81.7		
65	78.0	87.8	92.0	83.3	84.5	80.5	84.8	83.1	79.2	74.8	69.8	71.3	76.4	78.3	77.3	72.2	69.3		
70	63.2	50.6	48.4	55.1	73.9	74.3	60.7	50.2	48.8	54.0	66.6	70.1	57.3	49.0	46.7	54.0	68.4		
75	47.7	43.8	42.7	44.6	41.9	43.1	44.4	39.2	39.9	41.6	43.0	41.5	36.6	28.6	28.3	35.5	38.1		
80	30.4	32.7	33.9	30.0	28.9	30.1	31.5	32.1	31.3	27.8	27.8	29.9	31.8	30.3	28.5	29.9	31.0		
85	34.3	34.3	32.5	32.4	28.3	27.7	32.7	33.3	36.2	33.5	26.4	24.0	28.1	36.8	36.8	27.4	23.7		
90	34.1	32.0	33.6	34.9	34.1	34.6	34.4	32.1	32.5	34.5	38.7	38.8	34.9	27.9	29.9	32.1	35.3		
95	37.9	41.6	43.7	42.3	40.6	41.8	42.0	40.4	38.5	35.9	35.8	36.0	38.6	39.0	39.6	40.7	38.8		
100	27.3	28.8	29.8	28.1	28.9	31.1	29.8	30.5	30.9	29.1	27.0	26.5	27.7	29.7	29.4	27.6	28.3		
105	19.4	21.7	23.6	22.4	22.2	20.8	19.9	21.2	21.4	20.0	19.0	19.1	18.4	20.4	21.0	20.6	20.4		
110	16.3	19.6	19.6	18.2	16.0	17.5	16.8	17.5	17.5	16.5	15.5	15.4	15.8	16.3	16.8	15.8	15.7		
115	12.4	15.2	14.4	13.2	12.9	12.4	12.3	13.0	13.0	11.5	11.2	11.1	11.4	12.5	12.6	11.6	11.1		
120	8.61	9.20	8.62	8.75	8.29	7.71	7.97	7.90	8.21	7.88	6.96	7.05	7.09	7.79	7.43	6.77	6.87		
125	5.70	5.45	5.17	5.71	5.26	5.15	5.29	4.72	4.91	5.06	4.83	4.97	4.64	4.32	4.26	4.46	4.48		
130	3.80	3.24	3.00	3.40	3.82	3.81	3.25	2.94	3.02	3.13	3.08	2.96	2.63	2.46	2.43	2.64	2.85		
135	2.12	1.99	1.91	1.94	2.03	2.01	1.91	1.85	1.78	1.65	1.57	1.52	1.53	1.49	1.47	1.50	1.52		
140	1.09	1.07	1.04	1.06	1.04	1.05	1.06	0.90	0.84	0.75	0.72	0.67	0.61	0.58	0.56	0.55	0.54		
145	0.39	0.39	0.37	0.36	0.35	0.35	0.34	0.34	0.34	0.33	0.33	0.33	0.32	0.32	0.32	0.32	0.32		
150	0.30	0.29	0.29	0.29	0.29	0.29	0.28	0.28	0.28	0.28	0.28	0.28	0.27	0.27	0.27	0.27	0.27		
155	0.25	0.25	0.25	0.24	0.24	0.24	0.24	0.24	0.24	0.24	0.23	0.23	0.21	0.20	0.21	0.22	0.23		
160	0.20	0.20	0.20	0.20	0.20	0.19	0.19	0.19	0.19	0.19	0.18	0.18	0.18	0.16	0.13	0.14	0.16		
165	0.16	0.16	0.16	0.16	0.15	0.15	0.15	0.14	0.14	0.14	0.14	0.14	0.14	0.13	0.12	0.12	0.12		
170	0.11	0.11	0.11	0.11	0.11	0.10	0.10	0.09	0.09	0.09	0.08	0.08	0.08	0.08	0.08	0.08	0.08		
175	0.08	0.08	0.09	0.09	0.08	0.08	0.08	0.08	0.09	0.09	0.09	0.08	0.08	0.09	0.09	0.09	0.09		
180	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08		

Table 7: Luminous Intensity Data

## EQUIPMENT LIST

Test Equipment	Model	Equipment No.	Calibration Date	Calibration Due date
Goniophotometer system	GO-R5000	HZTE011-01	Aug. 02, 2019	Aug. 01, 2020
Digital Power Meter	PF2010A	HZTE028-01	Aug. 02, 2019	Aug. 01, 2020
AC Power Supply	DPS1060	HZTE001-06	Aug. 02, 2019	Aug. 01, 2020
DC Power Supply	WY12010	HZTE004-03	Aug. 02, 2019	Aug. 01, 2020
Temperature recorder	JM624U	HZTE018-08	Aug. 02, 2019	Aug. 01, 2020
Temperature and humidity recorder	JR900	HZTE018-01	Aug. 02, 2019	Aug. 01, 2020
Standard source	D908	HZTE012-01	Aug. 02, 2019	Aug. 01, 2020
Integrate Sphere system	3M	HZTE015-04	Aug. 02, 2019	Aug. 01, 2020
Digital Power Meter	WT210	HZTE008-01	Aug. 02, 2019	Aug. 01, 2020
AC Power Supply	PCR 500L	HZTE001-07	Aug. 02, 2019	Aug. 01, 2020
DC Power Supply	IT6154	HZTE004-04	Aug. 02, 2019	Aug. 01, 2020
Standard source	SCL-1400	HZTE012-02	Aug. 02, 2019	Aug. 01, 2020
Temperature and humidity recorder	JR900	HZTE018-02	Aug. 02, 2019	Aug. 01, 2020
Temperature Meter	TES1310	HZTE017-01	Aug. 02, 2019	Aug. 01, 2020

Table 8: Test Equipment List

## TEST METHODS

### Seasoning of SSL Product

For the purpose of rating new SSL products, SSL products shall be tested with no seasoning. Therefore, no seasoning was performed.

### Sphere-Spectroradiometer Method- Photometric and Electrical Measurements

A Labsphere Model CDS 2100 Spectroradiometer and Two Meter Sphere was used to measure correlated color temperature, chromaticity coordinates, and the color rendering index for each SSL unit. The coating reflectance of each sphere is 98%. The measure geometry is  $4\pi$ . Self-absorption correction is conducted in testing. Bandwidth of spectroradiometer is 350nm-1050nm.

Ambient temperature was measured at a position inside the sphere. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

The standard reference of the integrated sphere system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Standards and Technology.



The uncertainty of integrating sphere system reported in this document is expanded uncertainty is 2.1% with a coverage factor  $k=2$ .

## **Goniophotometer Method**

### **Photometric and Electrical Measurements**

An EVERFINE Type C Model GO-R5000 Goniophotometer was used to measure the intensity at each angle of distribution for each sample. The photometric distance is 2.475m for near-field measurement or 30m for far-field measurement. Bandwidth of spectroradiometer is 380nm-780nm.

Ambient temperature was measured at the same height of the sample mounted on the Goniophotometer equipment. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Everfine Digital Power Meter.

Some graphics were created with Photometric Plus software.

The standard reference of the Goniophotometer system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Metrology P.R. China.

The uncertainty of goniophotometer system reported in this document is expanded uncertainty is 2.3% with a coverage factor  $k=2$ .

### **Color Characteristics Measurements**

The color characteristics of SSL products include chromaticity coordinates, correlated color temperature, and color rendering index. These characteristics of SSL products may be spatially non-uniform, and thus, in order that they can be specified accurately, the color quantities shall be measured as values that are spatially average, weighted to intensity, over the angular range where light is intentionally emitted from the SSL product. The color characteristics measurements are using gonio-spectroradiometer.

### **Color Spatial Uniformity**

The characteristics of SSL products may be spatially non-uniform, the chromaticity coordinate shall be measured at two vertical planes ( $C=0^\circ/180^\circ$  and  $C=90^\circ/270^\circ$ ) and at  $10^\circ$  or less intervals for vertical angle until the light output dropped to below 10% of the peak intensity. The averaged weighted chromaticity coordinate

was calculated from these points. The data was then analyzed to check for delta color differences of the  $u'$ ,  $v'$  chromaticity coordinates. The spatial non-uniformity of chromaticity,  $\Delta u'v'$ , is determined as the maximum deviation (distance on the CIE ( $u'$ ,  $v'$ ) diagram) among all measured points from the spatially averaged chromaticity coordinate.

The geometry for the chromaticity measurement using gonio-spectroradiometer is shown as following.



\*\*\* End of Report \*\*\*

This report is considered invalidated without the Special Seal for Inspection of the LTL. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of LTL, this test report shall not be copied except in full and published as advertisement.