

LM-79-08 TEST REPORT

for

GREEN CREATIVE LTD

756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

LED Tube

Model: 10.5T8/4F/840/DIR/RD

Laboratory: Leading Testing Laboratories

NVLAP CODE: 200960-0

3rd Floor, Bld. 2, NO. 96 Longchuanwu Rd Qianjiang Economy Dev. Zone, YuhangDist,
Hangzhou, Zhejiang Province, China 311100


Tel: +86571 86376106

www.ledtestlab.com

Report No.: HZ19050020d

The laboratory that conducted the testing detailed in this report has been accredited for SSL by NVLAP.

Review by:



Engineer: April Zou
May 23, 2019

Approved by:



Manager: Jim Zhang
May 23, 2019

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TEST SUMMARY

Sample Tested: 10.5T8/4F/840/DIR/RD

Luminous Efficacy (Lumens /Watt)	Total Luminous Flux (Lumens)	Power (Watts)	Power Factor
135.3	1880.0	13.90	0.9923
CCT (K)	CRI	Stabilization Time (Light & Power)	
4059	81.9	60	

Table 1: Executive Data Summary

Note: The above results are recorded/ derived from measurements made using an Integrating Sphere.

Test specifications:

Date of Receipt	: May 16, 2019
Date of Test	: May 21, 2019
Test item	: Total Luminous Flux, Luminous Distribution Intensity, Luminous Efficacy, Correlated Color Temperature, Color Rendering Index, Chromaticity Coordinate, Electrical parameters
Reference Standard	: IESNA LM-79-2008 Approved Method for the Electrical and Photometric Measurements of Solid-State Lighting Products ANSI/IES TM-30-18 IES Method for Evaluating Light Source Color Rendition

TABLE OF CONTENT

LM-79-08 TEST REPORT	1
TEST SUMMARY	2
SAMPLE PHOTO	4
TEST RESULTS	5
Sphere-Spectroradiometer Method.....	5
Goniophotometer Method	6
Spectral Power Distribution - Sphere Spectroradiometer Method	7
Chromaticity Diagram - Sphere Spectroradiometer Method.....	8
Nominal CCT Quadrangles – Sphere Spectroradiometer Method	9
Color Rendition Report – Sphere Spectroradiometer Method	10
Zonal Lumen Tabulation- Goniophotometer Method	11
Illuminance Plots- Goniophotometer Method	12
Luminous Intensity Distribution Plots- Goniophotometer Method.....	13
Luminous Intensity Data- Goniophotometer Method	14
EQUIPMENT LIST	16
TEST METHODS	16
Seasoning of SSL Product.....	16
Sphere-Spectroradiometer Method- Photometric and Electrical Measurements.....	16
Goniophotometer Method	17
Photometric and Electrical Measurements	17
Color Characteristics Measurements.....	17
Color Spatial Uniformity	17

SAMPLE PHOTO




Figure 1- Overview of the sample

Equipment Under Test(EUT)

Name	: LED Tube
Model	: 10.5T8/4F/840/DIR/RD
Electrical Ratings	: 120-277V, 60Hz, 10.5W
Product Description	: 4000K LED Tubes supplied by a high frequency fluorescent lamp ballast: IOPA-1P32-N
Manufacturer	: GREEN CREATIVE LTD
Address	: 756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

TEST RESULTS

Test ambient temperature was 25.0°C.

Base orientation was light down. Test was conducted without a dimmer in the circuit.

The stabilization time of the sample was 60 minutes, and the total operating time including stabilization was 65 minutes.

Sphere-Spectroradiometer Method

Parameter	Result	
Test Voltage (V)	120.0	277.0
Voltage frequency (Hz)	60	60
Test Current (A)	0.117	0.055
Power Factor	0.9923	0.9315
Test Power (W)	13.90	14.06
THD A%	8.82	15.03
Luminous Efficacy (lm/W)	135.3	133.7
Total Luminous Flux (lm)	1880.0	1880.0
Color Rendering Index (CRI)	81.9	
R9	2.4	
Correlated Color Temperature (CCT)(K)	4059	
Chromaticity Chroma x	0.3792	
Chromaticity Chroma y	0.3805	
Chromaticity Chroma u	0.2228	
Chromaticity Chroma v	0.3354	
Duv	0.0015	
Chromaticity Chroma u'	0.2228	
Chromaticity Chroma v'	0.5030	

Special Color Rendering Indices	
R1	79.7
R2	88
R3	94.5
R4	80.8
R5	79.8
R6	83.5
R7	85.9
R8	62.8
R9	2.4
R10	71.7
R11	79.6
R12	59.5
R13	81.6
R14	97.1

Table 2: Test data per Sphere-Spectroradiometer Method

Note: According to CIE 1976 (u', v') diagram, $u' = u = 4x/(-2x+12y+3)$, $v' = 3v/2 = 9y/(-2x+12y+3)$.

Goniophotometer Method

Test ambient temperature was 25.2°C.

The photometric distance is 30 m.

Luminous data was taken at 0.5 vertical intervals and 10 horizontal intervals.

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.117
Power Factor	0.9928
Power (W)	13.95
Luminous Efficacy (lm/W)	132.6
Total Luminous Flux (lm)	1850.2
Beam Angle (°)	116.4 (0°-180°) / 238.0 (90°-270°)
Center Beam Candle Power (cd)	285
Maximum Beam Candle Power (cd)	285.5 (At: C=260.0, Gamma=0.5)
Spacing Criteria	1.29 (0°-180°) / 1.46 (90°-270°)
Zonal Lumens in the 0 °-60 °Zone	41.04%
Zonal Lumens in the 60 °-90 °Zone	27.00%
Zonal Lumens in the 90 °-120 °Zone	18.33%
Zonal Lumens in the 120 °-180 °Zone	13.64%

Table 3: Test data per Goniophotometer Method

Spectral Power Distribution - Sphere Spectroradiometer Method





Chart 1: Spectral Power Distribution

Spectral Distribution over Visible Wavelength							
WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)
380	3.33E-04	485	9.85E-03	590	3.23E-02	695	4.54E-03
385	3.31E-04	490	1.11E-02	595	3.23E-02	700	3.90E-03
390	3.63E-04	495	1.31E-02	600	3.20E-02	705	3.35E-03
395	3.94E-04	500	1.55E-02	605	3.13E-02	710	2.86E-03
400	4.37E-04	505	1.77E-02	610	3.03E-02	715	2.45E-03
405	5.30E-04	510	1.94E-02	615	2.90E-02	720	2.08E-03
410	6.99E-04	515	2.10E-02	620	2.73E-02	725	1.79E-03
415	1.07E-03	520	2.20E-02	625	2.55E-02	730	1.53E-03
420	1.69E-03	525	2.29E-02	630	2.37E-02	735	1.30E-03
425	2.86E-03	530	2.36E-02	635	2.17E-02	740	1.11E-03
430	4.98E-03	535	2.42E-02	640	1.97E-02	745	9.61E-04
435	8.54E-03	540	2.50E-02	645	1.77E-02	750	8.08E-04
440	1.49E-02	545	2.56E-02	650	1.58E-02	755	7.03E-04
445	2.65E-02	550	2.63E-02	655	1.40E-02	760	6.08E-04
450	3.70E-02	555	2.72E-02	660	1.24E-02	765	5.24E-04
455	3.08E-02	560	2.80E-02	665	1.09E-02	770	4.47E-04
460	2.07E-02	565	2.89E-02	670	9.47E-03	775	3.86E-04
465	1.66E-02	570	2.98E-02	675	8.23E-03	780	3.34E-04
470	1.28E-02	575	3.07E-02	680	7.15E-03		
475	9.75E-03	580	3.15E-02	685	6.15E-03		
480	9.20E-03	585	3.21E-02	690	5.31E-03		

Table 4: Spectral Power Distribution Numerical Data per Sphere - Spectroradiometer Method

Chromaticity Diagram - Sphere Spectroradiometer Method



Tristimulus values(x, y): (0.3792, 0.3805)

Chart 2: Chromaticity Diagram per Sphere - Spectroradiometer Method

Note: The location on the diagram of the tristimulus coordinates are indicated by the blue diamond.

Nominal CCT Quadrangles – Sphere Spectroradiometer Method





Chart 3: Plot of Lamp x/y coordinates on CIE 1931 Chromaticity Diagram

Color Rendition Report – Sphere Spectroradiometer Method



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3792
 y 0.3805
 u' 0.2228
 v' 0.5030

Chart 4: Full Report Created with the IES TM-30 Calculator

Note: The values in this diagram might be a little different from the values in Table 2 due to rounding.

Zonal Lumen Tabulation- Goniophotometer Method

$\gamma(^{\circ})$	Lumens	% Total
0- 10	27.124	1.47%
10- 20	79.055	4.27%
20- 30	124.269	6.72%
30- 40	159.079	8.60%
40- 50	180.923	9.78%
50- 60	188.774	10.20%
60- 70	183.426	9.91%
70- 80	167.974	9.08%
80- 90	148.156	8.01%
90-100	129.999	7.03%
100-110	112.968	6.11%
110-120	96.143	5.20%
120-130	80.13	4.33%
130-140	64.672	3.50%
140-150	49.436	2.67%
150-160	33.763	1.82%
160-170	18.486	1.00%
170-180	5.801	0.31%
Total	1850.2	100%

$\gamma(^{\circ})$	Lumens	% Total
0- 60	759.224	41.04%
60- 90	499.556	27.00%
0-90	1258.78	68.04%
90- 180	591.398	31.96%
0- 180	1850.2	100%

Table 5: Zonal Lumen

Illuminance Plots- Goniophotometer Method




Chart 5: Illuminance Plot (Footcandles)

Luminous Intensity Distribution Plots- Goniophotometer Method




Chart 6: Isocandela Plot




Chart 7: Polar Candela Distribution

Luminous Intensity Data- Goniophotometer Method

Table--1

UNIT: cd

C (DEG) y (DEG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	285	285	285	285	285	285	285	285	285	285	285	285	285	285	285	285	285	285	285
5	284	284	285	285	285	285	285	285	285	285	285	285	285	285	285	285	285	284	284
10	281	281	282	282	283	283	284	284	285	285	285	284	284	283	283	282	282	281	281
15	276	276	277	278	279	280	282	283	283	283	283	283	282	281	279	278	277	276	276
20	269	269	270	272	274	276	279	280	281	282	281	280	279	277	275	272	271	269	269
25	259	260	262	265	268	272	275	277	279	279	279	277	275	272	268	265	262	260	259
30	248	249	252	256	261	265	270	274	276	277	276	274	270	266	261	256	252	249	248
35	234	236	240	245	252	259	265	269	272	273	272	270	265	259	252	246	240	235	234
40	219	220	226	233	242	251	259	264	268	269	268	265	259	252	243	234	226	220	218
45	201	203	210	220	232	243	252	259	264	265	264	260	253	243	232	221	210	203	199
50	181	184	193	206	220	234	245	253	258	260	259	254	246	235	221	207	193	183	179
55	159	163	175	191	209	224	237	247	253	255	253	248	238	225	210	192	175	162	157
60	135	140	156	176	196	215	230	240	247	249	247	241	231	216	198	177	156	139	133
65	109	116	136	160	184	205	222	233	241	243	241	234	223	207	186	162	137	116	107
70	82.9	91.9	116	145	172	195	213	226	234	237	234	227	215	197	175	147	118	91.7	80.1
75	56.6	68.2	97.4	131	161	186	205	218	226	229	227	219	206	188	163	134	100	69.1	53.2
80	31.1	46.1	81.0	118	150	176	196	210	219	222	219	211	198	178	153	121	84.8	48.5	28.0
85	10.4	29.0	68.1	106	140	167	187	202	210	213	211	203	189	169	143	111	73.0	33.1	8.19
90	0.58	19.7	58.5	96.8	130	157	178	193	201	204	202	194	180	160	134	101	63.8	24.6	0.35
95	2.09	16.4	51.4	88.1	121	148	168	183	191	194	192	184	170	150	125	93.0	57.1	21.4	2.20
100	6.10	17.9	47.4	81.0	112	138	158	172	181	184	181	174	160	141	116	86.0	53.0	22.4	6.20
105	11.5	21.2	46.2	75.7	104	129	148	162	170	173	171	163	150	132	108	80.5	51.6	25.4	11.7
110	17.8	24.7	46.4	72.8	97.9	120	138	151	159	162	160	153	140	123	101	76.9	52.1	29.8	17.7
115	24.5	27.4	46.9	70.6	92.6	112	129	141	148	151	149	142	131	115	96.1	74.7	53.5	34.5	23.8
120	31.0	32.5	49.5	69.2	88.4	106	121	131	138	140	139	133	122	109	92.0	73.6	55.5	38.2	30.1
125	37.0	38.6	51.1	68.1	85.2	100	113	123	129	131	129	124	115	103	88.7	73.1	57.9	42.0	35.2
130	42.7	43.9	52.5	66.9	82.1	95.4	107	115	120	122	121	116	108	98.0	85.8	72.8	60.2	44.9	40.0
135	48.3	47.4	53.1	63.7	80.1	91.0	100	108	113	114	113	109	102	93.4	83.5	71.7	61.1	45.9	44.3
140	53.3	49.6	56.2	63.3	75.6	87.2	95.4	101	105	106	105	102	96.9	89.6	80.8	70.5	61.9	46.3	49.2
145	58.1	50.6	60.2	63.1	69.5	81.8	89.7	95.3	98.7	99.9	99.1	96.3	91.5	85.2	76.8	68.8	61.6	45.6	54.5
150	63.0	49.2	60.3	67.9	67.9	73.5	82.6	88.2	91.4	92.6	91.9	89.7	85.5	79.2	72.6	66.6	60.4	44.1	60.5
155	64.3	49.7	51.4	68.4	70.0	70.6	74.1	79.7	82.4	83.7	83.6	81.0	77.2	72.8	68.4	61.2	50.7	44.3	61.6
160	64.8	51.6	43.9	58.5	71.8	73.1	73.2	75.0	77.7	76.2	76.6	76.2	70.4	62.2	56.4	48.7	42.4	44.6	54.6
165	69.2	51.0	44.9	44.1	50.4	66.1	71.0	73.7	76.7	75.8	74.9	60.6	52.5	50.9	44.1	38.8	40.6	42.7	50.3
170	69.2	57.6	47.2	48.7	50.1	51.6	55.9	59.3	64.1	74.1	38.0	51.4	52.7	51.7	47.3	46.4	44.4	42.3	47.3
175	68.8	63.2	57.9	57.9	57.7	57.5	60.2	62.8	63.4	44.1	64.3	63.7	61.8	59.4	56.5	54.0	53.5	53.1	53.7
180	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5

Table 6: Luminous Intensity Data

Table--2

UNIT: cd

C (DEG) γ (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	285	285	285	285	285	285	285	285	285	285	285	285	285	285	285	285	285		
5	284	284	285	285	285	285	285	285	285	285	285	285	285	285	285	284	284		
10	281	282	282	282	283	283	284	284	284	284	284	283	283	282	282	282	281		
15	276	277	278	279	280	281	282	282	282	282	282	281	280	279	278	277	276		
20	269	270	272	273	275	277	279	280	280	280	279	277	276	274	272	270	269		
25	260	261	264	267	270	273	275	277	277	277	275	273	270	267	264	262	260		
30	248	251	255	259	264	268	271	273	274	273	271	268	264	260	255	251	249		
35	235	238	244	250	256	262	266	269	270	270	267	263	257	251	245	239	236		
40	219	224	231	240	248	256	261	265	266	265	262	256	249	241	233	226	221		
45	202	208	218	229	240	249	256	260	262	260	256	250	241	231	220	210	203		
50	182	191	204	217	230	241	249	254	256	255	250	243	232	219	206	193	184		
55	162	173	188	205	221	233	243	249	251	249	244	235	223	208	191	176	164		
60	138	154	173	193	211	225	236	242	245	243	237	227	213	196	176	158	142		
65	114	133	158	181	201	217	229	236	238	236	230	219	203	184	162	138	119		
70	89.4	114	142	169	191	209	221	229	231	229	222	211	194	172	147	119	94.7		
75	65.5	95.3	128	158	182	200	213	221	224	222	215	202	184	162	133	101	71.4		
80	44.2	79.1	115	147	172	192	205	214	216	214	207	194	175	151	120	84.6	50.2		
85	28.2	66.5	104	137	164	183	197	205	208	206	198	185	167	141	109	71.6	33.5		
90	19.9	57.7	95.5	128	155	174	188	197	200	197	190	176	158	132	99.6	62.1	23.8		
95	17.4	52.1	88.2	120	146	166	179	188	191	188	181	168	149	123	91.8	55.8	20.2		
100	19.0	48.5	82.0	112	138	157	171	178	181	179	172	159	140	115	85.1	51.4	20.3		
105	22.6	47.0	76.8	105	129	148	161	169	172	170	163	150	131	108	79.4	48.9	23.2		
110	27.8	47.7	72.9	98.6	121	139	151	159	162	160	152	140	123	101	74.8	48.6	27.9		
115	33.0	49.7	70.7	92.7	113	129	141	149	151	149	142	131	115	94.4	71.8	49.6	33.4		
120	39.1	52.0	69.7	88.3	106	121	132	138	141	139	132	122	107	89.2	70.0	51.5	39.0		
125	44.9	54.9	69.5	85.0	99.9	112	122	128	130	129	123	113	100	85.4	69.3	54.4	44.6		
130	50.0	57.4	69.5	82.6	94.9	105	114	119	121	119	114	106	95.2	82.6	69.1	57.5	49.9		
135	54.3	60.5	70.1	80.6	90.8	99.5	106	111	112	111	107	99.7	90.9	80.5	69.7	60.8	54.9		
140	58.3	62.7	70.6	78.9	87.3	94.4	99.9	103	105	103	100.0	94.4	87.2	78.8	70.5	63.8	59.4		
145	62.4	65.7	71.2	77.7	83.9	89.7	94.3	97.2	98.0	97.1	94.3	89.8	84.0	77.7	71.6	66.6	63.3		
150	65.7	66.0	71.4	76.7	81.5	85.6	89.0	91.2	91.9	91.2	89.0	85.7	81.6	77.0	72.6	69.1	66.6		
155	66.2	67.3	72.5	76.0	79.2	82.3	84.9	86.6	86.9	86.4	84.9	82.6	79.6	76.6	73.8	71.3	69.4		
160	61.5	65.2	67.8	75.3	77.7	79.4	81.2	82.4	82.6	82.3	81.4	80.0	78.3	76.6	74.8	73.1	72.5		
165	54.8	58.3	62.8	68.4	76.6	78.0	78.9	79.6	79.6	79.5	79.1	78.5	77.6	76.6	75.6	74.5	74.4		
170	51.7	53.0	53.9	58.4	64.6	73.9	77.1	77.7	77.5	77.5	77.3	77.1	76.7	76.2	75.3	73.7	72.6		
175	54.7	52.7	50.2	50.7	54.9	59.7	65.0	69.5	72.9	74.7	75.7	75.8	75.5	75.0	73.6	72.4	71.5		
180	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5		

Table 7: Luminous Intensity Data

EQUIPMENT LIST

Test Equipment	Model	Equipment No.	Calibration Date	Calibration Due date
Goniophotometer system	GO-R5000	HZTE011-01	Aug. 14, 2018	Aug. 13, 2019
Digital Power Meter	PF2010A	HZTE028-01	Sep. 12, 2018	Sep. 11, 2019
AC Power Supply	DPS1060	HZTE001-06	Aug. 09, 2018	Aug. 08, 2019
DC Power Supply	WY12010	HZTE004-03	Aug. 09, 2018	Aug. 08, 2019
Temperature recorder	JM624U	HZTE018-08	Aug. 09, 2018	Aug. 08, 2019
Temperature and humidity recorder	JR900	HZTE018-01	Aug. 09, 2018	Aug. 08, 2019
Standard source	D908	HZTE012-01	Aug. 14, 2018	Aug. 13, 2019
Integrate Sphere system	3M	HZTE015-04	Aug. 16, 2018	Aug. 15, 2019
Digital Power Meter	WT210	HZTE008-01	Aug. 02, 2018	Aug. 01, 2019
AC Power Supply	PCR 500L	HZTE001-07	Aug. 09, 2018	Aug. 08, 2019
DC Power Supply	IT6154	HZTE004-04	Aug. 09, 2018	Aug. 08, 2019
Standard source	SCL-1400	HZTE012-02	Aug. 16, 2018	Aug. 15, 2019
Temperature and humidity recorder	JR900	HZTE018-02	Aug. 09, 2018	Aug. 08, 2019
Temperature Meter	TES1310	HZTE017-01	Aug. 09, 2018	Aug. 08, 2019

Table 8: Test Equipment List

TEST METHODS

Seasoning of SSL Product

For the purpose of rating new SSL products, SSL products shall be tested with no seasoning. Therefore, no seasoning was performed.

Sphere-Spectroradiometer Method- Photometric and Electrical Measurements

A Labsphere Model CDS 2100 Spectroradiometer and Two Meter Sphere was used to measure correlated color temperature, chromaticity coordinates, and the color rendering index for each SSL unit. The coating reflectance of each sphere is 98%. The measure geometry is 4π . Self-absorption correction is conducted in testing. Bandwidth of spectroradiometer is 350nm-1050nm.

Ambient temperature was measured at a position inside the sphere. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

The standard reference of the integrated sphere system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Standards and Technology.

The uncertainty of integrating sphere system reported in this document is expanded uncertainty is 2.1% with a coverage factor $k=2$.

Goniophotometer Method

Photometric and Electrical Measurements

An EVERFINE Type C Model GO-R5000 Goniophotometer was used to measure the intensity at each angle of distribution for each sample. The photometric distance is 2.475m for near-field measurement or 30m for far-field measurement. Bandwidth of spectroradiometer is 380nm-780nm.

Ambient temperature was measured at the same height of the sample mounted on the Goniophotometer equipment. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Everfine Digital Power Meter.

Some graphics were created with Photometric Plus software.

The standard reference of the Goniophotometer system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Metrology P.R. China.

The uncertainty of goniophotometer system reported in this document is expanded uncertainty is 2.3% with a coverage factor $k=2$.

Color Characteristics Measurements

The color characteristics of SSL products include chromaticity coordinates, correlated color temperature, and color rendering index. These characteristics of SSL products may be spatially non-uniform, and thus, in order that they can be specified accurately, the color quantities shall be measured as values that are spatially average, weighted to intensity, over the angular range where light is intentionally emitted from the SSL product. The color characteristics measurements are using gonio-spectroradiometer.

Color Spatial Uniformity

The characteristics of SSL products may be spatially non-uniform, the chromaticity coordinate shall be measured at two vertical planes ($C=0^\circ/180^\circ$ and $C=90^\circ/270^\circ$) and at 10° or less intervals for vertical angle until the light output dropped to below 10% of the peak intensity. The averaged weighted chromaticity coordinate

was calculated from these points. The data was then analyzed to check for delta color differences of the u' , v' chromaticity coordinates. The spatial non-uniformity of chromaticity, $\Delta u'v'$, is determined as the maximum deviation (distance on the CIE (u' , v') diagram) among all measured points from the spatially averaged chromaticity coordinate.

The geometry for the chromaticity measurement using gonio-spectroradiometer is shown as following.



*** End of Report ***

This report is considered invalidated without the Special Seal for Inspection of the LTL. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of LTL, this test report shall not be copied except in full and published as advertisement.