



IES LM-79-08

MEASUREMENT AND TEST REPORT

For

GREEN CREATIVE LTD

756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai, China

Test Model: 5.5PLSV/835/HYB/GX23

Report Type:	Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution
Test Engineer:	George Yang <i>George Yang</i>
Report Number:	PKS181030084-10-2
Test Date:	2018-11-01 to 2018-11-06
Report Date:	2018-11-09
Reviewed By:	Ray Gao/EE Engineer <i>Ray Gao</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan). No.248 Chenghu Road, Kunshan, Jiangsu province, China. Tel: +86-0512-86175000 Fax: +86-0512-88934268
Test Facility:	Test facility was located at No.248 Chenghu Road, Kunshan, Jiangsu province, China.
Accreditation:	The IAS Accreditation Number TL-749.

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

1. Product Description

General Information:

one sample was received on 2018-10-30 and used for testing.

Model Tested: 5.5PLSV/835/HYB/GX23
 Manufacturer: GREEN CREATIVE LTD
 Brand Name: GREEN CREATIVE
 Product Designation: LED Lamp
 Aging Time Before Test: 0hour(For New Products)

Rated Values:

Rated Voltage/Frequency: 120-277VAC 60Hz
 Rated Power: 5.5W
 Nominal CCT: 3500K
 Nominal Lumen Output: 620lm

2. Standards Used

- IES LM-79-08: Approved Method: Electrical & Photometric Measurement of Solid-state Lighting Products
- ANSI C82.77-10-2014: Harmonic Emission Limits – Related Power Quality Requirements for Lighting Equipment
- IES TM-30-15: IES Method for Evaluating Light Source Color Rendition

3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
Integrating Sphere	INVENTFINE	Dia 1.5m	JWWCV090112	2018-01-24	2019-01-24
Power Meter	INVENTFINE	WT500	GSJWQ20009	2018-04-08	2019-04-08
Spectral photometer	INVENTFINE	CMS-3S	GSGSE100017	2018-01-24	2019-01-24
AC Power Supply	INVENTFINE	CHP500	JWJSD010071	2018-04-08	2019-04-08
Standard Light Source	INVENTFINE	N/A	JWWCR020106	2018-01-24	2019-01-24
Thermal Meter	KEJIAN	TA298	N/A	2017-11-14	2018-11-14
DC Power Supply	INVENTFINE	WL3005	JWWCP020069	2018-04-08	2019-04-08
AC Power Supply	INVENTFINE	CHP-5KVA	900511765	2018-04-08	2019-04-08
DC Power Supply	INVENTFINE	WL3010	JWDMP030001	2018-04-08	2019-04-08
Power Meter	INVENTFINE	WT500	GSDSQ200007	2018-04-08	2019-04-08
Goniophotometer	INVENTFINE	GPM-1900	YWGCF120001	2018-01-24	2019-01-24
Wireless Weather Station	ZHONGXING	KG218	N/A	2017-11-14	2018-11-14
Standard Light Source	INVENTFINE	N/A	JWBYR040007	2018-01-24	2019-01-24

Statement of Traceability: Bay Area Compliance Laboratories Corp.(Kunshan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with IES LM-79-08. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ during measurement. And relative humidity is less than 65%.

Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

4π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is $U=2.6\%$ ($K=2$), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is $U=24\text{K}$ ($K=2$), at the 95% confidence level. The uncertainty of the CRI is $U=2.5(K=2)$, at the 95% confidence level.

The uncertainty of power meter AC current $U=0.16\%$ of rdg, AC Voltage $U=0.18\%$ of rdg, Power $U=0.14\%$ ($K=2$), at the 95% confidence level.

Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The vertical angle (γ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

The uncertainty of the luminous flux is $U=2.6\%$ ($K=2$), at the 95% confidence level.

Fidelity Index and Gamut Index Calculation

The R_i , R_g was calculated according to IES TM-30-15 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

5. Test Result

[Integrating Sphere System]

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Downward**


Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.0463	5.43	0.9776	632.04	116.4

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
1.919	3320	-0.00065	0.4151	0.3939	0.2407	0.5140

Color Rendering Index


Ra 83.7			
R1 82	R2 91	R3 97	R4 82
R5 82	R6 89	R7 84	R8 63
R9 12	R10 79	R11 81	R12 69
R13 84	R14 98	R15 76	




Fidelity Index and Gamut Index

Fidelity Index R_f	83
Gamut Index R_g	96


Spectral Power Distribution Comparison




Plot of R_g versus R_f




Chroma Shift by Hue




R_f by Hue




Color Vector Graphic



Color Fidelity by CES Sample




Relative Spectral Power Distribution




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
380	1.560E-02	421	4.340E-01	462	5.626E+00	503	4.744E+00	544	7.828E+00
381	2.780E-02	422	4.935E-01	463	5.342E+00	504	4.876E+00	545	7.882E+00
382	1.550E-02	423	5.794E-01	464	5.128E+00	505	4.993E+00	546	7.950E+00
383	1.560E-02	424	6.559E-01	465	4.917E+00	506	5.116E+00	547	8.012E+00
384	4.910E-02	425	7.358E-01	466	4.723E+00	507	5.234E+00	548	8.061E+00
385	3.430E-02	426	8.298E-01	467	4.567E+00	508	5.333E+00	549	8.156E+00
386	3.300E-03	427	9.344E-01	468	4.373E+00	509	5.454E+00	550	8.233E+00
387	2.410E-02	428	1.072E+00	469	4.196E+00	510	5.570E+00	551	8.312E+00
388	9.100E-03	429	1.217E+00	470	4.039E+00	511	5.673E+00	552	8.377E+00
389	3.400E-03	430	1.350E+00	471	3.870E+00	512	5.765E+00	553	8.458E+00
390	2.830E-02	431	1.502E+00	472	3.729E+00	513	5.884E+00	554	8.517E+00
391	1.140E-02	432	1.673E+00	473	3.541E+00	514	5.962E+00	555	8.603E+00
392	4.100E-03	433	1.834E+00	474	3.414E+00	515	6.051E+00	556	8.678E+00
393	6.800E-03	434	2.018E+00	475	3.271E+00	516	6.131E+00	557	8.782E+00
394	1.180E-02	435	2.220E+00	476	3.149E+00	517	6.225E+00	558	8.854E+00
395	2.390E-02	436	2.446E+00	477	3.056E+00	518	6.294E+00	559	8.920E+00
396	1.050E-02	437	2.671E+00	478	2.970E+00	519	6.350E+00	560	9.029E+00
397	2.080E-02	438	2.931E+00	479	2.900E+00	520	6.440E+00	561	9.111E+00
398	6.700E-03	439	3.221E+00	480	2.848E+00	521	6.514E+00	562	9.217E+00
399	3.000E-04	440	3.516E+00	481	2.821E+00	522	6.565E+00	563	9.312E+00
400	0.000E+00	441	3.853E+00	482	2.809E+00	523	6.650E+00	564	9.411E+00
401	1.200E-02	442	4.234E+00	483	2.850E+00	524	6.715E+00	565	9.500E+00
402	2.630E-02	443	4.622E+00	484	2.838E+00	525	6.775E+00	566	9.576E+00
403	2.220E-02	444	5.128E+00	485	2.920E+00	526	6.835E+00	567	9.682E+00
404	1.250E-02	445	5.597E+00	486	2.935E+00	527	6.893E+00	568	9.786E+00
405	3.290E-02	446	6.087E+00	487	2.999E+00	528	6.927E+00	569	9.862E+00
406	1.070E-02	447	6.587E+00	488	3.058E+00	529	6.984E+00	570	9.965E+00
407	6.840E-02	448	7.061E+00	489	3.123E+00	530	7.059E+00	571	1.007E+01
408	1.820E-02	449	7.523E+00	490	3.225E+00	531	7.120E+00	572	1.018E+01
409	4.900E-02	450	7.882E+00	491	3.303E+00	532	7.191E+00	573	1.027E+01
410	6.800E-02	451	8.104E+00	492	3.413E+00	533	7.220E+00	574	1.038E+01
411	7.470E-02	452	8.250E+00	493	3.512E+00	534	7.264E+00	575	1.048E+01
412	7.010E-02	453	8.267E+00	494	3.602E+00	535	7.305E+00	576	1.056E+01
413	7.900E-02	454	8.176E+00	495	3.720E+00	536	7.367E+00	577	1.068E+01
414	1.356E-01	455	8.005E+00	496	3.853E+00	537	7.428E+00	578	1.075E+01
415	1.540E-01	456	7.722E+00	497	3.978E+00	538	7.474E+00	579	1.084E+01
416	1.779E-01	457	7.390E+00	498	4.089E+00	539	7.520E+00	580	1.093E+01
417	2.227E-01	458	6.992E+00	499	4.248E+00	540	7.600E+00	581	1.101E+01
418	2.763E-01	459	6.614E+00	500	4.345E+00	541	7.662E+00	582	1.111E+01
419	3.150E-01	460	6.259E+00	501	4.495E+00	542	7.724E+00	583	1.119E+01
420	3.744E-01	461	5.920E+00	502	4.606E+00	543	7.752E+00	584	1.125E+01

nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
585	1.134E+01	626	1.041E+01	667	4.705E+00	708	1.415E+00	749	2.556E-01
586	1.142E+01	627	1.027E+01	668	4.574E+00	709	1.334E+00	750	2.594E-01
587	1.151E+01	628	1.013E+01	669	4.425E+00	710	1.251E+00	751	2.894E-01
588	1.155E+01	629	9.996E+00	670	4.334E+00	711	1.218E+00	752	2.491E-01
589	1.165E+01	630	9.887E+00	671	4.217E+00	712	1.182E+00	753	2.455E-01
590	1.170E+01	631	9.769E+00	672	4.103E+00	713	1.199E+00	754	2.393E-01
591	1.176E+01	632	9.594E+00	673	3.986E+00	714	1.112E+00	755	1.571E-01
592	1.179E+01	633	9.495E+00	674	3.864E+00	715	1.039E+00	756	1.922E-01
593	1.185E+01	634	9.367E+00	675	3.793E+00	716	1.003E+00	757	1.965E-01
594	1.189E+01	635	9.155E+00	676	3.707E+00	717	1.009E+00	758	6.310E-02
595	1.195E+01	636	9.052E+00	677	3.556E+00	718	9.652E-01	759	1.612E-01
596	1.198E+01	637	8.899E+00	678	3.446E+00	719	9.203E-01	760	1.100E-01
597	1.201E+01	638	8.777E+00	679	3.370E+00	720	8.804E-01	761	1.242E-01
598	1.201E+01	639	8.628E+00	680	3.254E+00	721	8.340E-01	762	1.924E-01
599	1.204E+01	640	8.469E+00	681	3.164E+00	722	8.252E-01	763	2.170E-01
600	1.205E+01	641	8.345E+00	682	3.092E+00	723	8.255E-01	764	1.100E-01
601	1.205E+01	642	8.157E+00	683	3.052E+00	724	7.096E-01	765	5.320E-02
602	1.206E+01	643	8.052E+00	684	2.942E+00	725	7.644E-01	766	8.180E-02
603	1.206E+01	644	7.875E+00	685	2.805E+00	726	7.144E-01	767	1.056E-01
604	1.205E+01	645	7.725E+00	686	2.758E+00	727	6.697E-01	768	1.737E-01
605	1.200E+01	646	7.590E+00	687	2.718E+00	728	6.748E-01	769	1.144E-01
606	1.198E+01	647	7.423E+00	688	2.637E+00	729	6.868E-01	770	3.290E-02
607	1.198E+01	648	7.274E+00	689	2.470E+00	730	6.915E-01	771	5.920E-02
608	1.196E+01	649	7.128E+00	690	2.401E+00	731	5.967E-01	772	1.178E-01
609	1.188E+01	650	7.022E+00	691	2.375E+00	732	6.360E-01	773	2.530E-02
610	1.183E+01	651	6.854E+00	692	2.315E+00	733	5.431E-01	774	3.780E-02
611	1.180E+01	652	6.717E+00	693	2.249E+00	734	5.185E-01	775	6.470E-02
612	1.174E+01	653	6.550E+00	694	2.164E+00	735	5.332E-01	776	5.570E-02
613	1.168E+01	654	6.413E+00	695	2.104E+00	736	4.977E-01	777	7.950E-02
614	1.161E+01	655	6.266E+00	696	1.989E+00	737	4.609E-01	778	8.290E-02
615	1.155E+01	656	6.117E+00	697	1.976E+00	738	4.246E-01	779	6.850E-02
616	1.144E+01	657	5.983E+00	698	1.910E+00	739	3.708E-01	780	4.050E-02
617	1.135E+01	658	5.842E+00	699	1.848E+00	740	3.651E-01		
618	1.129E+01	659	5.714E+00	700	1.770E+00	741	4.385E-01		
619	1.117E+01	660	5.557E+00	701	1.769E+00	742	4.187E-01		
620	1.110E+01	661	5.445E+00	702	1.667E+00	743	3.997E-01		
621	1.095E+01	662	5.306E+00	703	1.624E+00	744	2.516E-01		
622	1.084E+01	663	5.153E+00	704	1.583E+00	745	3.163E-01		
623	1.077E+01	664	5.054E+00	705	1.496E+00	746	2.047E-01		
624	1.062E+01	665	4.925E+00	706	1.465E+00	747	2.758E-01		
625	1.053E+01	666	4.816E+00	707	1.411E+00	748	2.385E-01		

CIE 1931 x y Chromaticity Diagram



7-Step Chromaticity Quadrangles



[Goniophotometer System]

Total operating time for luminous intensity distribution: **1.0 hours**

Test orientation: **Downward**


Electrical Measurement

Input Voltage (V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.0	60	0.0460	5.45	0.9870

Photometric Measurement

Luminous Flux (lm)	Efficacy (lm/W)	I _{max} (cd)	S/MH (C0/180)	S/MH (C90/270)
633	116.19	228.0	1.24	1.24

Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle (50% I _{max}):	106.6	106.6	106.5	106.7	106.6
Field Angle (10% I _{max}):	164.6	164.5	164.4	164.4	164.5

Luminous Intensity (cd) Distribution Data

C γ	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	227	227	227	227	227	227	227	227
5.0°	226	227	228	227	227	226	226	226
10.0°	224	225	226	226	225	224	224	223
15.0°	219	221	222	222	222	220	220	218
20.0°	212	215	216	216	216	214	213	211
25.0°	203	206	207	208	208	206	204	201
30.0°	192	195	197	198	198	195	193	190
35.0°	179	183	184	185	185	183	180	177
40.0°	164	168	170	171	171	168	166	162
45.0°	147	151	154	155	155	152	149	145
50.0°	130	134	137	138	137	135	132	128
55.0°	111	115	118	120	119	117	114	110
60.0°	93	97	100	101	100	98	95	91
65.0°	74	78	81	83	82	80	77	74
70.0°	57	60	63	64	64	63	60	57
75.0°	41	45	47	48	48	47	45	42
80.0°	28	31	33	34	34	33	32	29
85.0°	18	20	22	23	23	22	21	19
90.0°	11	12	14	14	14	14	13	12
95.0°	6	7	8	8	8	8	7	6
100.0°	3	3	4	4	4	4	4	3
105.0°	1	1	2	2	2	2	2	1
110.0°	0	1	1	1	1	1	1	1
115.0°	0	0	0	1	1	1	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	0	0	0	0	0	0	0	0
145.0°	0	0	0	0	0	0	0	0
150.0°	0	0	0	0	0	0	0	0
155.0°	0	0	0	0	0	0	0	0
160.0°	0	0	0	0	0	0	0	0
165.0°	0	0	0	0	0	0	0	0
170.0°	0	0	0	0	0	0	0	0
175.0°	0	0	0	0	0	0	0	0
180.0°	0	0	0	0	0	0	0	0

Luminous Intensity (cd) Distribution Data (cont.)

C Y	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	227	227	227	227	227	227	227	227
5.0°	226	225	224	224	225	224	225	226
10.0°	222	221	221	220	220	219	221	222
15.0°	216	214	214	212	213	213	215	217
20.0°	208	206	205	204	204	205	207	209
25.0°	198	196	194	192	193	194	197	200
30.0°	186	183	182	180	180	181	184	187
35.0°	172	169	167	165	166	167	170	174
40.0°	156	153	150	149	149	151	154	158
45.0°	139	136	134	132	132	134	137	141
50.0°	121	118	116	114	114	116	119	123
55.0°	103	100	97	96	96	97	101	105
60.0°	85	82	79	78	78	79	82	86
65.0°	68	65	63	61	61	62	65	68
70.0°	52	49	47	45	45	46	49	51
75.0°	38	35	33	32	32	32	34	37
80.0°	26	24	23	21	21	22	23	25
85.0°	17	15	14	13	13	14	14	16
90.0°	10	9	8	8	7	8	8	9
95.0°	5	4	4	4	4	4	4	5
100.0°	2	2	2	1	1	1	2	2
105.0°	1	1	1	1	0	0	1	1
110.0°	0	0	0	0	0	0	0	0
115.0°	0	0	0	0	0	0	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	0	0	0	0	0	0	0	0
145.0°	0	0	0	0	0	0	0	0
150.0°	0	0	0	0	0	0	0	0
155.0°	0	0	0	0	0	0	0	0
160.0°	0	0	0	0	0	0	0	0
165.0°	0	0	0	0	0	0	0	0
170.0°	0	0	0	0	0	0	0	0
175.0°	0	0	0	0	0	0	0	0
180.0°	0	0	0	0	0	0	0	0

Zonal Lumen Density Measurement

Deg	Flux (lm)	%	Deg	Flux (lm)	%
0-5	5.4	0.85	0-5	5.4	0.85
5-10	16.0	2.53	0-10	21.4	3.39
10-15	26.1	4.12	0-15	47.5	7.51
15-20	35.2	5.56	0-20	82.8	13.07
20-25	43.1	6.80	0-25	125.8	19.88
25-30	49.3	7.78	0-30	175.1	27.66
30-35	53.6	8.47	0-35	228.7	36.13
35-40	55.9	8.83	0-40	284.6	44.96
40-45	56.1	8.87	0-45	340.7	53.83
45-50	54.3	8.58	0-50	395.0	62.41
50-55	50.6	8.00	0-55	445.7	70.41
55-60	45.4	7.17	0-60	491.1	77.58
60-65	39.0	6.16	0-65	530.1	83.75
65-70	31.9	5.03	0-70	562.0	88.78
70-75	24.6	3.89	0-75	586.6	92.68
75-80	18.0	2.84	0-80	604.6	95.52
80-85	12.3	1.95	0-85	616.9	97.46
85-90	7.8	1.23	0-90	624.7	98.69
90-95	4.5	0.70	0-95	629.1	99.40
95-100	2.2	0.35	0-100	631.4	99.75
100-105	1.0	0.15	0-105	632.4	99.90
105-110	0.4	0.06	0-110	632.7	99.96
110-115	0.2	0.02	0-115	632.9	99.99
115-120	0.1	0.01	0-120	633.0	100.00
120-125	0.0	0.00	0-125	633.0	100.00
125-130	0.0	0.00	0-130	633.0	100.00
130-135	0.0	0.00	0-135	633.0	100.00
135-140	0.0	0.00	0-140	633.0	100.00
140-145	0.0	0.00	0-145	633.0	100.00
145-150	0.0	0.00	0-150	633.0	100.00
150-155	0.0	0.00	0-155	633.0	100.00
155-160	0.0	0.00	0-160	633.0	100.00
160-165	0.0	0.00	0-165	633.0	100.00
165-170	0.0	0.00	0-170	633.0	100.00
170-175	0.0	0.00	0-175	633.0	100.00
175-180	0.0	0.00	0-180	633.0	100.00

6. Product Photo



*****END OF REPORT*****