



LM-79-08 Test Report

for

GREEN CREATIVE LTD

756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

LED Downlight

Model: GIMB2/930/FL/DIM120

Laboratory: Leading Testing Laboratories

NVLAP CODE: 200960-0

3rd Floor, Bld. 2, NO. 96 Longchuanwu Rd Qianjiang Economy Dev. Zone, YuhangDist,
Hangzhou, Zhejiang Province, China 311100

Tel: +86571 86376106

www.ledtestlab.com

Report No.: HZ19020002n

The laboratory that conducted the testing detailed in this report has been accredited for SSL by NVLAP.

Review by:

Engineer: April Zou
Feb. 21, 2019

Approved by:



Manager: Jim Zhang
Feb. 21, 2019

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Test Summary

Sample Tested: GIMB2/930/FL/DIM120

Luminous Efficacy (Lumens /Watt)	Total Luminous Flux (Lumens)	Power (Watts)	Power Factor
76.7	618.3	8.06	0.9572
CCT (K)	CRI	Stabilization Time (Light & Power)	
3025	96.0	60	

Table 1: Executive Data Summary

Note: The above results are recorded/ derived from measurements made using an Integrating Sphere.

Test specifications:

Date of Receipt	: Feb. 01, 2019
Date of Test	: Feb. 12, 2019
Test item	: Total Luminous Flux, Luminous Distribution Intensity, Luminous Efficacy, Correlated Color Temperature, Color Rendering Index, Chromaticity Coordinate, Electrical parameters
Reference Standard	: IESNA LM-79-2008 Approved Method for the Electrical and Photometric Measurements of Solid-State Lighting Products

TABLE OF CONTENT

LM-79-08 Test Report.....	1
Test Summary.....	2
Sample Photo.....	4
TEST RESULTS	5
Spectral Power Distribution - Sphere Spectroradiometer Method	7
Chromaticity Diagram - Sphere Spectroradiometer Method.....	8
Nominal CCT Quadrangles – Sphere Spectroradiometer Method	9
Color Vector – Sphere Spectroradiometer Method	10
Zonal Lumen Tabulation- Goniophotometer Method	11
Luminous Intensity Distribution Plots- Goniophotometer Method.....	13
Luminous Intensity Data- Goniophotometer Method.....	14
EQUIPMENT LIST	16
TEST METHODS	16
Seasoning of SSL Product.....	16
Sphere-Spectroradiometer Method- Photometric and Electrical Measurements.....	16
Goniophotometer Method	17
Photometric and Electrical Measurements.....	17
Color Characteristics Measurements.....	17
Color Spatial Uniformity	17

Sample Photo



Figure 1- Overview of the sample

Equipment Under Test(EUT)

Name	: LED Downlight
Model	: GIMB2/930/FL/DIM120
Electrical Ratings	: 120V, 60Hz, 8W
Product Description	: 3000K
Manufacturer	: GREEN CREATIVE LTD
Address	: 756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

TEST RESULTS

Test ambient temperature was 25.0°C.

Base orientation was Light down. Test was conducted without a dimmer in the circuit.

The stabilization time of the sample was 60 minutes, and the total operating time including stabilization was 70 minutes.

Sphere-Spectroradiometer Method

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.070
Power Factor	0.9572
Test Power (W)	8.06
THD A%	22.04
Luminous Efficacy (lm/W)	76.7
Total Luminous Flux (lm)	618.3
Color Rendering Index (CRI)	96
R9	81.1
Correlated Color Temperature (CCT)(K)	3025
Chromaticity Chroma x	0.4359
Chromaticity Chroma y	0.4054
Chromaticity Chroma u	0.2494
Chromaticity Chroma v	0.3478
Duv	0.0006
Chromaticity Chroma u'	0.2494
Chromaticity Chroma v'	0.5218

Special Color Rendering Indices	
R1	97
R2	96.9
R3	95.1
R4	97.1
R5	96.3
R6	96
R7	96.9
R8	92.5
R9	81.1
R10	91.6
R11	97.2
R12	85.6
R13	96.9
R14	96.5
Rf	95
Rg	101

Table 2: Test data per Sphere-Spectroradiometer Method

Note: According to CIE 1976 (u',v') diagram, $u' = u = 4x/(-2x+12y+3)$, $v' = 3v/2 = 9y/(-2x+12y+3)$.

Goniophotometer Method

Test ambient temperature was 24.8°C.

The photometric distance is 2.47m.

Luminous data was taken at 0.5 °vertical intervals and 10 °horizontal intervals.

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.072
Power Factor	0.9508
Test Power (W)	8.17
Luminous Efficacy (lm/W)	76.7
Total Luminous Flux (lm)	626.7
Beam Angle (°)	36.9
Center Beam Candle Power (cd)	1275
Spacing Criteria	0.62(0 °-180 °)/ 0.61 (90 °-270 °)
Zonal Lumens in the 0 °-60 °Zone	97.27%
Zonal Lumens in the 60 °-90 °Zone	2.60%
Zonal Lumens in the 90 °-120 °Zone	0.00%
Zonal Lumens in the 120 °-180 °Zone	0.12%

Table 3: Test data per Goniophotometer Method

Spectral Power Distribution - Sphere Spectroradiometer Method





Chart 1: Spectral Power Distribution

Spectral Distribution over Visible Wavelength							
WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)
380	8.98E-05	485	3.07E-03	590	9.74E-03	695	5.97E-03
385	9.33E-05	490	3.60E-03	595	1.01E-02	700	5.04E-03
390	1.01E-04	495	4.16E-03	600	1.05E-02	705	4.48E-03
395	1.06E-04	500	4.77E-03	605	1.10E-02	710	3.97E-03
400	1.26E-04	505	5.28E-03	610	1.14E-02	715	3.51E-03
405	1.66E-04	510	5.72E-03	615	1.17E-02	720	3.07E-03
410	2.47E-04	515	6.08E-03	620	1.21E-02	725	2.68E-03
415	3.98E-04	520	6.39E-03	625	1.23E-02	730	2.34E-03
420	6.26E-04	525	6.67E-03	630	1.24E-02	735	2.02E-03
425	9.57E-04	530	6.96E-03	635	1.24E-02	740	1.76E-03
430	1.40E-03	535	7.22E-03	640	1.22E-02	745	1.53E-03
435	2.03E-03	540	7.51E-03	645	1.19E-02	750	1.32E-03
440	2.91E-03	545	7.77E-03	650	1.15E-02	755	1.15E-03
445	4.20E-03	550	7.99E-03	655	1.10E-02	760	1.00E-03
450	5.49E-03	555	8.21E-03	660	1.04E-02	765	8.54E-04
455	5.18E-03	560	8.39E-03	665	9.74E-03	770	7.41E-04
460	3.91E-03	565	8.55E-03	670	9.04E-03	775	6.38E-04
465	3.31E-03	570	8.76E-03	675	8.35E-03	780	5.50E-04
470	2.95E-03	575	8.92E-03	680	7.64E-03		
475	2.64E-03	580	9.14E-03	685	6.95E-03		
480	2.70E-03	585	9.47E-03	690	6.28E-03		

Table 4: Spectral Power Distribution Numerical Data per Sphere - Spectroradiometer Method

Chromaticity Diagram - Sphere Spectroradiometer Method



Tristimulus values(x, y): (0.4359, 0.4054)

Chart 2: Chromaticity Diagram per Sphere - Spectroradiometer Method

Note: The location on the diagram of the tristimulus coordinates are indicated by the blue diamond.

Nominal CCT Quadrangles – Sphere Spectroradiometer Method




Chart 3: Plot of Lamp x/y coordinates on CIE 1931 Chromaticity Diagram

Color Vector – Sphere Spectroradiometer Method




Chart 4: Color Vector Diagram of TM-30-18

Note: The values in this diagram might be a little different from the values in Table 2 due to rounding.

Zonal Lumen Tabulation- Goniophotometer Method

$\gamma(^{\circ})$	Lumens	% Total
0- 10	109.782	17.52%
10- 20	219.029	34.95%
20- 30	169.759	27.09%
30- 40	75.715	12.08%
40- 50	23.521	3.75%
50- 60	11.825	1.89%
60- 70	9.515	1.52%
70- 80	4.983	0.80%
80- 90	1.788	0.29%
90-100	0.015	0.00%
100-110	0	0.00%
110-120	0	0.00%
120-130	0.019	0.00%
130-140	0.097	0.02%
140-150	0.193	0.03%
150-160	0.23	0.04%
160-170	0.178	0.03%
170-180	0.06	0.01%
Total	626.7	100%

$\gamma(^{\circ})$	Lumens	% Total
0- 60	609.631	97.27%
60- 90	16.286	2.60%
0-90	625.917	99.87%
90- 180	0.792	0.13%
0- 180	626.7	100%

Table 5: Zonal Lumen




Chart 5: Illuminance Plot (Footcandles)

Luminous Intensity Distribution Plots- Goniophotometer Method




Chart 6: Isocandela Plot




Chart 7: Polar Candela Distribution

Luminous Intensity Data- Goniophotometer Method

Table--1 UNIT: cd

C (DEG) y (DEG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275
5	1205	1203	1199	1196	1193	1191	1193	1194	1197	1202	1205	1208	1211	1215	1220	1222	1223	1225	1227
10	1002	993	984	983	984	984	987	990	996	1003	1009	1017	1024	1030	1037	1042	1053	1054	1053
15	768	760	754	753	754	755	757	760	766	775	782	790	798	805	811	813	818	827	825
20	544	534	532	531	531	531	533	535	539	545	553	561	570	576	580	583	585	595	598
25	348	340	340	338	336	336	336	338	341	345	353	359	366	373	376	379	381	389	393
30	202	197	195	194	193	191	192	194	196	199	203	208	214	217	220	222	226	233	237
35	105	102	102	101	100	99.2	98.9	99.2	101	104	106	109	111	113	115	118	121	126	131
40	49.3	48.5	48.7	48.0	47.4	46.9	46.6	46.5	47.3	48.9	51.1	52.8	55.2	56.0	57.7	59.4	61.3	63.6	65.2
45	24.9	24.9	25.1	25.2	24.9	24.4	23.8	24.2	24.6	25.1	26.6	27.6	28.3	28.4	28.4	28.8	29.0	29.8	30.3
50	16.7	16.6	16.7	16.6	16.6	16.2	16.3	16.3	16.6	16.7	17.4	18.1	18.6	18.7	18.5	18.4	18.4	18.8	19.1
55	11.9	11.9	12.0	11.9	12.0	11.7	11.8	11.8	11.8	11.7	12.0	12.4	12.8	12.8	12.7	12.7	12.9	13.2	13.4
60	10.5	10.4	10.8	11.2	11.2	10.6	10.5	10.5	10.4	10.4	10.5	10.6	10.8	10.8	11.0	11.2	11.3	11.5	11.7
65	8.53	8.85	9.49	10.1	10.3	9.78	9.12	8.86	8.72	8.81	8.87	8.82	8.92	9.22	9.54	9.83	9.99	10.1	10.5
70	5.98	6.20	6.71	7.21	7.23	6.70	6.46	6.37	6.37	6.42	6.44	6.45	6.48	6.66	6.82	6.90	7.02	7.39	7.50
75	4.12	4.26	4.49	4.74	4.77	4.51	4.46	4.44	4.47	4.45	4.46	4.44	4.46	4.56	4.65	4.66	4.76	4.91	5.12
80	2.56	2.60	2.75	2.83	2.80	2.64	2.66	2.67	2.72	2.72	2.74	2.74	2.75	2.81	2.87	2.88	2.95	3.04	3.20
85	1.00	0.99	1.56	1.60	1.63	1.52	1.51	1.52	1.52	1.60	1.60	1.62	1.63	1.62	1.64	1.65	1.61	1.45	1.29
90	0.06	0.03	0.03	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.07	0.13	0.16	0.18	0.22	0.20	0.42
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
125	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02
130	0.04	0.04	0.04	0.04	0.04	0.04	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.06
135	0.09	0.09	0.09	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.13
140	0.15	0.15	0.15	0.15	0.15	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.13	0.21
145	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.20	0.30
150	0.29	0.29	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.29	0.29	0.29	0.28	0.38
155	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.38	0.37	0.44
160	0.45	0.46	0.46	0.46	0.46	0.46	0.46	0.46	0.46	0.47	0.47	0.47	0.47	0.47	0.47	0.47	0.47	0.47	0.48
165	0.51	0.51	0.51	0.51	0.52	0.52	0.52	0.52	0.53	0.53	0.53	0.53	0.53	0.54	0.54	0.54	0.54	0.54	0.53
170	0.54	0.55	0.55	0.56	0.56	0.56	0.56	0.57	0.57	0.57	0.57	0.58	0.58	0.58	0.58	0.58	0.59	0.59	0.58
175	0.58	0.58	0.57	0.57	0.57	0.58	0.58	0.58	0.59	0.59	0.59	0.59	0.60	0.60	0.60	0.60	0.61	0.61	0.62
180	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66

Table 6: Luminous Intensity Data

Table--2

UNIT: cd

C (DEG) y (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275	1275		
5	1228	1229	1229	1229	1229	1229	1229	1228	1227	1225	1222	1220	1219	1217	1214	1210	1207		
10	1055	1053	1051	1051	1049	1051	1052	1051	1049	1047	1043	1039	1035	1029	1022	1016	1009		
15	829	830	829	829	826	824	823	820	819	818	816	811	806	800	790	783	775		
20	599	601	602	602	602	598	595	592	590	588	587	585	579	572	564	556	548		
25	395	397	397	397	397	396	392	389	388	387	386	384	379	372	364	358	353		
30	238	239	239	239	238	238	237	236	234	233	232	230	225	218	213	209	206		
35	132	133	132	132	131	132	132	131	131	129	128	125	120	116	113	110	108		
40	65.4	66.4	66.0	65.8	65.6	65.6	65.8	65.9	65.6	65.3	64.2	62.3	60.1	57.7	54.8	52.4	50.8		
45	29.8	29.6	29.6	29.4	29.2	28.9	29.1	29.7	29.9	30.2	29.7	29.5	28.7	27.8	26.4	25.2	25.1		
50	19.1	19.0	19.0	18.9	18.7	18.7	18.6	18.6	18.6	18.8	18.5	18.7	18.5	18.1	17.4	16.7	16.7		
55	13.4	13.4	13.4	13.5	13.4	13.3	13.1	12.8	12.7	12.8	12.8	12.7	12.7	12.5	11.9	11.6	11.7		
60	11.9	12.2	12.3	12.4	12.2	12.1	11.9	11.6	11.5	11.6	11.7	11.5	11.4	11.2	10.8	10.5	10.4		
65	10.9	11.5	12.4	12.2	11.3	10.9	10.7	10.4	10.2	10.5	10.5	10.1	9.84	9.67	9.29	8.96	8.62		
70	7.78	8.23	8.60	8.43	7.83	7.38	6.95	6.70	6.83	6.78	6.73	6.63	6.55	6.46	6.28	6.03	5.90		
75	5.26	5.45	5.65	5.75	5.32	5.06	4.86	4.68	4.56	4.55	4.47	4.36	4.35	4.25	4.12	4.01	4.05		
80	3.27	3.36	3.47	3.56	3.33	3.23	3.16	3.05	2.96	2.96	2.88	2.73	2.69	2.66	2.58	2.53	2.54		
85	1.39	1.87	2.01	2.11	1.95	1.94	2.11	2.14	1.96	1.91	1.95	1.70	1.70	1.71	1.68	1.71	1.48		
90	0.32	0.67	0.72	0.68	0.52	0.51	0.56	0.51	0.45	0.42	0.43	0.30	0.37	0.27	0.20	0.13	0.10		
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
125	0.02	0.02	0.02	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03		
130	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.08		
135	0.16	0.16	0.16	0.16	0.16	0.17	0.17	0.17	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.19	0.16		
140	0.27	0.26	0.27	0.27	0.27	0.27	0.28	0.28	0.29	0.29	0.29	0.30	0.30	0.30	0.30	0.31	0.26		
145	0.40	0.39	0.39	0.39	0.39	0.40	0.40	0.41	0.41	0.42	0.42	0.43	0.43	0.43	0.44	0.46	0.36		
150	0.53	0.52	0.52	0.52	0.52	0.52	0.53	0.53	0.54	0.54	0.55	0.55	0.56	0.56	0.57	0.59	0.44		
155	0.64	0.62	0.62	0.62	0.63	0.63	0.64	0.64	0.65	0.65	0.65	0.66	0.66	0.67	0.68	0.70	0.48		
160	0.71	0.72	0.72	0.72	0.72	0.73	0.73	0.73	0.74	0.74	0.74	0.75	0.75	0.76	0.76	0.77	0.47		
165	0.69	0.77	0.77	0.77	0.77	0.78	0.78	0.79	0.79	0.79	0.80	0.80	0.80	0.81	0.82	0.75	0.51		
170	0.58	0.74	0.74	0.74	0.74	0.74	0.75	0.75	0.76	0.76	0.77	0.77	0.78	0.78	0.79	0.53	0.54		
175	0.63	0.63	0.64	0.65	0.65	0.65	0.66	0.68	0.70	0.71	0.71	0.71	0.68	0.60	0.60	0.59	0.59		
180	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66	0.66		

Table 7: Luminous Intensity Data

EQUIPMENT LIST

Test Equipment	Model	Equipment No.	Calibration Date	Calibration Due date
Goniophotometer system	GO-R5000	HZTE011-01	Aug. 14, 2018	Aug. 13, 2019
Digital Power Meter	PF2010A	HZTE028-01	Sep. 12, 2018	Sep. 11, 2019
AC Power Supply	DPS1060	HZTE001-06	Aug. 09, 2018	Aug. 08, 2019
DC Power Supply	WY12010	HZTE004-03	Aug. 09, 2018	Aug. 08, 2019
Temperature recorder	JM624U	HZTE018-08	Aug. 09, 2018	Aug. 08, 2019
Temperature and humidity recorder	JR900	HZTE018-01	Aug. 09, 2018	Aug. 08, 2019
Standard source	D908	HZTE012-01	Aug. 14, 2018	Aug. 13, 2019
Integrate Sphere system	3M	HZTE015-04	Aug. 16, 2018	Aug. 15, 2019
Digital Power Meter	WT210	HZTE008-01	Aug. 02, 2018	Aug. 01, 2019
AC Power Supply	PCR 500L	HZTE001-07	Aug. 09, 2018	Aug. 08, 2019
DC Power Supply	IT6154	HZTE004-04	Aug. 09, 2018	Aug. 08, 2019
Standard source	SCL-1400	HZTE012-02	Aug. 16, 2018	Aug. 15, 2019
Temperature and humidity recorder	JR900	HZTE018-02	Aug. 09, 2018	Aug. 08, 2019
Temperature Meter	TES1310	HZTE017-01	Aug. 09, 2018	Aug. 08, 2019

Table 8: Test Equipment List

TEST METHODS

Seasoning of SSL Product

For the purpose of rating new SSL products, SSL products shall be tested with no seasoning. Therefore, no seasoning was performed.

Sphere-Spectroradiometer Method- Photometric and Electrical Measurements

A Labsphere Model CDS 2100 Spectroradiometer and Two Meter Sphere was used to measure correlated color temperature, chromaticity coordinates, and the color rendering index for each SSL unit. The coating reflectance of each sphere is 98%. The measure geometry is 4π . Self-absorption correction is conducted in testing. Bandwidth of spectroradiometer is 350nm-1050nm.

Ambient temperature was measured at a position inside the sphere. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

The standard reference of the integrated sphere system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Standards and Technology.

The uncertainty of integrating sphere system reported in this document is expanded uncertainty is 2.1% with a coverage factor $k=2$.

Goniophotometer Method

Photometric and Electrical Measurements

An EVERFINE Type C Model GO-R5000 Goniophotometer was used to measure the intensity at each angle of distribution for each sample. The photometric distance is 2.475m for near-field measurement or 30m for far-field measurement. Bandwidth of spectroradiometer is 380nm-780nm.

Ambient temperature was measured at the same height of the sample mounted on the Goniophotometer equipment. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Everfine Digital Power Meter.

Some graphics were created with Photometric Plus software.

The standard reference of the Goniophotometer system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Metrology P.R. China.

The uncertainty of goniophotometer system reported in this document is expanded uncertainty is 2.3% with a coverage factor $k=2$.

Color Characteristics Measurements

The color characteristics of SSL products include chromaticity coordinates, correlated color temperature, and color rendering index. These characteristics of SSL products may be spatially non-uniform, and thus, in order that they can be specified accurately, the color quantities shall be measured as values that are spatially average, weighted to intensity, over the angular range where light is intentionally emitted from the SSL product. The color characteristics measurements are using gonio-spectroradiometer.

Color Spatial Uniformity

The characteristics of SSL products may be spatially non-uniform, the chromaticity coordinate shall be measured at two vertical planes ($C=0^\circ/180^\circ$ and $C=90^\circ/270^\circ$) and at 10° or less intervals for vertical angle until the light output dropped to below 10% of the peak intensity. The averaged weighted chromaticity coordinate

was calculated from these points. The data was then analyzed to check for delta color differences of the u' , v' chromaticity coordinates. The spatial non-uniformity of chromaticity, $\Delta u'v'$, is determined as the maximum deviation (distance on the CIE (u' , v') diagram) among all measured points from the spatially averaged chromaticity coordinate.

The geometry for the chromaticity measurement using gonio-spectroradiometer is shown as following.



*** End of Report ***

This report is considered invalidated without the Special Seal for Inspection of the LTL. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of LTL, this test report shall not be copied except in full and published as advertisement.