

IES LM-79-08

MEASUREMENT AND TEST REPORT

For

GREEN CREATIVE LTD

756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai, China

Test Model: SLFT8/80CCT2750/DIM010UNV

Report Type:	Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution
Test Engineer:	George Yang <i>George Yang</i>
Report Number:	PKS190130080-10-3
Test Date:	2019-01-31
Report Date:	2019-02-19
Reviewed By:	Ray Gao/EE Engineer <i>Ry Gao</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan). No.248 Chenghu Road, Kunshan, Jiangsu province, China. Tel: +86-0512-86175000 Fax: +86-0512-88934268
Test Facility:	Test facility was located at No.248 Chenghu Road, Kunshan, Jiangsu province, China.
Accreditation:	The IAS Accreditation Number TL-749.

1. Product Description

General Information:

one sample was received on 2019-01-30 and used for testing.

Model Tested: SLFT8/80CCT2750/DIM010UNV
 Manufacturer: GREEN CREATIVE LTD
 Brand Name: GREEN CREATIVE
 Product Designation: LED Downlight
 Dimming: Dimmable
 Connectable: None
 Color Tunable: White-tunable
 CCT Range: 2700K/5000K
 Aging Time Before Test: 0hour(For New Products)

Rated Values:

Rated Voltage/Frequency: 120-277VAC 50/60Hz
 Rated Power: 19W
 Nominal Lumen Output: 1900/1960lm

2. Standards Used

- IES LM-79-08: Approved Method: Electrical & Photometric Measurement of Solid-state Lighting Products
- ANSI C82.77-10-2014: Harmonic Emission Limits – Related Power Quality Requirements for Lighting Equipment
- IES TM-30-15: IES Method for Evaluating Light Source Color Rendition

3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
Integrating Sphere	INVENTFINE	Dia 1.5m	JWWCV090112	2019-01-23	2020-01-23
Power Meter	INVENTFINE	WT500	GSJWQ20009	2018-04-08	2019-04-08
Spectral photometer	INVENTFINE	CMS-3S	GSGSE100017	2019-01-23	2020-01-23
AC Power Supply	INVENTFINE	CHP500	JWJSD010071	2018-04-08	2019-04-08
Standard Light Source	INVENTFINE	N/A	JWWCR020106	2018-12-24	2019-12-24
Thermal Meter	KEJIAN	TA298	N/A	2018-12-01	2019-12-01
DC Power Supply	INVENTFINE	WL3005	JWWCP020069	2018-04-08	2019-04-08
AC Power Supply	INVENTFINE	CHP-5KVA	900511765	2018-04-08	2019-04-08
DC Power Supply	INVENTFINE	WL3010	JWDMP030001	2018-04-08	2019-04-08
Power Meter	INVENTFINE	WT500	GSDSQ200007	2018-04-08	2019-04-08
Goniophotometer	INVENTFINE	GPM-1900	YWGCF120001	2019-01-24	2020-01-24
Wireless Weather Station	ZHONGXING	KG218	N/A	2018-12-01	2019-12-01

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
Standard Light Source	INVENTFINE	N/A	JWBYR040008	2019-01-24	2020-01-24

Statement of Traceability: Bay Area Compliance Laboratories Corp.(Kunshan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with IES LM-79-08. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ during measurement. And relative humidity is less than 65%.

Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

4π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is $U_{\text{rel}}=2.61\%$ ($k=2$), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is $U=34\text{K}$ ($k=2$), at the 95% confidence level. The uncertainty of the CRI is $U=2.5(k=2)$, at the 95% confidence level.

The uncertainty of power meter AC current $U_{\text{rel}}=0.48\%$ of rdg, AC Voltage $U_{\text{rel}}=0.25\%$ of rdg, Power $U_{\text{rel}}=0.44\%$, ($k=2$), at the 95% confidence level.

Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The vertical angle (γ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

The uncertainty of the luminous flux is $U_{\text{rel}}=2.6\%$ ($k=2$), at the 95% confidence level.

Fidelity Index and Gamut Index Calculation

The R_f , R_g was calculated according to IES TM-30-15 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

5. Test Result

[Integrating Sphere System]

Test CCT Setting: 2700K

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Downward**


Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.1547	18.54	0.9987	1917.99	103.44

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
6.020	2670	-0.00072	0.4611	0.4089	0.2641	0.5269

Color Rendering Index


Ra			
83.1			
R1	R2	R3	R4
82	92	96	81
R5	R6	R7	R8
82	91	81	59
R9	R10	R11	R12
13	82	80	74
R13	R14	R15	
84	99	75	




Fidelity Index and Gamut Index

Fidelity Index R_f	83
Gamut Index R_g	96


Spectral Power Distribution Comparison




Plot of R_g versus R_f




Chroma Shift by Hue




R_t by Hue




Color Vector Graphic



Color Fidelity by CES Sample




Relative Spectral Power Distribution




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
380	3.890E-02	421	3.407E-01	462	1.069E+01	503	1.165E+01	544	2.095E+01
381	4.950E-02	422	3.877E-01	463	1.034E+01	504	1.195E+01	545	2.125E+01
382	2.800E-02	423	4.867E-01	464	1.011E+01	505	1.234E+01	546	2.147E+01
383	9.700E-03	424	5.260E-01	465	9.926E+00	506	1.267E+01	547	2.169E+01
384	4.730E-02	425	6.419E-01	466	9.726E+00	507	1.296E+01	548	2.193E+01
385	3.500E-02	426	7.249E-01	467	9.517E+00	508	1.326E+01	549	2.221E+01
386	3.200E-03	427	8.855E-01	468	9.246E+00	509	1.354E+01	550	2.252E+01
387	2.890E-02	428	1.055E+00	469	8.903E+00	510	1.383E+01	551	2.279E+01
388	2.120E-02	429	1.272E+00	470	8.533E+00	511	1.410E+01	552	2.311E+01
389	3.200E-03	430	1.473E+00	471	8.101E+00	512	1.440E+01	553	2.344E+01
390	4.600E-02	431	1.680E+00	472	7.692E+00	513	1.469E+01	554	2.367E+01
391	1.710E-02	432	1.989E+00	473	7.247E+00	514	1.495E+01	555	2.402E+01
392	6.400E-03	433	2.247E+00	474	6.926E+00	515	1.519E+01	556	2.435E+01
393	4.400E-03	434	2.572E+00	475	6.611E+00	516	1.546E+01	557	2.471E+01
394	9.400E-03	435	2.901E+00	476	6.363E+00	517	1.571E+01	558	2.515E+01
395	1.450E-02	436	3.294E+00	477	6.198E+00	518	1.593E+01	559	2.546E+01
396	1.290E-02	437	3.721E+00	478	6.102E+00	519	1.608E+01	560	2.577E+01
397	2.380E-02	438	4.207E+00	479	6.065E+00	520	1.637E+01	561	2.616E+01
398	4.100E-03	439	4.742E+00	480	6.083E+00	521	1.661E+01	562	2.657E+01
399	2.000E-04	440	5.349E+00	481	6.114E+00	522	1.682E+01	563	2.694E+01
400	0.000E+00	441	6.092E+00	482	6.216E+00	523	1.699E+01	564	2.738E+01
401	1.800E-02	442	6.911E+00	483	6.352E+00	524	1.716E+01	565	2.773E+01
402	4.140E-02	443	7.911E+00	484	6.406E+00	525	1.736E+01	566	2.810E+01
403	4.170E-02	444	9.087E+00	485	6.628E+00	526	1.756E+01	567	2.862E+01
404	2.170E-02	445	1.032E+01	486	6.715E+00	527	1.779E+01	568	2.909E+01
405	2.770E-02	446	1.172E+01	487	6.852E+00	528	1.796E+01	569	2.948E+01
406	6.900E-03	447	1.328E+01	488	7.062E+00	529	1.810E+01	570	2.994E+01
407	7.060E-02	448	1.472E+01	489	7.192E+00	530	1.828E+01	571	3.036E+01
408	6.000E-03	449	1.611E+01	490	7.440E+00	531	1.843E+01	572	3.083E+01
409	4.240E-02	450	1.723E+01	491	7.689E+00	532	1.861E+01	573	3.121E+01
410	7.810E-02	451	1.808E+01	492	7.942E+00	533	1.881E+01	574	3.168E+01
411	6.540E-02	452	1.838E+01	493	8.227E+00	534	1.901E+01	575	3.218E+01
412	7.770E-02	453	1.837E+01	494	8.489E+00	535	1.920E+01	576	3.260E+01
413	1.970E-02	454	1.778E+01	495	8.817E+00	536	1.934E+01	577	3.301E+01
414	1.039E-01	455	1.695E+01	496	9.184E+00	537	1.954E+01	578	3.349E+01
415	8.680E-02	456	1.584E+01	497	9.529E+00	538	1.972E+01	579	3.396E+01
416	9.400E-02	457	1.472E+01	498	9.885E+00	539	1.993E+01	580	3.434E+01
417	1.205E-01	458	1.364E+01	499	1.025E+01	540	2.016E+01	581	3.481E+01
418	1.615E-01	459	1.256E+01	500	1.059E+01	541	2.036E+01	582	3.524E+01
419	1.998E-01	460	1.179E+01	501	1.097E+01	542	2.057E+01	583	3.566E+01
420	2.792E-01	461	1.115E+01	502	1.131E+01	543	2.073E+01	584	3.614E+01

nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
585	3.645E+01	626	3.870E+01	667	1.961E+01	708	6.262E+00	749	1.229E+00
586	3.686E+01	627	3.837E+01	668	1.912E+01	709	6.067E+00	750	1.261E+00
587	3.730E+01	628	3.801E+01	669	1.869E+01	710	5.788E+00	751	1.230E+00
588	3.764E+01	629	3.771E+01	670	1.820E+01	711	5.614E+00	752	1.165E+00
589	3.800E+01	630	3.728E+01	671	1.778E+01	712	5.441E+00	753	1.141E+00
590	3.843E+01	631	3.684E+01	672	1.740E+01	713	5.379E+00	754	1.043E+00
591	3.883E+01	632	3.639E+01	673	1.693E+01	714	5.175E+00	755	9.392E-01
592	3.913E+01	633	3.600E+01	674	1.652E+01	715	4.932E+00	756	1.035E+00
593	3.946E+01	634	3.560E+01	675	1.608E+01	716	4.773E+00	757	9.390E-01
594	3.970E+01	635	3.513E+01	676	1.569E+01	717	4.612E+00	758	5.768E-01
595	4.005E+01	636	3.472E+01	677	1.532E+01	718	4.483E+00	759	8.403E-01
596	4.033E+01	637	3.430E+01	678	1.491E+01	719	4.237E+00	760	7.085E-01
597	4.066E+01	638	3.385E+01	679	1.450E+01	720	4.191E+00	761	7.386E-01
598	4.090E+01	639	3.340E+01	680	1.411E+01	721	4.039E+00	762	7.984E-01
599	4.098E+01	640	3.289E+01	681	1.375E+01	722	3.927E+00	763	8.410E-01
600	4.127E+01	641	3.246E+01	682	1.344E+01	723	3.793E+00	764	6.207E-01
601	4.144E+01	642	3.195E+01	683	1.313E+01	724	3.531E+00	765	5.038E-01
602	4.153E+01	643	3.134E+01	684	1.267E+01	725	3.526E+00	766	5.493E-01
603	4.169E+01	644	3.096E+01	685	1.229E+01	726	3.326E+00	767	6.425E-01
604	4.185E+01	645	3.043E+01	686	1.204E+01	727	3.152E+00	768	6.639E-01
605	4.190E+01	646	3.005E+01	687	1.174E+01	728	3.139E+00	769	4.762E-01
606	4.201E+01	647	2.944E+01	688	1.145E+01	729	3.107E+00	770	4.051E-01
607	4.207E+01	648	2.901E+01	689	1.106E+01	730	3.014E+00	771	4.663E-01
608	4.210E+01	649	2.843E+01	690	1.072E+01	731	2.789E+00	772	4.541E-01
609	4.205E+01	650	2.788E+01	691	1.042E+01	732	2.740E+00	773	3.417E-01
610	4.202E+01	651	2.747E+01	692	1.015E+01	733	2.417E+00	774	3.407E-01
611	4.199E+01	652	2.697E+01	693	9.864E+00	734	2.423E+00	775	4.270E-01
612	4.195E+01	653	2.645E+01	694	9.661E+00	735	2.392E+00	776	3.724E-01
613	4.191E+01	654	2.596E+01	695	9.323E+00	736	2.237E+00	777	3.540E-01
614	4.172E+01	655	2.549E+01	696	8.978E+00	737	2.177E+00	778	3.758E-01
615	4.160E+01	656	2.492E+01	697	8.785E+00	738	1.974E+00	779	3.042E-01
616	4.156E+01	657	2.445E+01	698	8.517E+00	739	1.893E+00	780	2.249E-01
617	4.129E+01	658	2.390E+01	699	8.271E+00	740	1.828E+00		
618	4.109E+01	659	2.347E+01	700	8.032E+00	741	1.866E+00		
619	4.082E+01	660	2.287E+01	701	7.795E+00	742	1.741E+00		
620	4.066E+01	661	2.245E+01	702	7.521E+00	743	1.675E+00		
621	4.038E+01	662	2.197E+01	703	7.286E+00	744	1.476E+00		
622	4.008E+01	663	2.146E+01	704	7.094E+00	745	1.484E+00		
623	3.980E+01	664	2.106E+01	705	6.871E+00	746	1.310E+00		
624	3.951E+01	665	2.056E+01	706	6.636E+00	747	1.357E+00		
625	3.913E+01	666	2.007E+01	707	6.417E+00	748	1.364E+00		

CIE 1931 x y Chromaticity Diagram



7-Step Chromaticity Quadrangles



Test CCT Setting: 5000K

Total operating time for integrating sphere test: **1.0 hour**


Test orientation: **Downward**

Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.1549	18.57	0.999	2012.07	108.35

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
6.289	5012	0.00418	0.3456	0.3604	0.2084	0.4890


Color Rendering Index




Fidelity Index and Gamut Index

Fidelity Index R_f	82
Gamut Index R_g	95


Spectral Power Distribution Comparison




Plot of R_g versus R_f




Chroma Shift by Hue




R_t by Hue




Color Vector Graphic



Color Fidelity by CES Sample




Relative Spectral Power Distribution




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
380	4.560E-02	421	9.802E-01	462	2.876E+01	503	2.064E+01	544	2.935E+01
381	5.670E-02	422	1.171E+00	463	2.745E+01	504	2.108E+01	545	2.950E+01
382	6.030E-02	423	1.419E+00	464	2.638E+01	505	2.157E+01	546	2.954E+01
383	3.020E-02	424	1.679E+00	465	2.552E+01	506	2.205E+01	547	2.958E+01
384	5.510E-02	425	2.068E+00	466	2.476E+01	507	2.243E+01	548	2.975E+01
385	2.070E-02	426	2.440E+00	467	2.382E+01	508	2.283E+01	549	2.967E+01
386	2.900E-03	427	2.892E+00	468	2.286E+01	509	2.323E+01	550	2.988E+01
387	6.610E-02	428	3.463E+00	469	2.171E+01	510	2.370E+01	551	2.994E+01
388	5.640E-02	429	4.056E+00	470	2.057E+01	511	2.395E+01	552	3.003E+01
389	2.600E-02	430	4.666E+00	471	1.934E+01	512	2.431E+01	553	3.011E+01
390	7.340E-02	431	5.369E+00	472	1.806E+01	513	2.463E+01	554	3.018E+01
391	4.660E-02	432	6.189E+00	473	1.694E+01	514	2.504E+01	555	3.020E+01
392	3.400E-03	433	7.095E+00	474	1.590E+01	515	2.532E+01	556	3.028E+01
393	1.000E-04	434	8.087E+00	475	1.503E+01	516	2.558E+01	557	3.040E+01
394	7.800E-03	435	9.174E+00	476	1.423E+01	517	2.593E+01	558	3.043E+01
395	2.440E-02	436	1.040E+01	477	1.367E+01	518	2.606E+01	559	3.043E+01
396	1.690E-02	437	1.176E+01	478	1.328E+01	519	2.633E+01	560	3.053E+01
397	4.600E-03	438	1.334E+01	479	1.307E+01	520	2.655E+01	561	3.057E+01
398	1.000E-04	439	1.510E+01	480	1.295E+01	521	2.682E+01	562	3.060E+01
399	3.900E-03	440	1.701E+01	481	1.288E+01	522	2.702E+01	563	3.068E+01
400	6.100E-03	441	1.945E+01	482	1.291E+01	523	2.713E+01	564	3.069E+01
401	2.110E-02	442	2.212E+01	483	1.299E+01	524	2.733E+01	565	3.070E+01
402	5.140E-02	443	2.520E+01	484	1.310E+01	525	2.750E+01	566	3.075E+01
403	2.970E-02	444	2.876E+01	485	1.320E+01	526	2.764E+01	567	3.085E+01
404	3.070E-02	445	3.269E+01	486	1.340E+01	527	2.779E+01	568	3.090E+01
405	3.440E-02	446	3.682E+01	487	1.358E+01	528	2.794E+01	569	3.102E+01
406	3.250E-02	447	4.107E+01	488	1.381E+01	529	2.804E+01	570	3.111E+01
407	7.860E-02	448	4.501E+01	489	1.399E+01	530	2.821E+01	571	3.100E+01
408	2.810E-02	449	4.897E+01	490	1.429E+01	531	2.824E+01	572	3.100E+01
409	8.060E-02	450	5.165E+01	491	1.464E+01	532	2.837E+01	573	3.101E+01
410	1.036E-01	451	5.371E+01	492	1.500E+01	533	2.855E+01	574	3.104E+01
411	1.472E-01	452	5.418E+01	493	1.546E+01	534	2.859E+01	575	3.098E+01
412	1.486E-01	453	5.382E+01	494	1.588E+01	535	2.865E+01	576	3.096E+01
413	1.343E-01	454	5.188E+01	495	1.637E+01	536	2.872E+01	577	3.106E+01
414	2.370E-01	455	4.931E+01	496	1.688E+01	537	2.883E+01	578	3.110E+01
415	2.910E-01	456	4.576E+01	497	1.746E+01	538	2.886E+01	579	3.104E+01
416	3.174E-01	457	4.228E+01	498	1.796E+01	539	2.900E+01	580	3.109E+01
417	3.863E-01	458	3.865E+01	499	1.852E+01	540	2.906E+01	581	3.107E+01
418	5.162E-01	459	3.533E+01	500	1.908E+01	541	2.913E+01	582	3.099E+01
419	6.512E-01	460	3.280E+01	501	1.958E+01	542	2.930E+01	583	3.095E+01
420	8.085E-01	461	3.060E+01	502	2.010E+01	543	2.934E+01	584	3.097E+01

nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
585	3.084E+01	626	2.380E+01	667	1.166E+01	708	3.630E+00	749	6.098E-01
586	3.083E+01	627	2.354E+01	668	1.132E+01	709	3.471E+00	750	5.798E-01
587	3.077E+01	628	2.317E+01	669	1.104E+01	710	3.223E+00	751	6.791E-01
588	3.073E+01	629	2.302E+01	670	1.080E+01	711	3.130E+00	752	6.773E-01
589	3.066E+01	630	2.264E+01	671	1.055E+01	712	3.011E+00	753	6.443E-01
590	3.059E+01	631	2.233E+01	672	1.027E+01	713	2.987E+00	754	5.411E-01
591	3.049E+01	632	2.196E+01	673	1.001E+01	714	2.898E+00	755	4.485E-01
592	3.042E+01	633	2.172E+01	674	9.731E+00	715	2.694E+00	756	5.310E-01
593	3.035E+01	634	2.143E+01	675	9.610E+00	716	2.614E+00	757	5.176E-01
594	3.024E+01	635	2.110E+01	676	9.294E+00	717	2.556E+00	758	2.152E-01
595	3.011E+01	636	2.075E+01	677	9.060E+00	718	2.419E+00	759	4.221E-01
596	3.002E+01	637	2.051E+01	678	8.794E+00	719	2.282E+00	760	2.815E-01
597	2.997E+01	638	2.014E+01	679	8.601E+00	720	2.234E+00	761	3.147E-01
598	2.990E+01	639	1.981E+01	680	8.343E+00	721	2.123E+00	762	4.319E-01
599	2.970E+01	640	1.957E+01	681	8.210E+00	722	2.103E+00	763	5.009E-01
600	2.958E+01	641	1.933E+01	682	8.001E+00	723	2.081E+00	764	3.007E-01
601	2.942E+01	642	1.891E+01	683	7.780E+00	724	1.876E+00	765	1.725E-01
602	2.919E+01	643	1.861E+01	684	7.548E+00	725	1.813E+00	766	2.619E-01
603	2.901E+01	644	1.824E+01	685	7.327E+00	726	1.762E+00	767	2.747E-01
604	2.895E+01	645	1.803E+01	686	7.098E+00	727	1.580E+00	768	3.827E-01
605	2.874E+01	646	1.770E+01	687	6.973E+00	728	1.607E+00	769	2.782E-01
606	2.863E+01	647	1.742E+01	688	6.720E+00	729	1.617E+00	770	2.042E-01
607	2.846E+01	648	1.708E+01	689	6.467E+00	730	1.599E+00	771	1.872E-01
608	2.815E+01	649	1.675E+01	690	6.299E+00	731	1.415E+00	772	2.281E-01
609	2.802E+01	650	1.656E+01	691	6.213E+00	732	1.499E+00	773	1.051E-01
610	2.784E+01	651	1.619E+01	692	6.011E+00	733	1.334E+00	774	1.367E-01
611	2.763E+01	652	1.589E+01	693	5.770E+00	734	1.220E+00	775	2.196E-01
612	2.741E+01	653	1.562E+01	694	5.591E+00	735	1.268E+00	776	2.222E-01
613	2.725E+01	654	1.528E+01	695	5.482E+00	736	1.105E+00	777	1.075E-01
614	2.698E+01	655	1.497E+01	696	5.250E+00	737	1.127E+00	778	2.130E-01
615	2.684E+01	656	1.467E+01	697	5.151E+00	738	9.749E-01	779	1.205E-01
616	2.658E+01	657	1.441E+01	698	4.992E+00	739	9.631E-01	780	1.380E-01
617	2.622E+01	658	1.405E+01	699	4.818E+00	740	9.278E-01		
618	2.602E+01	659	1.386E+01	700	4.664E+00	741	9.827E-01		
619	2.573E+01	660	1.357E+01	701	4.564E+00	742	9.476E-01		
620	2.542E+01	661	1.324E+01	702	4.351E+00	743	9.215E-01		
621	2.519E+01	662	1.291E+01	703	4.174E+00	744	7.203E-01		
622	2.494E+01	663	1.265E+01	704	4.058E+00	745	7.561E-01		
623	2.467E+01	664	1.244E+01	705	3.918E+00	746	5.053E-01		
624	2.437E+01	665	1.210E+01	706	3.819E+00	747	7.697E-01		
625	2.408E+01	666	1.189E+01	707	3.656E+00	748	6.748E-01		

CIE 1931 x y Chromaticity Diagram



7-Step Chromaticity Quadrangles



[Goniophotometer System]

Test CCT Setting: 2700K

Total operating time for luminous intensity distribution: **1.0 hours**

Test orientation: **Downward**


Electrical Measurement

Input Voltage (V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.0	60	0.155	18.64	1

Photometric Measurement

Luminous Flux (lm)	Efficacy (lm/W)	I_{max} (cd)	S/MH (C0/180)	S/MH (C90/270)
1930.8	103.63	956.0	1.19	1.19

Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle (50% I_{max}):	90.9	90.6	90.6	90.8	90.7
Field Angle (10% I_{max}):	130.1	129.9	130.1	130.2	130.1

Luminous Intensity (cd) Distribution Data

$\begin{matrix} C \\ \backslash \\ Y \end{matrix}$	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	956.0	956.0	956.0	956.0	956.0	956.0	956.0	956.0
5.0°	952.2	949.7	947.4	950.7	948.8	946.8	951.2	949.0
10.0°	939.9	935.8	932.3	935.7	931.6	930.7	934.2	931.9
15.0°	915.8	911.1	907.5	908.7	906.8	904.1	905.7	905.7
20.0°	878.1	874.8	870.1	869.8	868.3	867.1	869.1	869.5
25.0°	832.5	829.9	822.8	825.6	822.3	820.8	823.9	824.0
30.0°	770.6	765.8	762.5	758.9	758.3	755.9	758.1	760.6
35.0°	691.0	686.2	682.6	681.4	678.0	678.3	678.6	680.5
40.0°	596.2	591.7	587.6	586.3	584.9	584.9	588.0	589.8
45.0°	491.1	485.8	482.6	481.3	480.8	480.8	484.3	483.8
50.0°	378.5	372.6	370.3	371.1	369.4	368.7	373.3	374.4
55.0°	268.6	265.1	260.9	259.9	261.2	260.5	261.8	265.0
60.0°	170.2	166.9	165.1	163.6	163.8	162.3	162.8	165.6
65.0°	98.3	97.8	95.6	95.2	93.4	93.7	94.7	94.2
70.0°	64.2	63.3	62.9	62.8	62.4	61.8	62.7	62.8
75.0°	48.0	47.3	46.7	46.2	46.0	46.0	45.7	46.1
80.0°	31.1	30.0	30.0	28.4	28.4	28.5	28.7	29.4
85.0°	12.3	11.8	11.2	10.2	9.0	8.4	9.2	10.3
90.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155.0°	0.7	1.3	0.9	0.8	0.9	0.0	1.2	0.9
160.0°	1.2	1.4	1.5	1.3	1.5	1.7	1.4	1.0
165.0°	1.7	1.7	1.7	1.9	1.9	1.8	1.3	1.6
170.0°	1.7	1.8	1.9	1.8	2.1	1.7	1.8	1.8
175.0°	2.0	2.2	2.2	2.6	2.3	2.3	2.2	2.3
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Luminous Intensity (cd) Distribution Data (cont.)

$\begin{matrix} C \\ \backslash \\ y \end{matrix}$	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	956.0	956.0	956.0	956.0	956.0	956.0	956.0	956.0
5.0°	952.5	951.1	948.8	953.7	952.5	950.0	953.7	951.5
10.0°	936.9	935.8	936.4	937.4	941.3	939.6	940.4	939.9
15.0°	912.1	909.0	908.2	914.1	913.5	914.2	915.7	914.8
20.0°	873.5	873.9	872.1	879.1	879.7	878.4	880.9	878.3
25.0°	827.3	828.5	829.3	832.2	833.5	834.6	835.7	834.3
30.0°	760.8	762.4	764.0	770.4	770.6	770.7	770.5	766.5
35.0°	682.2	683.1	682.3	687.6	690.3	691.0	689.8	687.7
40.0°	588.6	590.5	590.0	594.9	597.2	597.1	596.3	593.6
45.0°	484.6	484.6	486.6	490.1	489.6	489.3	489.9	488.4
50.0°	370.6	372.8	375.2	379.3	377.4	376.3	377.5	375.5
55.0°	259.7	262.7	265.7	269.5	268.1	267.2	266.3	262.2
60.0°	160.5	163.7	167.0	168.0	169.0	168.9	166.5	164.9
65.0°	91.5	93.7	94.9	95.6	97.1	97.6	97.5	95.0
70.0°	61.3	62.2	62.6	63.3	63.8	64.0	63.7	63.3
75.0°	44.0	45.1	45.5	46.4	46.6	47.0	47.1	46.6
80.0°	26.8	27.8	28.4	29.0	29.0	29.6	29.4	28.9
85.0°	8.3	8.8	10.2	10.5	10.5	10.6	10.8	10.7
90.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155.0°	0.0	0.0	0.7	0.7	0.0	0.9	0.9	0.7
160.0°	0.0	0.7	1.0	1.0	1.3	1.0	1.4	0.9
165.0°	1.0	1.0	1.2	1.6	1.6	1.4	1.9	1.7
170.0°	1.3	1.2	2.1	1.8	1.8	2.1	2.1	1.6
175.0°	1.1	1.7	1.8	2.3	2.1	2.4	2.0	2.0
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Zonal Lumen Density Measurement

Deg	Flux (lm)	%	Deg	Flux (lm)	%
0-5	22.8	1.18	0-5	22.8	1.18
5-10	67.5	3.50	0-10	90.3	4.68
10-15	109.5	5.67	0-15	199.8	10.35
15-20	147.1	7.62	0-20	346.9	17.97
20-25	178.6	9.25	0-25	525.5	27.21
25-30	201.6	10.44	0-30	727.0	37.65
30-35	213.3	11.05	0-35	940.3	48.70
35-40	212.8	11.02	0-40	1153.1	59.72
40-45	199.4	10.33	0-45	1352.5	70.05
45-50	173.7	9.00	0-50	1526.3	79.05
50-55	138.7	7.18	0-55	1665.0	86.23
55-60	99.3	5.14	0-60	1764.3	91.38
60-65	63.4	3.28	0-65	1827.7	94.66
65-70	40.1	2.08	0-70	1867.8	96.74
70-75	28.6	1.48	0-75	1896.3	98.22
75-80	20.1	1.04	0-80	1916.5	99.26
80-85	10.6	0.55	0-85	1927.1	99.81
85-90	2.8	0.14	0-90	1929.9	99.96
90-95	0.0	0.00	0-95	1929.9	99.96
95-100	0.0	0.00	0-100	1929.9	99.96
100-105	0.0	0.00	0-105	1929.9	99.96
105-110	0.0	0.00	0-110	1929.9	99.96
110-115	0.0	0.00	0-115	1929.9	99.96
115-120	0.0	0.00	0-120	1929.9	99.96
120-125	0.0	0.00	0-125	1929.9	99.96
125-130	0.0	0.00	0-130	1929.9	99.96
130-135	0.0	0.00	0-135	1929.9	99.96
135-140	0.0	0.00	0-140	1929.9	99.96
140-145	0.0	0.00	0-145	1929.9	99.96
145-150	0.0	0.00	0-150	1929.9	99.96
150-155	0.1	0.00	0-155	1930.0	99.96
155-160	0.2	0.01	0-160	1930.2	99.97
160-165	0.2	0.01	0-165	1930.4	99.98
165-170	0.2	0.01	0-170	1930.6	99.99
170-175	0.1	0.01	0-175	1930.7	100.00
175-180	0.0	0.00	0-180	1930.8	100.00

Test CCT Setting: 5000K

Total operating time for luminous intensity distribution: **1.0 hours**

Test orientation: **Downward**


Electrical Measurement

Input Voltage (V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.0	60	0.156	18.67	1

Photometric Measurement

Luminous Flux (lm)	Efficacy (lm/W)	I _{max} (cd)	S/MH (C0/180)	S/MH (C90/270)
2025.2	108.53	1006.4	1.18	1.18

Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle (50% I _{max}):	89.8	89.9	89.8	89.8	89.8
Field Angle (10% I _{max}):	130.8	130.5	130.6	130.7	130.7

Luminous Intensity (cd) Distribution Data

C y	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	1006.4	1006.4	1006.4	1006.4	1006.4	1006.4	1006.4	1006.4
5.0°	1001.2	1000.9	998.0	1002.3	997.0	997.9	998.2	999.6
10.0°	985.8	985.7	982.2	985.9	982.0	979.3	980.7	983.2
15.0°	960.0	957.7	954.3	958.2	952.8	952.3	951.7	955.2
20.0°	922.0	920.1	914.2	919.4	910.0	913.1	912.3	914.3
25.0°	874.0	870.9	867.4	867.6	862.8	864.2	864.5	865.4
30.0°	804.9	803.1	800.1	801.7	795.3	792.0	794.3	793.6
35.0°	718.0	717.0	712.6	714.4	708.1	705.4	706.6	709.3
40.0°	617.4	614.6	611.8	611.6	607.3	605.7	606.9	608.3
45.0°	506.7	505.2	501.3	499.7	495.8	496.6	495.8	498.7
50.0°	393.3	388.5	387.1	386.4	382.7	384.4	385.4	387.3
55.0°	285.5	280.6	278.7	277.6	274.5	276.2	279.6	281.6
60.0°	186.4	182.0	178.4	177.6	175.8	176.2	179.7	181.3
65.0°	108.0	105.6	103.5	102.6	101.1	101.0	101.6	103.5
70.0°	67.8	66.9	66.7	66.5	65.6	65.7	65.7	66.3
75.0°	50.3	49.9	49.0	49.2	48.5	48.3	48.6	48.6
80.0°	32.8	31.9	31.2	31.4	30.0	30.0	30.8	30.8
85.0°	13.4	13.3	12.0	11.4	9.6	8.9	9.8	11.1
90.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145.0°	0.0	0.0	0.0	0.7	0.0	0.0	0.0	0.0
150.0°	0.0	1.0	0.9	0.7	1.0	1.1	1.3	1.3
155.0°	1.6	1.5	1.5	1.4	1.8	1.6	1.4	1.6
160.0°	1.6	1.6	2.1	1.6	1.9	2.3	2.1	2.6
165.0°	2.0	2.2	2.3	2.4	2.3	2.3	2.4	2.3
170.0°	2.3	2.7	2.6	2.7	2.4	3.0	2.8	2.4
175.0°	2.8	2.6	3.2	3.2	3.0	3.3	3.1	2.9
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



Luminous Intensity (cd) Distribution Data (cont.)

$\begin{matrix} C \\ \backslash \\ Y \end{matrix}$	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	1006.4	1006.4	1006.4	1006.4	1006.4	1006.4	1006.4	1006.4
5.0°	999.6	999.4	1002.1	1005.4	1002.3	1001.4	1002.6	1000.3
10.0°	984.2	985.4	984.6	991.9	986.8	989.0	986.4	986.6
15.0°	954.7	957.1	959.0	963.2	962.4	961.4	960.0	959.1
20.0°	915.9	919.0	920.5	925.9	921.9	926.0	922.2	921.0
25.0°	866.5	869.0	870.8	875.6	872.6	876.1	873.1	872.8
30.0°	794.6	797.5	802.3	806.7	804.8	805.6	804.7	802.8
35.0°	707.5	708.9	714.1	719.5	719.0	718.5	716.0	715.8
40.0°	606.3	608.0	614.1	619.2	619.5	618.2	615.6	613.6
45.0°	494.9	499.9	503.4	506.7	505.7	507.4	505.6	502.0
50.0°	384.5	387.2	390.8	392.6	392.6	393.0	392.6	389.1
55.0°	275.9	278.3	280.9	282.6	282.5	284.3	284.7	281.9
60.0°	176.8	178.4	178.4	181.4	182.2	184.9	183.7	183.0
65.0°	99.3	101.2	101.1	103.0	104.7	105.6	105.0	104.7
70.0°	64.6	65.4	66.3	66.8	66.7	67.0	67.4	67.3
75.0°	46.7	47.5	48.4	48.7	49.1	49.3	49.5	49.1
80.0°	28.7	29.3	29.9	30.6	31.5	31.2	31.0	30.7
85.0°	9.0	10.4	11.6	12.1	12.0	11.6	12.1	12.0
90.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150.0°	0.0	0.0	0.7	1.0	0.8	0.8	0.9	0.7
155.0°	0.8	1.1	1.2	1.3	1.1	1.3	1.6	1.4
160.0°	1.2	1.7	1.5	1.8	1.9	2.2	2.1	1.9
165.0°	1.8	2.2	2.1	2.5	2.3	2.5	2.3	2.4
170.0°	2.2	2.6	2.6	2.8	2.4	2.8	3.0	2.5
175.0°	2.5	2.4	2.6	3.0	2.6	2.8	2.9	3.0
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Zonal Lumen Density Measurement

Deg	Flux (lm)	%	Deg	Flux (lm)	%
0-5	24.0	1.18	0-5	24.0	1.18
5-10	71.0	3.51	0-10	95.0	4.69
10-15	115.2	5.69	0-15	210.2	10.38
15-20	154.6	7.63	0-20	364.9	18.02
20-25	187.5	9.26	0-25	552.4	27.28
25-30	211.3	10.43	0-30	763.7	37.71
30-35	222.9	11.00	0-35	986.6	48.71
35-40	221.2	10.92	0-40	1207.7	59.63
40-45	206.3	10.18	0-45	1414.0	69.82
45-50	179.9	8.88	0-50	1593.9	78.70
50-55	145.5	7.18	0-55	1739.3	85.88
55-60	106.5	5.26	0-60	1845.8	91.14
60-65	68.9	3.40	0-65	1914.8	94.55
65-70	43.0	2.12	0-70	1957.7	96.67
70-75	30.1	1.49	0-75	1987.9	98.15
75-80	21.3	1.05	0-80	2009.1	99.20
80-85	11.4	0.56	0-85	2020.5	99.77
85-90	3.1	0.15	0-90	2023.6	99.92
90-95	0.0	0.00	0-95	2023.6	99.92
95-100	0.0	0.00	0-100	2023.6	99.92
100-105	0.0	0.00	0-105	2023.6	99.92
105-110	0.0	0.00	0-110	2023.6	99.92
110-115	0.0	0.00	0-115	2023.6	99.92
115-120	0.0	0.00	0-120	2023.6	99.92
120-125	0.0	0.00	0-125	2023.6	99.92
125-130	0.0	0.00	0-130	2023.6	99.92
130-135	0.0	0.00	0-135	2023.6	99.92
135-140	0.0	0.00	0-140	2023.6	99.92
140-145	0.0	0.00	0-145	2023.6	99.92
145-150	0.1	0.01	0-150	2023.8	99.93
150-155	0.3	0.01	0-155	2024.0	99.94
155-160	0.3	0.02	0-160	2024.4	99.96
160-165	0.3	0.02	0-165	2024.7	99.97
165-170	0.3	0.01	0-170	2025.0	99.99
170-175	0.2	0.01	0-175	2025.2	100.00
175-180	0.0	0.00	0-180	2025.2	100.00

6. Product Photo



*****END OF REPORT*****