

LM-79-08 TEST REPORT

for

GREEN CREATIVE LTD

Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, KL,
Hong Kong

LED Tube

Model: 10T8/4F/850/DEB/C

Laboratory: Leading Testing Laboratories

NVLAP CODE: 200960-0

3rd Floor, Bld. 2, NO. 96 Longchuanwu Rd Qianjiang Economy Dev. Zone, YuhangDist,
Hangzhou, Zhejiang Province, China 311100

Tel: +86571 86376106

www.ledtestlab.com

Report No.: HZ20070023d

The laboratory that conducted the testing detailed in this report has been accredited for SSL by NVLAP.

Review by:



Engineer: April Zou

Aug. 03, 2020

Approved by:



Manager: Jim Zhang

Aug. 03, 2020

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TEST SUMMARY

Sample Tested: 10T8/4F/850/DEB/C

Luminous Efficacy (Lumens /Watt)	Total Luminous Flux (Lumens)	Power (Watts)	Power Factor
178.6	1844.7	10.33	0.9789
CCT (K)	CRI	Stabilization Time (Light & Power)	
5065	82.7	60	

Table 1: Executive Data Summary

Note: The above results are recorded/ derived from measurements made using an Integrating Sphere.

Test specifications:

Date of Receipt	: Jul. 22, 2020
Date of Test	: Jul. 24, 2020
Test item	: Total Luminous Flux, Luminous Distribution Intensity, Luminous Efficacy, Correlated Color Temperature, Color Rendering Index, Chromaticity Coordinate, Electrical parameters
Reference Standard	: IESNA LM-79-2008 Approved Method for the Electrical and Photometric Measurements of Solid-State Lighting Products ANSI/IES TM-30-18 IES Method for Evaluating Light Source Color Rendition

TABLE OF CONTENT

LM-79-08 TEST REPORT	1
TEST SUMMARY	2
SAMPLE PHOTO	4
TEST RESULTS	5
Sphere-Spectroradiometer Method.....	5
Goniophotometer Method	6
Spectral Power Distribution - Sphere Spectroradiometer Method	7
Chromaticity Diagram - Sphere Spectroradiometer Method.....	8
Nominal CCT Quadrangles – Sphere Spectroradiometer Method	9
Color Rendition Report – Sphere Spectroradiometer Method	10
Zonal Lumen Tabulation- Goniophotometer Method	11
Illuminance Plots- Goniophotometer Method	12
Luminous Intensity Distribution Plots- Goniophotometer Method.....	13
Luminous Intensity Data- Goniophotometer Method	14
EQUIPMENT LIST	16
TEST METHODS	16
Seasoning of SSL Product.....	16
Sphere-Spectroradiometer Method- Photometric and Electrical Measurements.....	16
Goniophotometer Method	17
Photometric and Electrical Measurements	17
Color Characteristics Measurements.....	17
Color Spatial Uniformity	17

SAMPLE PHOTO



Figure 1- Overview of the sample

Equipment Under Test(EUT)

Name	: LED Tube
Model	: 10T8/4F/850/DEB/C
Electrical Ratings	: 120-277V, 50/60Hz, 10W
Product Description	: 5000K
Manufacturer	: GREEN CREATIVE LTD
Address	: Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, KL, Hong Kong

TEST RESULTS

Test ambient temperature was 26.0 °C.

Base orientation was horizontal. Test was conducted without a dimmer in the circuit.

The stabilization time of the sample was 60 minutes, and the total operating time including stabilization was 65 minutes.

Sphere-Spectroradiometer Method

Parameter	Result	
Test Voltage (V)	120.0	277.0
Voltage frequency (Hz)	60	60
Test Current (A)	0.088	0.042
Power Factor	0.9789	0.9063
Test Power (W)	10.33	10.46
THD A%	18.31	20.21
Luminous Efficacy (lm/W)	178.6	176.0
Total Luminous Flux (lm)	1844.7	1841.3
Color Rendering Index (CRI)	82.7	
R9	6	
Correlated Color Temperature (CCT)(K)	5065	
Chromaticity Chroma x	0.3435	
Chromaticity Chroma y	0.3539	
Chromaticity Chroma u	0.2095	
Chromaticity Chroma v	0.3237	
Duv	0.0018	
Chromaticity Chroma u'	0.2095	
Chromaticity Chroma v'	0.4856	

Special Color Rendering Indices	
R1	81.1
R2	87.9
R3	92.3
R4	82.7
R5	81.8
R6	82.8
R7	86.5
R8	66.7
R9	6
R10	71.2
R11	82.1
R12	60.5
R13	82.9
R14	96

Table 2: Test data per Sphere-Spectroradiometer Method

Note: According to CIE 1976 (u', v') diagram, $u' = u = 4x/(-2x+12y+3)$, $v' = 3v/2 = 9y/(-2x+12y+3)$.

Goniophotometer Method

Test ambient temperature was 25.0 °C.

The photometric distance is 30 m.

Luminous data was taken at 0.5 vertical intervals and 10 horizontal intervals.

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.088
Power Factor	0.9793
Power (W)	10.36
Luminous Efficacy (lm/W)	176.4
Total Luminous Flux (lm)	1827.4
Beam Angle (°)	107.4 (0°-180°) / 181.5 (90°-270°)
Center Beam Candle Power (cd)	354
Maximum Beam Candle Power (cd)	354.5 (At: C=60.0, Gamma=2.0)
Spacing Criteria	1.23 (0°-180°) / 1.34 (90°-270°)
Zonal Lumens in the 0 °-60 °Zone	46.95%
Zonal Lumens in the 60 °-90 °Zone	26.34%
Zonal Lumens in the 90 °-120 °Zone	15.61%
Zonal Lumens in the 120 °-180 °Zone	11.10%

Table 3: Test data per Goniophotometer Method

Spectral Power Distribution - Sphere Spectroradiometer Method




Chart 1: Spectral Power Distribution

Spectral Distribution over Visible Wavelength							
WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)
380	2.18E-04	485	1.17E-02	590	2.91E-02	695	3.79E-03
385	1.88E-04	490	1.30E-02	595	2.87E-02	700	3.25E-03
390	1.88E-04	495	1.52E-02	600	2.80E-02	705	2.77E-03
395	1.73E-04	500	1.77E-02	605	2.72E-02	710	2.37E-03
400	1.34E-04	505	1.99E-02	610	2.61E-02	715	2.02E-03
405	1.60E-04	510	2.16E-02	615	2.47E-02	720	1.74E-03
410	3.12E-04	515	2.31E-02	620	2.32E-02	725	1.49E-03
415	6.41E-04	520	2.40E-02	625	2.17E-02	730	1.26E-03
420	1.39E-03	525	2.46E-02	630	2.00E-02	735	1.08E-03
425	2.87E-03	530	2.52E-02	635	1.82E-02	740	9.16E-04
430	5.74E-03	535	2.57E-02	640	1.66E-02	745	7.89E-04
435	1.08E-02	540	2.61E-02	645	1.49E-02	750	6.74E-04
440	1.99E-02	545	2.66E-02	650	1.33E-02	755	5.78E-04
445	3.68E-02	550	2.70E-02	655	1.18E-02	760	4.95E-04
450	5.27E-02	555	2.75E-02	660	1.04E-02	765	4.23E-04
455	4.30E-02	560	2.79E-02	665	9.09E-03	770	3.67E-04
460	2.76E-02	565	2.84E-02	670	7.91E-03	775	3.13E-04
465	2.23E-02	570	2.88E-02	675	6.88E-03	780	2.70E-04
470	1.65E-02	575	2.91E-02	680	5.94E-03		
475	1.20E-02	580	2.92E-02	685	5.14E-03		
480	1.11E-02	585	2.93E-02	690	4.42E-03		

Table 4: Spectral Power Distribution Numerical Data per Sphere - Spectroradiometer Method

Chromaticity Diagram - Sphere Spectroradiometer Method




Chart 2: Chromaticity Diagram per Sphere - Spectroradiometer Method

Note: The location on the diagram of the tristimulus coordinates are indicated by the blue diamond.

Nominal CCT Quadrangles – Sphere Spectroradiometer Method





Chart 3: Plot of Lamp x/y coordinates on CIE 1931 Chromaticity Diagram

Color Rendition Report – Sphere Spectroradiometer Method



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3435

y 0.3539

u' 0.2095

v' 0.4856

Chart 4: Full Report Created with the IES TM-30 Calculator

Note: The values in this diagram might be a little different from the values in Table 2 due to rounding.

Zonal Lumen Tabulation- Goniophotometer Method

$\gamma(^{\circ})$	Lumens	% Total
0- 10	33.538	1.84%
10- 20	96.376	5.27%
20- 30	147.592	8.08%
30- 40	182.416	9.98%
40- 50	199.148	10.90%
50- 60	198.831	10.88%
60- 70	184.666	10.11%
70- 80	161.388	8.83%
80- 90	135.3	7.40%
90-100	112.827	6.17%
100-110	94.296	5.16%
110-120	78.148	4.28%
120-130	64.182	3.51%
130-140	51.665	2.83%
140-150	39.723	2.17%
150-160	27.554	1.51%
160-170	14.912	0.82%
170-180	4.833	0.26%
Total	1827.4	100%

$\gamma(^{\circ})$	Lumens	% Total
0- 60	857.901	46.95%
60- 90	481.354	26.34%
0-90	1339.255	73.29%
90- 180	488.14	26.71%
0- 180	1827.4	100%

Table 5: Zonal Lumen

Illuminance Plots- Goniophotometer Method




Chart 5: Illuminance Plot (Footcandles)

Luminous Intensity Distribution Plots- Goniophotometer Method




Chart 6: Isocandela Plot




Chart 7: Polar Candela Distribution

Luminous Intensity Data- Goniophotometer Method

Table--1

UNIT: cd

C (DGG) γ (DGG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	354	354	354	354	354	354	354	354	354	354	354	354	354	354	354	354	354	354	354
5	353	353	353	353	354	354	354	354	354	354	354	354	354	353	353	353	353	353	353
10	348	348	348	349	349	350	351	351	351	351	351	350	350	350	349	349	348	347	347
15	339	339	340	342	343	344	345	346	347	347	346	346	345	343	342	341	340	339	338
20	327	328	329	331	334	336	337	339	340	340	340	338	337	335	332	330	328	327	326
25	312	313	315	318	322	325	328	331	332	332	332	330	327	324	320	317	314	312	310
30	294	295	299	303	308	312	317	321	322	323	322	320	316	312	306	301	297	294	292
35	273	275	279	285	292	299	305	310	312	313	312	309	304	298	291	284	278	273	271
40	250	253	258	266	275	284	292	298	301	302	301	297	291	283	274	265	257	251	248
45	225	228	236	246	257	268	278	285	290	291	289	284	277	267	256	245	235	227	223
50	198	202	212	225	239	252	264	273	278	279	277	272	263	251	238	224	211	201	197
55	171	175	187	203	220	237	250	260	265	267	265	259	248	236	220	203	187	175	169
60	142	149	163	182	202	221	236	246	253	255	252	245	234	220	202	182	164	149	141
65	114	121	140	162	185	205	222	233	240	242	240	232	220	205	185	163	141	122	113
70	85.2	94.2	117	144	169	191	208	220	227	229	227	219	207	190	169	145	119	96.6	84.9
75	57.7	69.1	96.0	126	154	177	195	207	214	217	214	206	193	176	154	128	98.6	72.5	58.6
80	32.4	47.1	78.3	111	140	164	182	194	202	204	202	194	181	163	141	113	81.2	51.4	33.7
85	10.9	30.3	64.4	98.2	128	152	169	182	189	192	189	181	169	152	128	99.7	67.2	34.6	12.4
90	0.45	20.9	54.6	87.6	117	140	158	170	177	180	177	170	157	140	117	89.0	57.0	24.3	0.59
95	2.88	17.6	48.2	79.3	107	130	147	159	166	168	165	159	147	129	107	80.3	50.0	19.8	2.21
100	6.85	18.1	43.9	72.5	98.5	120	137	149	155	157	155	148	136	120	98.7	73.2	45.1	18.8	5.46
105	11.5	20.9	41.7	67.0	90.8	111	127	138	144	146	144	138	126	111	90.8	67.3	42.0	20.6	9.53
110	16.5	24.9	41.5	62.7	84.0	103	117	127	133	135	133	127	117	102	83.8	62.5	40.9	24.1	14.1
115	21.4	29.4	42.5	60.0	78.2	94.8	108	118	123	125	123	117	108	94.2	77.8	59.2	41.2	28.1	18.9
120	26.4	33.7	44.3	58.5	73.7	88.0	99.9	108	113	115	113	108	99.2	87.3	72.9	57.3	42.4	32.2	24.0
125	31.1	37.9	46.3	57.9	70.4	82.3	92.4	99.9	104	106	104	99.6	91.8	81.4	69.3	56.3	44.3	36.4	29.3
130	35.7	41.7	48.5	57.8	68.0	77.9	86.2	92.4	96.2	97.6	96.2	92.0	85.4	76.8	66.7	56.0	46.5	40.3	34.2
135	40.1	45.3	50.6	58.0	66.3	74.3	81.1	86.2	89.3	90.4	89.2	85.8	80.3	73.1	64.9	56.3	48.8	43.9	39.2
140	44.1	47.8	52.5	58.4	64.9	71.3	76.8	80.9	83.5	84.3	83.3	80.5	76.0	70.1	63.5	56.8	51.1	47.2	43.9
145	45.5	50.8	54.4	58.8	63.8	68.8	73.1	76.4	78.4	79.1	78.2	75.9	72.3	67.7	62.6	57.5	53.1	50.1	47.2
150	48.3	53.0	54.0	59.2	63.0	66.7	69.9	72.4	73.9	74.4	73.8	72.0	69.2	65.7	61.9	58.2	55.0	52.9	50.6
155	51.7	54.8	55.9	59.7	62.2	64.9	67.2	69.0	70.1	70.4	70.0	68.7	66.7	64.1	61.5	58.9	56.7	55.4	53.4
160	49.2	54.4	56.0	58.7	61.7	63.3	64.9	66.1	66.8	67.0	66.8	65.9	64.6	62.9	61.2	59.6	58.2	57.3	56.7
165	45.5	50.2	53.8	57.1	60.6	62.1	63.0	63.6	64.1	64.3	64.2	63.7	63.0	62.0	61.1	60.2	59.4	58.9	58.7
170	41.3	45.1	48.7	54.2	58.2	60.8	61.6	61.9	62.1	62.3	62.2	62.1	61.8	61.4	60.9	60.5	60.1	59.4	58.3
175	38.8	41.6	45.9	50.2	54.4	56.8	58.0	59.4	60.4	60.9	61.1	61.0	60.9	60.8	60.6	60.5	60.4	60.1	59.5
180	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3

Table 6: Luminous Intensity Data

Table--2

UNIT: cd

C (DEG) y (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	354	354	354	354	354	354	354	354	354	354	354	354	354	354	354	354	354		
5	352	352	352	352	352	352	352	352	352	352	353	352	352	352	352	352	353		
10	346	346	347	347	347	347	347	348	348	348	348	348	348	347	347	348	348		
15	337	337	338	339	339	340	341	341	342	342	342	341	340	340	340	339	339		
20	325	325	326	328	329	331	332	333	334	334	334	332	331	330	329	328	327		
25	310	310	312	315	318	320	322	324	325	325	324	322	320	318	315	313	312		
30	292	293	296	300	304	308	312	314	315	315	314	311	307	304	300	296	294		
35	271	273	278	284	290	296	300	304	305	305	303	299	294	288	282	277	274		
40	249	252	258	266	275	283	289	293	295	295	291	286	279	271	263	256	251		
45	224	229	238	249	260	269	277	282	285	284	280	273	264	254	243	233	227		
50	199	206	217	231	244	256	265	272	274	273	268	260	249	236	223	210	201		
55	172	182	196	213	229	243	253	260	263	262	256	247	234	219	202	186	175		
60	145	158	176	196	214	230	242	249	252	251	245	234	220	202	182	163	148		
65	118	134	156	179	200	217	230	238	241	239	232	221	205	185	163	140	121		
70	91.8	112	138	163	186	204	217	226	229	227	220	208	191	170	144	118	94.7		
75	67.5	92.2	121	149	172	191	205	214	217	215	208	195	177	155	128	98.1	70.8		
80	45.8	74.9	106	135	159	179	193	201	204	202	195	182	164	141	113	81.2	50.1		
85	28.9	61.4	93.4	122	147	166	180	188	192	190	182	170	152	129	100	68.1	34.3		
90	18.9	50.9	82.5	111	135	154	167	175	179	176	169	157	140	117	89.1	57.7	24.6		
95	15.0	43.3	73.2	101	124	142	155	162	165	163	156	145	128	106	79.7	50.0	20.2		
100	15.4	39.0	65.8	91.5	113	130	142	150	153	151	144	133	117	96.9	72.1	45.2	20.1		
105	17.7	37.2	60.9	83.7	104	120	131	138	141	139	133	122	108	88.8	66.3	43.2	21.9		
110	21.2	37.2	57.1	77.2	95.3	110	120	127	129	128	122	112	99.0	82.1	62.9	42.9	25.0		
115	24.5	38.5	54.8	72.1	88.1	101	111	117	119	117	112	104	91.7	77.0	60.4	43.8	28.2		
120	27.5	40.4	53.8	68.4	82.3	93.7	102	107	109	108	104	96.2	85.8	73.1	59.0	45.2	31.2		
125	29.6	42.8	53.6	65.6	77.4	87.5	94.8	99.6	101	100	96.5	89.9	80.9	70.1	58.2	46.9	33.6		
130	30.8	45.3	53.8	63.7	73.5	82.2	88.5	92.6	94.3	93.4	90.0	84.4	76.7	67.7	58.0	48.7	35.1		
135	30.8	47.3	54.4	62.7	70.7	77.6	82.9	86.5	87.9	87.2	84.4	79.6	73.2	65.9	58.0	50.5	35.3		
140	30.1	47.7	55.0	61.7	68.2	73.6	78.1	81.0	82.3	81.7	79.4	75.5	70.4	64.5	58.1	52.0	34.6		
145	32.5	47.3	55.6	60.9	66.2	70.2	73.9	76.2	77.3	76.8	75.0	71.9	68.3	63.5	58.2	50.3	35.4		
150	38.9	43.3	55.1	60.5	64.2	67.9	70.2	72.0	72.9	72.5	71.2	69.0	66.1	61.5	57.7	45.5	37.3		
155	43.1	32.5	47.3	60.1	62.7	65.2	67.4	68.6	70.2	68.6	68.3	65.8	59.7	55.6	51.6	38.0	38.1		
160	44.7	30.5	35.3	46.9	60.0	62.0	64.2	65.3	65.8	66.0	60.8	52.2	48.7	46.7	41.4	34.0	39.9		
165	54.4	37.7	28.3	32.4	35.9	48.0	56.7	59.4	62.4	47.9	42.2	41.8	41.0	36.0	32.8	34.5	37.6		
170	56.0	50.6	41.1	32.8	35.0	39.8	41.8	45.5	30.0	43.1	45.5	42.4	37.5	35.5	33.7	34.3	37.9		
175	58.7	57.9	57.0	56.4	56.4	57.4	58.5	53.5	40.4	27.7	39.6	39.0	37.5	37.2	39.6	40.0	38.8		
180	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3	55.3		

Table 7: Luminous Intensity Data

EQUIPMENT LIST

Test Equipment	Model	Equipment No.	Calibration Date	Calibration Due date
Goniophotometer system	GO-R5000	HZTE011-01	Aug. 02, 2019	Aug. 01, 2020
Digital Power Meter	PF2010A	HZTE028-01	Aug. 02, 2019	Aug. 01, 2020
AC Power Supply	DPS1060	HZTE001-06	Aug. 02, 2019	Aug. 01, 2020
DC Power Supply	WY12010	HZTE004-03	Aug. 02, 2019	Aug. 01, 2020
Temperature recorder	JM624U	HZTE018-08	Aug. 02, 2019	Aug. 01, 2020
Temperature and humidity recorder	JR900	HZTE018-01	Aug. 02, 2019	Aug. 01, 2020
Standard source	D908	HZTE012-01	Aug. 02, 2019	Aug. 01, 2020
Integrate Sphere system	3M	HZTE015-04	Aug. 02, 2019	Aug. 01, 2020
Digital Power Meter	WT210	HZTE008-01	Aug. 02, 2019	Aug. 01, 2020
AC Power Supply	PCR 500L	HZTE001-07	Aug. 02, 2019	Aug. 01, 2020
DC Power Supply	IT6154	HZTE004-04	Aug. 02, 2019	Aug. 01, 2020
Standard source	SCL-1400	HZTE012-02	Aug. 02, 2019	Aug. 01, 2020
Temperature and humidity recorder	JR900	HZTE018-02	Aug. 02, 2019	Aug. 01, 2020
Temperature Meter	TES1310	HZTE017-01	Aug. 02, 2019	Aug. 01, 2020

Table 8: Test Equipment List

TEST METHODS

Seasoning of SSL Product

For the purpose of rating new SSL products, SSL products shall be tested with no seasoning. Therefore, no seasoning was performed.

Sphere-Spectroradiometer Method- Photometric and Electrical Measurements

A Labsphere Model CDS 2100 Spectroradiometer and Two Meter Sphere was used to measure correlated color temperature, chromaticity coordinates, and the color rendering index for each SSL unit. The coating reflectance of each sphere is 98%. The measure geometry is 4π . Self-absorption correction is conducted in testing. Bandwidth of spectroradiometer is 350nm-1050nm.

Ambient temperature was measured at a position inside the sphere. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

The standard reference of the integrated sphere system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Standards and Technology.

The uncertainty of integrating sphere system reported in this document is expanded uncertainty is 2.1% with a coverage factor $k=2$.

Goniophotometer Method

Photometric and Electrical Measurements

An EVERFINE Type C Model GO-R5000 Goniophotometer was used to measure the intensity at each angle of distribution for each sample. The photometric distance is 2.475m for near-field measurement or 30m for far-field measurement. Bandwidth of spectroradiometer is 380nm-780nm.

Ambient temperature was measured at the same height of the sample mounted on the Goniophotometer equipment. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Everfine Digital Power Meter.

Some graphics were created with Photometric Plus software.

The standard reference of the Goniophotometer system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Metrology P.R. China.

The uncertainty of goniophotometer system reported in this document is expanded uncertainty is 2.3% with a coverage factor $k=2$.

Color Characteristics Measurements

The color characteristics of SSL products include chromaticity coordinates, correlated color temperature, and color rendering index. These characteristics of SSL products may be spatially non-uniform, and thus, in order that they can be specified accurately, the color quantities shall be measured as values that are spatially average, weighted to intensity, over the angular range where light is intentionally emitted from the SSL product. The color characteristics measurements are using gonio-spectroradiometer.

Color Spatial Uniformity

The characteristics of SSL products may be spatially non-uniform, the chromaticity coordinate shall be measured at two vertical planes ($C=0^\circ/180^\circ$ and $C=90^\circ/270^\circ$) and at 10° or less intervals for vertical angle until the light output dropped to below 10% of the peak intensity. The averaged weighted chromaticity coordinate

was calculated from these points. The data was then analyzed to check for delta color differences of the u' , v' chromaticity coordinates. The spatial non-uniformity of chromaticity, $\Delta u'v'$, is determined as the maximum deviation (distance on the CIE (u' , v') diagram) among all measured points from the spatially averaged chromaticity coordinate.

The geometry for the chromaticity measurement using gonio-spectroradiometer is shown as following.



*** End of Report ***

This report is considered invalidated without the Special Seal for Inspection of the LTL. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of LTL, this test report shall not be copied except in full and published as advertisement.