

LM-79-08 TEST REPORT

for

GREEN CREATIVE LTD

756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

LED Lamp

Model: 9PLO/830/HYBM

Laboratory: Leading Testing Laboratories

NVLAP CODE: 200960-0

3rd Floor, Bld. 2, NO. 96 Longchuanwu Rd Qianjiang Economy Dev. Zone, YuhangDist,
Hangzhou, Zhejiang Province, China 311100

Tel: +86571 86376106

www.ledtestlab.com

Report No.: HZ19120026p

The laboratory that conducted the testing detailed in this report has been accredited for SSL by NVLAP.

Review by:



Engineer: April Zou
Dec. 30, 2019

Approved by:



Manager: Jim Zhang
Dec. 30, 2019

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TEST SUMMARY

Sample Tested: **9PLO/830/HYBM**

Luminous Efficacy (Lumens /Watt)	Total Luminous Flux (Lumens)	Power (Watts)	Power Factor
141.9	1248.7	8.80	0.9796
CCT (K)	CRI	Stabilization Time (Light & Power)	
3034	82.7	60	

Table 1: Executive Data Summary

Note: The above results are recorded/ derived from measurements made using an Integrating Sphere.

Test specifications:

Date of Receipt	: Dec. 19, 2019
Date of Test	: Dec. 27, 2019
Test item	: Total Luminous Flux, Luminous Distribution Intensity, Luminous Efficacy, Correlated Color Temperature, Color Rendering Index, Chromaticity Coordinate, Electrical parameters
Reference Standard	: IESNA LM-79-2008 Approved Method for the Electrical and Photometric Measurements of Solid-State Lighting Products ANSI/IES TM-30-18 IES Method for Evaluating Light Source Color Rendition

TABLE OF CONTENT

LM-79-08 TEST REPORT	1
TEST SUMMARY	2
SAMPLE PHOTO	4
TEST RESULTS	5
Sphere-Spectroradiometer Method.....	5
Goniophotometer Method	6
Spectral Power Distribution - Sphere Spectroradiometer Method	7
Chromaticity Diagram - Sphere Spectroradiometer Method.....	8
Nominal CCT Quadrangles – Sphere Spectroradiometer Method	9
Color Rendition Report – Sphere Spectroradiometer Method	10
Zonal Lumen Tabulation- Goniophotometer Method	11
Illuminance Plots- Goniophotometer Method	12
Luminous Intensity Distribution Plots- Goniophotometer Method.....	13
Luminous Intensity Data- Goniophotometer Method	14
EQUIPMENT LIST	16
TEST METHODS	16
Seasoning of SSL Product.....	16
Sphere-Spectroradiometer Method- Photometric and Electrical Measurements.....	16
Goniophotometer Method	17
Photometric and Electrical Measurements	17
Color Characteristics Measurements.....	17
Color Spatial Uniformity	17

SAMPLE PHOTO



Figure 1- Overview of the sample

Equipment Under Test(EUT)

Name	: LED Lamp
Model	: 9PLO/830/HYBM
Electrical Ratings	: 120-277V, 50/60Hz, 9W
Product Description	: 3000K
Manufacturer	: GREEN CREATIVE LTD
Address	: 756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

TEST RESULTS

Test ambient temperature was 26.0 °C.

Base orientation was light down. Test was conducted without a dimmer in the circuit.

The stabilization time of the sample was 60 minutes, and the total operating time including stabilization was 65 minutes.

Sphere-Spectroradiometer Method

Parameter	Result	
Test Voltage (V)	120.0	277.0
Voltage frequency (Hz)	60	60
Test Current (A)	0.075	0.037
Power Factor	0.9796	0.8964
Test Power (W)	8.80	9.03
THD A%	17.11	18.79
Luminous Efficacy (lm/W)	141.9	138.3
Total Luminous Flux (lm)	1248.7	1249.1
Color Rendering Index (CRI)	82.7	
R9	8.3	
Correlated Color Temperature (CCT)(K)	3034	
Chromaticity Chroma x	0.4337	
Chromaticity Chroma y	0.4018	
Chromaticity Chroma u	0.2495	
Chromaticity Chroma v	0.3467	
Duv	0.0005	
Chromaticity Chroma u'	0.2495	
Chromaticity Chroma v'	0.5200	

Special Color Rendering Indices	
R1	81.8
R2	93
R3	94.4
R4	79
R5	81.8
R6	91.4
R7	81.4
R8	58.5
R9	8.3
R10	83.5
R11	78
R12	70.4
R13	84.9
R14	97.8

Table 2: Test data per Sphere-Spectroradiometer Method

Note: According to CIE 1976 (u', v') diagram, $u' = u = 4x/(-2x+12y+3)$, $v' = 3v/2 = 9y/(-2x+12y+3)$.

Goniophotometer Method

Test ambient temperature was 24.8 °C.

The photometric distance is 2.47 m.

Luminous data was taken at 0.5 vertical intervals and 10 horizontal intervals.

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.075
Power Factor	0.9802
Power (W)	8.83
Luminous Efficacy (lm/W)	142.8
Total Luminous Flux (lm)	1260.6
Beam Angle (°)	335.7 (0°-180°) / 335.4 (90°-270°)
Center Beam Candle Power (cd)	9.07
Maximum Beam Candle Power (cd)	142.2 (At: C=60.0, Gamma=88.0)
Spacing Criteria	5.24 (0°-180°) / 5.28 (90°-270°)
Zonal Lumens in the 0 °-60 °Zone	19.13%
Zonal Lumens in the 60 °-90 °Zone	32.58%
Zonal Lumens in the 90 °-120 °Zone	31.74%
Zonal Lumens in the 120 °-180 °Zone	16.55%

Table 3: Test data per Goniophotometer Method

Spectral Power Distribution - Sphere Spectroradiometer Method





Chart 1: Spectral Power Distribution

Spectral Distribution over Visible Wavelength							
WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)
380	6.20E-05	485	5.90E-03	590	2.44E-02	695	4.51E-03
385	6.87E-05	490	6.21E-03	595	2.50E-02	700	3.87E-03
390	6.84E-05	495	6.83E-03	600	2.54E-02	705	3.32E-03
395	6.30E-05	500	7.76E-03	605	2.54E-02	710	2.84E-03
400	6.40E-05	505	8.84E-03	610	2.51E-02	715	2.45E-03
405	7.04E-05	510	9.92E-03	615	2.45E-02	720	2.11E-03
410	1.06E-04	515	1.09E-02	620	2.35E-02	725	1.80E-03
415	1.90E-04	520	1.16E-02	625	2.23E-02	730	1.54E-03
420	3.59E-04	525	1.23E-02	630	2.10E-02	735	1.31E-03
425	6.61E-04	530	1.29E-02	635	1.95E-02	740	1.12E-03
430	1.16E-03	535	1.35E-02	640	1.79E-02	745	9.54E-04
435	2.01E-03	540	1.40E-02	645	1.63E-02	750	8.19E-04
440	3.42E-03	545	1.47E-02	650	1.47E-02	755	7.00E-04
445	5.72E-03	550	1.54E-02	655	1.32E-02	760	6.00E-04
450	9.79E-03	555	1.63E-02	660	1.18E-02	765	5.10E-04
455	1.43E-02	560	1.73E-02	665	1.04E-02	770	4.41E-04
460	1.43E-02	565	1.84E-02	670	9.12E-03	775	3.77E-04
465	1.10E-02	570	1.97E-02	675	7.98E-03	780	3.22E-04
470	9.13E-03	575	2.09E-02	680	6.96E-03		
475	7.80E-03	580	2.23E-02	685	6.04E-03		
480	6.39E-03	585	2.34E-02	690	5.22E-03		

Table 4: Spectral Power Distribution Numerical Data per Sphere - Spectroradiometer Method

Chromaticity Diagram - Sphere Spectroradiometer Method



Tristimulus values(x, y): (0.4337, 0.4018)

Chart 2: Chromaticity Diagram per Sphere - Spectroradiometer Method

Note: The location on the diagram of the tristimulus coordinates are indicated by the blue diamond.

Nominal CCT Quadrangles – Sphere Spectroradiometer Method





Chart 3: Plot of Lamp x/y coordinates on CIE 1931 Chromaticity Diagram

Color Rendition Report – Sphere Spectroradiometer Method



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4337
 y 0.4018
 u' 0.2495
 v' 0.5200

Chart 4: Full Report Created with the IES TM-30 Calculator

Note: The values in this diagram might be a little different from the values in Table 2 due to rounding.

Zonal Lumen Tabulation- Goniophotometer Method

$\gamma(^{\circ})$	Lumens	% Total
0- 10	1.379	0.11%
10- 20	8.279	0.66%
20- 30	22.626	1.79%
30- 40	43.561	3.46%
40- 50	69.071	5.48%
50- 60	96.199	7.63%
60- 70	121.143	9.61%
70- 80	139.997	11.11%
80- 90	149.592	11.87%
90-100	148.377	11.77%
100-110	136.265	10.81%
110-120	115.483	9.16%
120-130	89.423	7.09%
130-140	62.097	4.93%
140-150	37.191	2.95%
150-160	16.543	1.31%
160-170	3.271	0.26%
170-180	0.059	0.00%
Total	1260.6	100%

$\gamma(^{\circ})$	Lumens	% Total
0- 60	241.115	19.13%
60- 90	410.732	32.58%
0-90	651.847	51.71%
90- 180	608.709	48.29%
0- 180	1260.6	100%

Table 5: Zonal Lumen

Illuminance Plots- Goniophotometer Method




Chart 5: Illuminance Plot (Footcandles)

Luminous Intensity Distribution Plots- Goniophotometer Method




Chart 6: Isocandela Plot




Chart 7: Polar Candela Distribution

Luminous Intensity Data- Goniophotometer Method

Table--1

UNIT: cd

C (DEG) y (DEG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07
5	11.8	11.6	11.5	11.4	11.3	11.2	11.1	11.1	11.1	11.1	11.2	11.3	11.5	11.6	11.7	11.9	11.9	12.1	12.2
10	18.3	18.2	18.1	18.1	18.0	17.9	17.8	17.6	17.4	17.3	17.6	18.0	18.2	18.5	18.7	18.8	18.8	18.7	19.0
15	26.8	26.9	27.1	27.2	27.1	27.0	26.8	26.5	25.9	25.8	26.4	26.9	27.2	27.5	27.7	27.8	27.7	27.3	27.6
20	36.1	36.7	37.1	37.4	37.4	37.3	36.9	36.5	35.7	35.2	36.2	36.9	37.3	37.7	37.8	37.8	37.4	36.8	36.9
25	45.9	46.8	47.6	48.0	48.1	48.1	47.7	46.9	45.8	45.1	46.4	47.4	47.8	48.2	48.3	48.2	47.6	46.6	46.5
30	55.7	57.2	58.2	58.8	58.9	58.9	58.4	57.6	56.2	55.2	56.8	58.0	58.5	58.9	58.9	58.7	57.9	56.5	56.3
35	65.7	67.6	68.8	69.6	69.7	69.7	69.2	68.3	66.7	65.3	67.3	68.5	69.0	69.3	69.3	68.9	68.2	66.6	66.0
40	75.6	77.8	79.1	80.0	80.1	80.3	79.9	78.8	76.9	75.2	77.6	78.8	79.3	79.6	79.5	79.2	78.2	76.4	75.6
45	85.4	87.9	89.3	90.3	90.5	90.6	90.2	89.2	87.1	85.0	87.6	88.8	89.2	89.4	89.3	89.1	88.0	86.0	85.0
50	94.7	97.6	99.2	100	100	100	100	99.1	96.8	94.7	97.2	98.6	98.8	98.9	98.8	98.5	97.5	95.3	94.1
55	104	107	108	109	109	110	109	108	106	104	106	108	108	108	107	107	106	104	103
60	112	115	117	117	117	118	118	117	115	112	115	116	116	115	115	115	114	112	110
65	119	122	124	125	124	125	125	124	122	120	122	123	122	122	122	122	121	119	117
70	125	129	130	131	130	131	131	131	129	126	129	129	128	128	128	128	127	125	123
75	130	133	135	135	135	136	136	136	134	131	134	134	133	132	132	132	132	129	128
80	133	137	138	139	138	139	140	139	137	134	137	138	136	135	135	135	135	133	131
85	135	139	140	140	140	141	142	142	139	136	139	139	138	137	137	137	137	134	132
90	135	139	140	141	141	141	142	142	140	137	140	140	138	137	137	137	137	135	132
95	134	138	139	140	139	140	141	141	139	136	139	139	137	136	136	136	136	133	131
100	131	135	136	137	137	138	138	138	136	133	136	136	135	133	133	133	133	130	128
105	127	130	132	133	132	133	134	134	132	129	131	132	130	129	129	129	128	126	124
110	121	124	126	127	127	128	128	128	126	123	126	126	125	124	123	123	123	120	118
115	114	117	119	120	120	121	121	121	119	116	118	119	118	117	116	116	115	113	111
120	106	109	111	112	113	113	113	113	111	108	110	111	110	110	109	109	107	105	103
125	97.0	100	102	104	103	104	104	103	102	98.9	101	102	102	101	100	100	98.6	96.4	94.4
130	87.2	90.4	92.2	93.5	94.0	94.4	94.3	93.3	91.8	89.3	91.7	92.3	92.3	91.7	91.3	90.4	89.1	86.8	85.0
135	77.3	80.0	82.1	83.2	83.8	84.2	83.9	83.1	81.2	79.2	81.3	82.0	82.0	81.7	81.2	80.5	79.1	77.1	75.3
140	67.1	69.6	71.1	72.4	73.0	73.3	73.2	72.3	70.6	68.8	70.5	71.6	71.8	71.4	71.0	70.1	68.7	66.9	65.2
145	56.7	58.8	60.2	61.5	61.9	62.2	62.2	61.4	60.0	58.4	59.8	60.7	61.0	60.9	60.3	59.3	58.4	56.5	55.3
150	46.4	48.0	49.0	48.6	49.8	51.0	50.9	50.4	49.2	47.9	49.1	49.7	50.1	50.0	49.4	48.2	47.1	46.1	44.6
155	34.4	35.4	36.4	37.0	37.1	38.0	39.5	39.4	38.6	37.7	38.4	38.8	38.8	38.2	37.5	36.7	35.7	34.9	33.7
160	22.9	23.9	24.7	25.1	25.4	25.1	25.8	26.9	27.7	27.2	27.3	27.2	26.6	25.9	25.7	24.7	23.8	22.1	21.0
165	10.7	11.7	12.7	13.5	14.1	11.9	8.59	10.1	15.6	15.6	15.3	14.8	14.3	14.0	13.3	12.2	11.2	9.40	9.05
170	2.00	2.88	3.56	4.16	4.22	3.06	3.34	4.53	5.18	5.23	4.91	4.42	3.69	3.35	1.43	0.49	0.89	1.78	1.06
175	0.18	0.19	0.21	0.20	0.24	0.26	0.25	0.25	0.25	0.26	0.27	0.28	0.26	0.23	0.22	0.21	0.21	0.18	0.21
180	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06

Table 6: Luminous Intensity Data

Table--2

UNIT: cd

C (DEG) y (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07		
5	12.5	12.7	12.9	13.0	13.1	13.1	13.1	13.0	12.9	12.9	12.9	12.8	12.7	12.6	12.4	12.2	11.9		
10	19.6	20.0	20.3	20.5	20.7	20.7	20.5	20.3	20.0	20.2	20.2	20.2	20.1	19.8	19.6	19.1	18.7		
15	28.4	29.1	29.6	29.9	30.1	30.0	29.7	29.2	28.8	29.1	29.4	29.5	29.4	29.1	28.7	28.1	27.4		
20	38.2	39.1	39.7	40.1	40.3	40.1	39.7	38.9	38.1	38.9	39.4	39.6	39.5	39.2	38.8	38.0	37.1		
25	48.2	49.4	50.1	50.5	50.8	50.5	49.9	48.9	47.8	49.0	49.7	50.0	50.0	49.8	49.2	48.4	47.1		
30	58.2	59.7	60.6	61.0	61.2	60.9	60.2	58.9	57.5	59.2	60.1	60.4	60.4	60.3	59.7	58.7	57.2		
35	68.4	69.9	70.9	71.3	71.7	71.3	70.4	68.9	67.3	69.2	70.4	70.7	70.9	70.6	70.2	69.0	67.3		
40	78.4	79.9	81.0	81.4	81.7	81.4	80.3	78.8	77.0	79.3	80.5	81.0	80.9	80.9	80.5	79.3	77.5		
45	88.0	89.8	90.7	91.2	91.5	91.1	90.2	88.4	86.4	88.9	90.2	90.6	90.7	90.8	90.3	89.2	87.4		
50	97.1	99.0	99.9	100	101	100	99.5	97.5	95.4	98.3	99.5	99.9	100	99.9	99.6	98.7	96.8		
55	106	108	108	109	109	109	108	106	104	107	108	109	108	108	108	108	106		
60	114	115	116	116	117	117	116	114	112	115	116	116	116	116	116	116	114		
65	121	122	123	123	123	123	123	121	118	121	123	123	123	123	123	123	121		
70	127	128	128	128	129	129	129	126	124	127	128	128	128	128	129	129	127		
75	131	132	132	132	133	133	133	131	129	132	133	132	132	132	133	133	132		
80	134	135	135	135	135	136	136	134	131	135	136	135	135	135	136	136	135		
85	136	137	136	136	137	137	137	135	133	136	137	137	136	137	138	138	137		
90	136	137	136	136	137	137	137	135	133	136	137	137	136	137	138	138	137		
95	134	135	135	135	135	136	136	134	132	135	136	135	135	136	137	137	136		
100	131	132	132	132	132	133	132	131	128	132	133	132	132	133	134	134	133		
105	127	128	128	127	128	128	128	126	124	127	128	128	128	129	130	130	128		
110	121	122	122	122	122	122	122	120	118	121	123	122	122	123	124	124	122		
115	114	115	115	115	116	116	115	113	111	114	116	116	116	116	117	117	116		
120	106	107	107	107	108	107	107	105	103	106	108	108	108	109	109	109	107		
125	97.1	98.2	98.7	98.7	99.0	98.6	97.9	96.0	94.4	97.4	98.8	99.1	99.5	100	100	99.9	98.4		
130	87.3	88.8	89.4	89.4	89.6	89.1	88.2	86.3	85.1	87.7	89.1	89.6	90.1	90.7	90.8	90.1	88.6		
135	77.5	78.7	79.3	79.7	79.6	79.1	78.1	76.4	75.2	77.7	79.1	79.7	80.3	80.7	80.6	79.9	78.5		
140	67.3	68.4	69.0	69.1	69.2	68.6	67.6	66.1	65.2	67.3	68.8	69.4	69.9	70.3	70.1	69.4	68.1		
145	56.9	57.8	58.3	58.4	58.5	57.9	57.0	55.8	55.0	56.8	58.0	58.7	59.2	59.3	59.3	58.7	57.5		
150	45.8	46.8	47.0	46.5	46.1	45.6	45.1	44.4	44.0	45.2	46.0	46.6	47.3	47.8	48.1	47.8	47.0		
155	34.0	33.8	33.3	32.3	31.6	31.0	30.3	29.6	29.3	30.3	31.0	32.0	33.5	34.8	35.8	36.0	35.5		
160	20.5	19.8	19.1	18.1	17.4	16.8	16.5	16.1	15.9	16.5	16.9	17.6	18.9	20.0	21.1	22.1	22.7		
165	8.72	7.71	7.02	6.02	5.24	4.84	4.71	4.57	4.49	4.69	5.00	5.21	6.09	7.15	8.16	9.16	9.94		
170	0.99	0.44	0.28	0.22	0.18	0.16	0.16	0.16	0.16	0.16	0.16	0.18	0.20	0.24	0.38	0.63	1.20		
175	0.21	0.20	0.19	0.18	0.17	0.16	0.14	0.14	0.14	0.12	0.12	0.12	0.12	0.13	0.14	0.15	0.15		
180	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06		

Table 7: Luminous Intensity Data

EQUIPMENT LIST

Test Equipment	Model	Equipment No.	Calibration Date	Calibration Due date
Goniophotometer system	GO-R5000	HZTE011-01	Aug. 02, 2019	Aug. 01, 2020
Digital Power Meter	PF2010A	HZTE028-01	Aug. 02, 2019	Aug. 01, 2020
AC Power Supply	DPS1060	HZTE001-06	Aug. 02, 2019	Aug. 01, 2020
DC Power Supply	WY12010	HZTE004-03	Aug. 02, 2019	Aug. 01, 2020
Temperature recorder	JM624U	HZTE018-08	Aug. 02, 2019	Aug. 01, 2020
Temperature and humidity recorder	JR900	HZTE018-01	Aug. 02, 2019	Aug. 01, 2020
Standard source	D908	HZTE012-01	Aug. 02, 2019	Aug. 01, 2020
Integrate Sphere system	3M	HZTE015-04	Aug. 02, 2019	Aug. 01, 2020
Digital Power Meter	WT210	HZTE008-01	Aug. 02, 2019	Aug. 01, 2020
AC Power Supply	PCR 500L	HZTE001-07	Aug. 02, 2019	Aug. 01, 2020
DC Power Supply	IT6154	HZTE004-04	Aug. 02, 2019	Aug. 01, 2020
Standard source	SCL-1400	HZTE012-02	Aug. 02, 2019	Aug. 01, 2020
Temperature and humidity recorder	JR900	HZTE018-02	Aug. 02, 2019	Aug. 01, 2020
Temperature Meter	TES1310	HZTE017-01	Aug. 02, 2019	Aug. 01, 2020

Table 8: Test Equipment List

TEST METHODS

Seasoning of SSL Product

For the purpose of rating new SSL products, SSL products shall be tested with no seasoning. Therefore, no seasoning was performed.

Sphere-Spectroradiometer Method- Photometric and Electrical Measurements

A Labsphere Model CDS 2100 Spectroradiometer and Two Meter Sphere was used to measure correlated color temperature, chromaticity coordinates, and the color rendering index for each SSL unit. The coating reflectance of each sphere is 98%. The measure geometry is 4π . Self-absorption correction is conducted in testing. Bandwidth of spectroradiometer is 350nm-1050nm.

Ambient temperature was measured at a position inside the sphere. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

The standard reference of the integrated sphere system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Standards and Technology.

The uncertainty of integrating sphere system reported in this document is expanded uncertainty is 2.1% with a coverage factor $k=2$.

Goniophotometer Method

Photometric and Electrical Measurements

An EVERFINE Type C Model GO-R5000 Goniophotometer was used to measure the intensity at each angle of distribution for each sample. The photometric distance is 2.475m for near-field measurement or 30m for far-field measurement. Bandwidth of spectroradiometer is 380nm-780nm.

Ambient temperature was measured at the same height of the sample mounted on the Goniophotometer equipment. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Everfine Digital Power Meter.

Some graphics were created with Photometric Plus software.

The standard reference of the Goniophotometer system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Metrology P.R. China.

The uncertainty of goniophotometer system reported in this document is expanded uncertainty is 2.3% with a coverage factor $k=2$.

Color Characteristics Measurements


The color characteristics of SSL products include chromaticity coordinates, correlated color temperature, and color rendering index. These characteristics of SSL products may be spatially non-uniform, and thus, in order that they can be specified accurately, the color quantities shall be measured as values that are spatially average, weighted to intensity, over the angular range where light is intentionally emitted from the SSL product. The color characteristics measurements are using gonio-spectroradiometer.

Color Spatial Uniformity

The characteristics of SSL products may be spatially non-uniform, the chromaticity coordinate shall be measured at two vertical planes ($C=0^\circ/180^\circ$ and $C=90^\circ/270^\circ$) and at 10° or less intervals for vertical angle until the light output dropped to below 10% of the peak intensity. The averaged weighted chromaticity coordinate

was calculated from these points. The data was then analyzed to check for delta color differences of the u' , v' chromaticity coordinates. The spatial non-uniformity of chromaticity, $\Delta u'v'$, is determined as the maximum deviation (distance on the CIE (u' , v') diagram) among all measured points from the spatially averaged chromaticity coordinate.

The geometry for the chromaticity measurement using gonio-spectroradiometer is shown as following.



*** End of Report ***

This report is considered invalidated without the Special Seal for Inspection of the LTL. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of LTL, this test report shall not be copied except in full and published as advertisement.