

## LM-79-19 TEST REPORT

for

### GREEN CREATIVE LTD

Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, KL,  
Hong Kong

### LED Lamp

**Model: 6.8PLO/830/HYB/PF**

### Laboratory: Leading Testing Laboratories

**NVLAP CODE: 200960-0**

3rd Floor, Bld. 2, NO. 96 Longchuanwu Rd Qianjiang Economy Dev. Zone, YuhangDist,  
Hangzhou, Zhejiang Province, China 311100

Tel: +86571 86376106

[www.ledtestlab.com](http://www.ledtestlab.com)

Report No.: HZ22080002b

The laboratory that conducted the testing detailed in this report has been accredited for SSL by NVLAP.

Review by:



Engineer: April Zou  
Aug. 09, 2022

Approved by:



Manager: Jim Zhang  
Aug. 09, 2022

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

## TEST SUMMARY

Sample Tested: 6.8PLO/830/HYB/PF

Luminous Efficacy (Lumens /Watt)	Total Luminous Flux (Lumens)	Power (Watts)	Power Factor
112.8	766.8	6.80	0.9777
CCT (K)	CRI	Stabilization Time (Light & Power)	
3097	83.5	50	

Table 1: Executive Data Summary

Note: The above results are recorded/ derived from measurements made using an Integrating Sphere.

### Test specifications:

<b>Date of Receipt</b>	: Aug. 01, 2022
<b>Date of Test</b>	: Aug. 04, 2022
<b>Test item</b>	: Total Luminous Flux, Luminous Distribution Intensity, Luminous Efficacy, Correlated Color Temperature, Color Rendering Index, Chromaticity Coordinate, Electrical parameters
<b>Reference Standard</b>	: IESNA LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products ANSI/IES TM-30-18 IES Method for Evaluating Light Source Color Rendition

## TABLE OF CONTENT

LM-79-19 TEST REPORT.....	1
TEST SUMMARY .....	2
SAMPLE PHOTO .....	4
TEST RESULTS .....	5
Sphere-Spectroradiometer Method.....	5
Goniophotometer Method .....	6
Spectral Power Distribution - Sphere Spectroradiometer Method .....	7
Chromaticity Diagram - Sphere Spectroradiometer Method.....	8
Nominal CCT Quadrangles – Sphere Spectroradiometer Method .....	9
Color Rendition Report – Sphere Spectroradiometer Method .....	10
Zonal Lumen Tabulation- Goniophotometer Method .....	11
Illuminance Plots- Goniophotometer Method .....	12
Luminous Intensity Distribution Plots- Goniophotometer Method.....	13
Luminous Intensity Data- Goniophotometer Method .....	14
EQUIPMENT LIST .....	16
TEST METHODS .....	16
Seasoning of SSL Product.....	16
Sphere-Spectroradiometer Method- Photometric and Electrical Measurements.....	16
Goniophotometer Method .....	17
Photometric and Electrical Measurements .....	17
Color Characteristics Measurements.....	17

## SAMPLE PHOTO



Figure 1- Overview of the sample

### Equipment Under Test(EUT)

<b>Name</b>	: LED Lamp
<b>Model</b>	: 6.8PLO/830/HYB/PF
<b>Electrical Ratings</b>	: 120-277V, 50/60Hz, 6.8W
<b>Product Description</b>	: 3000K
<b>Manufacturer</b>	: GREEN CREATIVE LTD
<b>Address</b>	: Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, KL, Hong Kong

## TEST RESULTS

Test ambient temperature was 26.0 °C.

Base orientation was base up. Test was conducted without a dimmer in the circuit.

The stabilization time of the sample was 50 minutes, and the total operating time including stabilization was 55 minutes.

### Sphere-Spectroradiometer Method

Parameter	Result	
Test Voltage (V)	120.0	277.0
Voltage frequency (Hz)	60	60
Test Current (A)	0.058	0.029
Power Factor	0.9777	0.8929
Test Power (W)	6.80	7.08
THD A%	13.26	21.49
Luminous Efficacy (lm/W)	112.8	111.4
Total Luminous Flux (lm)	766.8	788.7
Color Rendering Index (CRI)	83.5	
R9	11.7	
Correlated Color Temperature (CCT)(K)	3097	
Chromaticity Chroma x	0.4304	
Chromaticity Chroma y	0.4024	
Chromaticity Chroma u	0.2471	
Chromaticity Chroma v	0.3465	
Duv	0.0003	
Chromaticity Chroma u'	0.2471	
Chromaticity Chroma v'	0.5197	

Special Color Rendering Indices	
R1	82.1
R2	91.8
R3	96.3
R4	81.2
R5	82.2
R6	89.9
R7	83.6
R8	61.2
R9	11.7
R10	81
R11	80.4
R12	71.6
R13	84.5
R14	98.7

Table 2: Test data per Sphere-Spectroradiometer Method

Note: According to CIE 1976 (u',v') diagram,  $u' = u = 4x/(-2x+12y+3)$ ,  $v' = 3v/2 = 9y/(-2x+12y+3)$ .

### Goniophotometer Method

Test ambient temperature was 24.8 °C.

The photometric distance is 2.47 m.

Luminous data was taken at 0.5 vertical intervals and 10 horizontal intervals.

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.058
Power Factor	0.9780
Power (W)	6.81
Luminous Efficacy (lm/W)	112.8
Total Luminous Flux (lm)	767.9
Beam Angle ( ° )	332.9 (0°-180°) / 332.2 (90°-270°)
Center Beam Candle Power (cd)	8.74
Maximum Beam Candle Power (cd)	84.08 (At: C=240.0, Gamma=86.0)
Spacing Criteria	4.46 (0°-180°) / 4.43 (90°-270°)
Zonal Lumens in the 0 °-60 °Zone	19.87%
Zonal Lumens in the 60 °-90 °Zone	32.48%
Zonal Lumens in the 90 °-120 °Zone	31.31%
Zonal Lumens in the 120 °-180 °Zone	16.34%

Table 3: Test data per Goniophotometer Method

## Spectral Power Distribution - Sphere Spectroradiometer Method





Chart 1: Spectral Power Distribution

Spectral Distribution over Visible Wavelength							
WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)
380	4.88E-05	485	3.53E-03	590	1.46E-02	695	3.03E-03
385	3.81E-05	490	3.91E-03	595	1.50E-02	700	2.62E-03
390	4.48E-05	495	4.47E-03	600	1.52E-02	705	2.27E-03
395	4.19E-05	500	5.16E-03	605	1.52E-02	710	1.94E-03
400	5.19E-05	505	5.86E-03	610	1.50E-02	715	1.68E-03
405	8.22E-05	510	6.48E-03	615	1.46E-02	720	1.45E-03
410	1.37E-04	515	7.02E-03	620	1.41E-02	725	1.26E-03
415	2.47E-04	520	7.42E-03	625	1.35E-02	730	1.08E-03
420	4.51E-04	525	7.77E-03	630	1.27E-02	735	9.23E-04
425	7.85E-04	530	8.15E-03	635	1.19E-02	740	7.94E-04
430	1.28E-03	535	8.43E-03	640	1.10E-02	745	6.80E-04
435	2.07E-03	540	8.84E-03	645	1.01E-02	750	5.85E-04
440	3.25E-03	545	9.24E-03	650	9.20E-03	755	4.93E-04
445	5.05E-03	550	9.69E-03	655	8.29E-03	760	4.30E-04
450	7.36E-03	555	1.02E-02	660	7.44E-03	765	3.67E-04
455	8.23E-03	560	1.07E-02	665	6.62E-03	770	3.17E-04
460	6.83E-03	565	1.14E-02	670	5.87E-03	775	2.69E-04
465	5.41E-03	570	1.21E-02	675	5.17E-03	780	2.29E-04
470	4.61E-03	575	1.28E-02	680	4.56E-03		
475	3.85E-03	580	1.35E-02	685	3.99E-03		
480	3.45E-03	585	1.41E-02	690	3.47E-03		

Table 4: Spectral Power Distribution Numerical Data per Sphere - Spectroradiometer Method

## Chromaticity Diagram - Sphere Spectroradiometer Method



Tristimulus values(x, y): (0.4304, 0.4024)

Chart 2: Chromaticity Diagram per Sphere - Spectroradiometer Method

Note: The location on the diagram of the tristimulus coordinates are indicated by the blue diamond.



# Nominal CCT Quadrangles – Sphere Spectroradiometer Method




Chart 3: Plot of Lamp x/y coordinates on CIE 1931 Chromaticity Diagram

# Color Rendition Report – Sphere Spectroradiometer Method


## ANSI/IES TM-30-18 Color Rendition Report

Source: LED

Manufacturer: GREEN CREATIVE LTD

Date: 2022/08/04

Model: 6.8PLO/830/HYB/PF



**Notes:** This is a recommended method for displaying ANSI/IES TM-30-18 information.

$x$  0.4304  
 $y$  0.4024  
 $u'$  0.2471  
 $v'$  0.5197

CIE 13.3-1995  
(CRI)  
 $R_a$  84  
 $R_9$  12

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

Chart 4: Full Report Created with the IES TM-30 Calculator

Note: The values in this diagram might be a little different from the values in Table 2 due to rounding.

### Zonal Lumen Tabulation- Goniophotometer Method

$\gamma(^{\circ})$	Lumens	% Total
0- 10	1.142	0.15%
10- 20	5.901	0.77%
20- 30	15.047	1.96%
30- 40	27.9	3.63%
40- 50	43.211	5.63%
50- 60	59.397	7.73%
60- 70	74.128	9.65%
70- 80	85.017	11.07%
80- 90	90.306	11.76%
90-100	89.246	11.62%
100-110	81.85	10.66%
110-120	69.311	9.03%
120-130	53.723	7.00%
130-140	37.358	4.86%
140-150	22.332	2.91%
150-160	10.092	1.31%
160-170	1.954	0.25%
170-180	0.023	0.00%
Total	767.9	100%

$\gamma(^{\circ})$	Lumens	% Total
0- 60	152.598	19.87%
60- 90	249.451	32.48%
0-90	402.049	52.35%
90- 180	365.889	47.65%
0- 180	767.9	100%

Table 5: Zonal Lumen

## Illuminance Plots- Goniophotometer Method




Chart 5: Illuminance Plot (Footcandles)

## Luminous Intensity Distribution Plots- Goniophotometer Method




Chart 6: Isocandela Plot




Chart 7: Polar Candela Distribution

## Luminous Intensity Data- Goniophotometer Method

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74
5	9.43	9.52	9.64	9.81	9.97	10.1	10.3	10.5	10.7	10.9	11.1	11.3	11.5	11.7	11.7	11.7	11.7	11.7	11.6
10	12.9	13.1	13.3	13.6	13.9	14.2	14.4	14.6	14.8	15.2	15.6	16.0	16.2	16.5	16.6	16.6	16.5	16.4	16.2
15	17.8	18.2	18.5	18.8	19.2	19.5	19.7	19.9	20.0	20.6	21.2	21.6	21.9	22.2	22.3	22.4	22.3	22.0	21.6
20	23.4	23.9	24.4	24.8	25.1	25.5	25.7	25.8	25.8	26.4	27.1	27.7	28.1	28.4	28.5	28.4	28.3	27.9	27.5
25	29.3	29.9	30.4	30.8	31.3	31.6	31.7	31.8	31.7	32.3	33.2	33.9	34.3	34.6	34.8	34.7	34.4	34.0	33.4
30	35.2	36.0	36.5	37.1	37.5	37.9	38.0	37.9	37.6	38.3	39.3	40.0	40.4	40.8	41.0	40.8	40.6	40.0	39.3
35	41.0	41.9	42.5	43.1	43.5	43.9	44.0	43.8	43.5	44.0	45.2	46.0	46.4	46.8	47.0	46.9	46.4	45.8	45.0
40	46.6	47.8	48.5	49.0	49.3	49.8	49.9	49.7	49.2	49.6	50.9	51.8	52.3	52.6	52.8	52.6	52.2	51.3	50.5
45	52.1	53.4	54.2	54.7	55.2	55.5	55.6	55.3	54.6	55.1	56.6	57.5	57.8	58.3	58.5	58.2	57.8	56.9	55.9
50	57.4	58.9	59.7	60.2	60.7	61.0	61.0	60.8	59.9	60.3	61.9	62.8	63.2	63.6	63.7	63.4	63.0	62.0	61.1
55	62.6	64.1	64.9	65.6	65.8	66.3	66.3	65.9	65.0	65.0	66.8	67.8	68.2	68.6	68.7	68.3	68.0	66.9	65.9
60	67.3	68.9	69.7	70.0	70.3	70.8	70.8	70.5	69.4	69.5	71.4	72.2	72.6	72.8	72.9	72.8	72.4	71.2	70.1
65	71.5	73.1	73.8	74.2	74.5	74.8	74.9	74.5	73.4	73.2	75.2	75.9	76.2	76.5	76.7	76.5	76.1	74.9	73.8
70	74.8	76.5	77.3	77.8	77.9	78.2	78.2	77.7	76.7	76.3	78.2	79.2	79.4	79.4	79.6	79.4	79.2	77.9	76.7
75	77.6	79.2	80.0	80.2	80.5	80.9	80.8	80.4	79.2	78.8	80.7	81.4	81.6	81.7	81.8	81.6	81.4	80.1	79.0
80	79.6	81.4	82.0	82.1	82.3	82.5	82.5	82.1	80.9	80.4	82.3	83.0	83.1	83.1	83.1	83.0	82.8	81.4	80.4
85	80.4	82.4	82.9	83.1	83.2	83.4	83.4	82.9	81.8	80.9	83.0	83.7	83.6	83.6	83.6	83.5	83.2	81.9	80.9
90	80.6	82.5	83.1	83.2	83.3	83.5	83.3	83.0	81.8	80.8	82.9	83.5	83.3	83.3	83.4	83.1	82.9	81.6	80.6
95	80.0	81.9	82.5	82.6	82.7	82.7	82.5	82.1	80.8	79.8	81.8	82.3	82.3	82.1	82.2	82.0	81.7	80.5	79.5
100	78.6	80.4	80.8	81.1	80.9	81.1	81.0	80.4	79.1	78.1	79.8	80.3	80.2	80.2	80.2	79.8	79.6	78.2	77.3
105	76.3	77.9	78.4	78.5	78.6	78.5	78.4	77.7	76.5	75.2	77.0	77.6	77.5	77.3	77.3	77.0	76.6	75.4	74.6
110	73.0	74.6	75.1	75.3	75.3	75.3	74.9	74.3	73.0	71.8	73.4	74.0	73.8	73.7	73.6	73.3	72.9	71.7	71.0
115	69.1	70.6	71.1	71.3	71.3	71.3	71.0	70.1	68.8	67.5	69.2	69.6	69.5	69.5	69.3	69.0	68.5	67.3	66.8
120	64.6	66.0	66.6	66.8	66.6	66.5	66.1	65.4	64.1	62.9	64.3	64.7	64.7	64.6	64.5	64.1	63.7	62.4	61.9
125	59.6	60.7	61.4	61.6	61.5	61.5	61.1	60.3	59.0	57.7	58.8	59.5	59.4	59.3	59.1	58.7	58.1	57.1	56.7
130	54.2	55.2	55.8	56.1	56.0	55.8	55.5	54.7	53.5	52.3	53.2	53.7	53.6	53.6	53.3	52.9	52.3	51.4	51.0
135	48.4	49.3	50.0	50.2	50.1	49.9	49.5	48.7	47.6	46.4	47.2	47.6	47.6	47.5	47.3	46.8	46.3	45.4	45.1
140	42.5	43.3	43.8	44.1	43.9	43.8	43.4	42.5	41.5	40.4	40.9	41.3	41.3	41.2	41.0	40.5	40.0	39.2	39.0
145	36.4	37.0	37.5	37.7	37.6	37.4	36.9	36.1	35.2	34.3	34.5	34.8	34.8	34.8	34.5	34.0	33.5	32.8	32.8
150	30.2	30.6	31.0	31.1	31.0	30.8	30.3	29.6	28.8	28.0	28.1	28.1	28.1	28.0	27.7	27.3	26.9	26.4	26.4
155	23.2	23.5	23.3	23.0	23.2	22.9	23.0	22.8	22.3	21.8	21.5	21.5	21.4	21.1	20.9	20.6	20.3	19.9	20.0
160	16.0	15.7	14.2	12.3	10.3	8.66	9.66	12.2	14.4	14.3	14.0	13.7	13.4	13.3	13.6	13.7	13.7	13.6	13.6
165	6.88	5.98	4.19	2.67	1.71	0.58	0.38	0.79	2.71	3.63	3.67	3.18	3.41	3.97	4.53	5.06	5.70	5.98	6.67
170	0.51	0.45	0.41	0.35	0.29	0.24	0.21	0.17	0.14	0.14	0.15	0.16	0.16	0.19	0.19	0.17	0.15	0.14	0.15
175	0.24	0.21	0.19	0.19	0.18	0.16	0.15	0.14	0.14	0.13	0.13	0.13	0.12	0.11	0.11	0.11	0.11	0.12	0.12
180	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04

Table 6: Luminous Intensity Data

Table--2		UNIT: cd																	
C (DEG) γ (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74	8.74		
5	11.5	11.4	11.3	11.2	11.0	10.9	10.6	10.4	10.2	9.98	9.80	9.63	9.51	9.41	9.34	9.29	9.33		
10	16.1	16.1	16.0	15.8	15.5	15.2	14.8	14.5	14.1	13.7	13.5	13.3	13.2	13.1	12.9	12.8	12.7		
15	21.8	21.8	21.7	21.4	21.2	20.8	20.3	19.7	19.2	18.9	18.7	18.5	18.4	18.2	18.0	17.9	17.7		
20	27.7	27.8	27.7	27.5	27.2	26.8	26.3	25.5	24.8	24.7	24.6	24.4	24.2	24.1	23.8	23.6	23.3		
25	33.8	34.0	34.0	33.7	33.5	33.0	32.3	31.5	30.6	30.7	30.8	30.6	30.4	30.2	29.9	29.6	29.2		
30	39.9	40.2	40.3	40.0	39.8	39.2	38.5	37.6	36.5	36.8	36.9	36.8	36.6	36.4	36.1	35.7	35.2		
35	45.8	46.1	46.2	46.1	45.9	45.3	44.4	43.4	42.2	42.7	43.0	42.9	42.7	42.5	42.1	41.7	41.1		
40	51.6	52.1	52.2	51.9	51.8	51.1	50.4	49.1	47.8	48.6	48.9	48.8	48.8	48.5	48.1	47.6	46.8		
45	57.2	57.8	57.9	57.6	57.5	56.9	56.0	54.7	53.3	54.3	54.7	54.7	54.6	54.3	53.9	53.4	52.4		
50	62.4	63.0	63.2	63.1	62.9	62.4	61.6	60.1	58.7	59.9	60.3	60.4	60.3	59.9	59.6	59.0	57.9		
55	67.4	68.0	68.2	68.0	68.0	67.4	66.6	65.3	63.9	65.1	65.7	65.7	65.6	65.3	65.0	64.3	63.1		
60	71.8	72.5	72.6	72.4	72.4	72.1	71.3	69.8	68.6	69.9	70.6	70.6	70.6	70.2	69.8	69.1	68.0		
65	75.6	76.2	76.4	76.3	76.3	76.2	75.4	73.8	72.6	74.2	74.6	74.7	74.6	74.4	74.0	73.5	72.1		
70	78.8	79.3	79.7	79.4	79.6	79.2	78.7	77.2	75.9	77.6	78.1	78.0	78.0	77.9	77.5	76.9	75.7		
75	81.0	81.6	81.9	81.8	81.9	81.8	81.2	79.6	78.4	80.2	80.7	80.7	80.7	80.6	80.2	79.7	78.3		
80	82.4	83.1	83.2	83.2	83.5	83.3	82.8	81.3	80.2	81.9	82.6	82.7	82.6	82.5	82.1	81.6	80.3		
85	83.0	83.5	83.7	83.8	84.0	84.0	83.6	82.0	81.1	82.9	83.6	83.6	83.6	83.6	83.2	82.8	81.4		
90	82.7	83.3	83.5	83.4	83.7	83.8	83.4	81.9	81.1	83.0	83.4	83.7	83.8	83.6	83.4	83.0	81.6		
95	81.4	82.1	82.4	82.5	82.8	82.9	82.4	81.0	80.4	82.2	82.8	82.9	83.1	83.1	82.8	82.4	81.1		
100	79.4	80.0	80.3	80.4	80.9	80.8	80.5	79.2	78.7	80.5	81.1	81.3	81.5	81.5	81.3	80.8	79.5		
105	76.5	77.2	77.5	77.6	78.1	78.1	77.7	76.5	76.1	78.0	78.6	78.8	79.0	79.0	78.9	78.5	77.2		
110	72.8	73.5	73.8	74.1	74.4	74.5	74.1	72.9	72.7	74.5	75.2	75.4	75.7	75.8	75.7	75.2	74.0		
115	68.5	69.1	69.5	69.8	70.2	70.1	69.8	68.7	68.7	70.4	71.2	71.6	71.8	71.8	71.7	71.3	70.0		
120	63.4	64.3	64.7	64.9	65.3	65.3	65.0	63.9	64.0	65.6	66.4	66.8	67.1	67.3	67.0	66.7	65.6		
125	58.1	58.8	59.3	59.5	59.9	59.9	59.3	58.3	59.0	60.4	61.3	61.6	62.0	62.1	61.9	61.5	60.3		
130	52.2	53.0	53.6	53.7	54.2	54.3	52.3	52.1	53.4	54.8	55.7	56.0	56.4	56.6	56.4	55.8	54.9		
135	46.2	46.9	47.4	47.7	48.1	48.1	44.5	45.4	47.6	48.8	49.6	50.1	50.4	50.6	50.4	49.9	49.1		
140	39.9	40.6	41.1	41.5	41.8	41.9	36.8	38.2	41.6	42.6	43.4	43.9	44.3	44.4	44.2	43.8	43.1		
145	33.4	34.1	34.6	35.0	35.3	34.1	29.2	29.4	35.2	36.1	37.0	37.5	37.9	38.1	37.8	37.4	36.9		
150	26.8	27.4	27.9	28.2	28.4	24.6	21.0	19.8	27.6	29.5	30.3	30.8	31.2	31.4	31.3	31.0	30.6		
155	20.3	20.7	21.0	21.4	21.7	15.9	12.6	11.0	19.0	22.2	23.7	24.1	24.4	24.7	24.7	24.5	23.5		
160	13.8	14.0	14.3	14.6	14.8	10.4	8.05	6.54	11.7	14.6	16.8	17.3	17.7	17.8	18.0	18.1	16.7		
165	6.89	6.88	7.06	7.39	7.46	6.33	4.70	5.81	7.23	7.78	9.11	9.09	8.95	9.19	9.41	9.56	8.64		
170	0.18	0.35	0.56	0.80	0.95	0.97	0.76	1.49	1.45	1.34	1.67	1.58	1.06	0.98	1.10	1.08	0.94		
175	0.12	0.13	0.14	0.14	0.15	0.15	0.16	0.17	0.19	0.20	0.22	0.23	0.24	0.25	0.25	0.25	0.25		
180	0.04	0.04	0.04	0.04	0.04	0.04	0.05	0.05	0.05	0.05	0.04	0.04	0.04	0.04	0.04	0.04	0.04		

Table 7: Luminous Intensity Data



## EQUIPMENT LIST

Test Equipment	Model	Equipment No.	Calibration Date	Calibration Due date
Goniophotometer system	GO-R5000	HZTE011-01	Aug. 05, 2021	Aug. 04, 2022
Digital Power Meter	PF2010A	HZTE028-01	Aug. 05, 2021	Aug. 04, 2022
AC Power Supply	DPS1060	HZTE001-06	Aug. 05, 2021	Aug. 04, 2022
DC Power Supply	WY12010	HZTE004-03	Aug. 05, 2021	Aug. 04, 2022
Temperature recorder	JM624U	HZTE018-08	Aug. 05, 2021	Aug. 04, 2022
Temperature and humidity recorder	JR900	HZTE018-01	Aug. 05, 2021	Aug. 04, 2022
Standard source	D908	HZTE012-01	Aug. 05, 2021	Aug. 04, 2022
Integrate Sphere system	3M	HZTE015-04	Aug. 05, 2021	Aug. 04, 2022
Digital Power Meter	WT210	HZTE008-01	Aug. 05, 2021	Aug. 04, 2022
AC Power Supply	PCR 500L	HZTE001-07	Aug. 05, 2021	Aug. 04, 2022
DC Power Supply	IT6154	HZTE004-04	Aug. 05, 2021	Aug. 04, 2022
Standard source	SCL-1400	HZTE012-02	Aug. 05, 2021	Aug. 04, 2022
Temperature and humidity recorder	JR900	HZTE018-02	Aug. 05, 2021	Aug. 04, 2022
Temperature Meter	TES1310	HZTE017-01	Aug. 05, 2021	Aug. 04, 2022

Table 7: Test Equipment List

## TEST METHODS

### Seasoning of SSL Product

For the purpose of rating new SSL products, SSL products shall be tested with no seasoning. Therefore, no seasoning was performed.

### Sphere-Spectroradiometer Method- Photometric and Electrical Measurements

A Labsphere Model CDS 2100 Spectroradiometer and 3 Meter Sphere was used to measure correlated color temperature, chromaticity coordinates, and the color rendering index for each SSL unit. The coating reflectance of each sphere is 98%. The measure geometry is  $4\pi$ . Self-absorption correction is conducted in testing. Bandwidth of spectroradiometer is 350nm-1050nm.

Ambient temperature was measured at a position inside the sphere. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 20 min, taken 10 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

The standard reference of the integrated sphere system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Standards and Technology.



The uncertainty of integrating sphere system reported in this document is expanded uncertainty is 2.1% with a coverage factor  $k=2$ .

## **Goniophotometer Method**

### **Photometric and Electrical Measurements**

An EVERFINE Type C Model GO-R5000 Goniophotometer was used to measure the intensity at each angle of distribution for each sample. The photometric distance is 2.475m for near-field measurement or 30m for far-field measurement. Bandwidth of spectroradiometer is 380nm-780nm.

Ambient temperature was measured at the same height of the sample mounted on the Goniophotometer equipment. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 20 min, taken 10 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Everfine Digital Power Meter.

Some graphics were created with Photometric Plus software.

The standard reference of the Goniophotometer system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Metrology P.R. China.

The uncertainty of goniophotometer system reported in this document is expanded uncertainty is 2.3% with a coverage factor  $k=2$ .

### **Color Characteristics Measurements**

The color characteristics of SSL products include chromaticity coordinates, correlated color temperature, and color rendering index. These characteristics of SSL products may be spatially non-uniform, and thus, in order that they can be specified accurately, the color quantities shall be measured as values that are spatially average, weighted to intensity, over the angular range where light is intentionally emitted from the SSL product. The color characteristics measurements are using gonio-spectroradiometer.

\*\*\* End of Report \*\*\*

This report is considered invalidated without the Special Seal for Inspection of the LTL. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of LTL, this test report shall not be copied except in full and published as advertisement.