




















SURFACE DOWNLIGHT SELECTION GUIDE

GREEN CREATIVE offers an extensive selection of surface downlighting. Select from the classic disk design, perfect for multifamily and residential applications, to the most advanced CLICK with sensor for intermittently occupied spaces, or the slimmer trim designed 3N1, which fits any job, with your choice of 120V or 0-10V dimming, optional spring J-box adapter and decorative trims. GREEN CREATIVE offers the surface mount downlight that fits your needs!



SELECTION GUIDE

				
		CLK	CLKSEN	3N1
Size		6"	6"	5.5"/7"/9"/12"
Application	Retail			
	Residential			
	Hospitality			
	Closets			
	Hallways			
Specifications	Power	11W / 15W (HO)	10W	10W / 14W / 16.5W / 24W
	CCT	2700 / 3000 / 4000K	2700 / 3000 / 4000K	Selectable 3000 / 3500 / 4000K
	CRI (min.)	90	90	90
	SDCM LED binning (max.)	3-Steps	4-Steps	3-Steps
	Lumen @30K	850 / 1150	600	750 / 1000 / 1250 / 2000
	Efficacy @30K	75LPW	60LPW	73/79/80/82LPW
	Beam	110°	110°	110°
	Jbox Installation	✓		✓
	Can Retrofit	✓		✓
	Direct Mount			✓
	Dimming Type	ELV / Triac	N.A	ELV / Triac & 0-10V
	Dimming Level	Down to 10% (min.)	N.A	Down to 10% (120V) and 5% (0-10V)
	Listing	ETL	ETL	ETL
	Lifetime	50,000hrs	50,000hrs	50,000hrs
	Warranty	5yrs	5yrs	5yrs
	Location	Dry, Damp and Wet	Dry, Damp and Wet	Dry, Damp and Wet
	Energy Star	✓	✓	✓
	Title 24	✓	✓	✓
	Air-Tight	✓	✓	✓
	Closet Rating	✓	✓	✓
Accessories	4 and 6" can retrofit		4 and 6" can retrofit, Spring Jbox Direct Mount, Black, Brushed Nickel and Bronze Trims	
Special Features	Integrated Sensor		PIR Motion - On/Off - 10 Minutes of Stand-by	
	SelectKelvin 			✓



INSTALLATION TYPE AND COMPATIBILITY

INSTALLATION TYPE					
			CLK	CLKSEN	3N1
Junction Box Installation		Octagonal 4x2-1/8"	✓ 6"	✓ 6"	✓ 5.5"/7"/9"/12"
		Round New Work ø4" & ø3-1/2"	✓ 6"	✓ 6"	✓ 5.5"/7"/9"/12"
		Round Old Work ø3-1/2"	✓ 6"	✓ 6"	✓ 5.5"/7"/9"/12"
		Round Surface Mount ø4"	✓ 6"	✓ 6"	✓ 5.5"/7"/9"/12"
		Non Metal-Cable 4x2-1/8"	✓ 6"	✓ 6"	✓ 5.5"/7"/9"/12"
Can Retrofit		4" Can (NC or Remodel)	✓ 6" with SMDL4/ACC		✓ 5.5" with 3N1/ACC/4CAN
		5" Can (NC or Remodel)	✓ 6" with SMDL6/ACC		✓ 7"/9" with 3N1/ACC/56CAN
		6" Can (NC or Remodel)	✓ 6" with SMDL6/ACC		✓ 7"/9" with 3N1/ACC/56CAN
Direct Mount		Proprietary Spring Junction Box			✓ 5.5"/7"/9" With 3N1/ACC/JBOX
Ceiling Height		600 lm to 850 lm	✓ 6"	✓ 6"	✓ 5.5"
		1,000 lm to 1,200 lm	✓ 6" HO		✓ 7"
		1,200 lm to 2,000 lm			✓ 9" and 12"