

SELECTFIT DOWNLIGHTS



GREENCREATIVE



FEATURES

- 4", 6", 8" & 9.5" fixture sizes
- Choose from either 3000K / 3500K / 4000K or 2700K / 5000K with SelectKelvin technology
- Selectable lumen output with SelectDrive technology
- 120V line voltage or 0-10V dimming available
- Ambient temperature range: -4°F to 95°F (-20°C to 35°C)
- Wet location, IC and Air-tight rated
- L70 rated lifetime of 50,000 hours

- ENERGY STAR® certified
- ETL listed and classified
- 5 year warranty



OFFICE



APPLICATIONS

- Commercial
- Education
- Office
- Retail



SELECFIT TECHNOLOGY AND BENEFIT

SELECTABLE CCT

Make retrofit projects easier with the SELECFIT commercial downlight family of fixtures. Select the CCT before, during or after installation with just the flip of a switch and never worry about having the correct CCT for a project again.

Select Kelvin



SELECTABLE OUTPUT

Get the right amount of light with SELECFIT, powered by SelectDrive technology. Choose either Low, Medium or High light output. With just the flip of a switch ensure that every space has just the right amount of light.

Select Drive

QUALITY, DURABILITY AND SIMPLICITY

SELECFIT fixtures are made with high quality materials for easy installation and long lasting durability. The heavy duty spring clips ensure a quick, tight fit to the ceiling. The seamless integration of heat sink, recessed reflector and opaque lens ensure a smooth, uniform beam of light from an IC, Air-tight and Wet location rated fixture, suitable for most commercial downlighting needs.



ORDERING

Series	Size	CRI	CCT	Dimming
<input checked="" type="checkbox"/> SLFT SELECFIT	<input type="checkbox"/> 4 4" 500 / 700 / 1000lm	<input checked="" type="checkbox"/> 80 CRI 80	<input type="checkbox"/> CCTS Selectable CCT 3000K / 3500K / 4000K	<input type="checkbox"/> DIM120V 120V - Line voltage dimming
	<input type="checkbox"/> 6 6" 700 / 1000 / 1500lm		<input type="checkbox"/> CCT2750* Selectable CCT 2700K / 5000K	<input type="checkbox"/> DIM010UNV 120-277V - 0-10V dimming
	<input type="checkbox"/> 8 8" 1000 / 1500 / 2000lm			
	<input type="checkbox"/> 9.5 9.5" 2000 / 2500 / 3200lm			

*AVAILABLE IN DIM010UNV ONLY

ACCESSORY ORDERING INFORMATION

Product	Model	Description
35157	SLFT/TRIM4/CC	4" Clear Trim Insert (Field Installation)
35158	SLFT/TRIM6/CC	6" Clear Trim Insert (Field Installation)
35159	SLFT/TRIM8/CC	8" Clear Trim Insert (Field Installation)
35160	SLFT/TRIM9.5/CC	9.5" Clear Trim Insert (Field Installation)
98569	GOOFRING4	4" Goof Ring - Outer Diameter 8-1/8"
98568	GOOFRING6	6" Goof Ring - Outer Diameter 10-1/2"
98567	GOOFRING8	8" Goof Ring - Outer Diameter 12-1/2"
98566	GOOFRING9.5	9.5" Goof Ring - Outer Diameter 14-3/16"
98501	NCPLATE/T4689	New Construction or Remodel Plate for T-Grid ceilings for use with 4", 6", 8" and 9.5" models
98502	NCPLATE468	New Construction Plate for Stud/Joist mounting for use with 4", 6" and 8" models
98583	NCPLATEJB	Additional J-Box for new construction plate installation
35121	NCFJB4	Round New Construction Frame w/ Jbox 4"
35122	NCFJB6	Round New Construction Frame w/ Jbox 6"
35123	NCFJB8	Round New Construction Frame w/ Jbox 8"
35124	NCFJB9.5	Round New Construction Frame w/ Jbox 9.5"
35125	NCFEMB	Emergency Bracket For New Construction Frame
35126	NCFBFB	Butterfly Brackets For New Construction Frame
58012	35EMINVERTER	35W Emergency Inverter for use with 4", 6" and 8" models only
58013	35EMINVERTER/CEC	California Title 20 Compliant 35W Emergency Inverter for use with 4", 6" and 8" models only
98003	23EMDRIVER	California Title 20 Compliant 23W Emergency LED Driver for use with 4", 6" and 8" models only
98235	50EMINVERTER	50W Emergency Inverter for use with 9.5" model